575130

Sandia National Laboratories
Waste Isolation Pilot Plant

Review of Conceptual Models for the Additional Panels Performance Assessment

Author:	Clifford Hansen	*Signature on File*	8812	4/27/2021
	Print	Signature	Org.	Date
Technical Review:	Todd Zeitler	*Signature on File*	8912	4/27/2021
	Print	Signature	Org.	Date
Technical Review:	Ross Kirkes	*Signature on File*	8881	4/27/2021
	Print	Signature	Org.	Date
Management Review:	Steve Wagner		8881	4/27/2021
	Print	Signature	Org.	Date
QA Review:	Shelly Nielsen		8880	4/27/2021
	Print	Signature	Org.	Date

Sandia National Laboratories

WIPP:04.09.03.01:PA:QA-L:572681:

Information Only

Contents

1 Introduction and Summary 6
2 Disposal System Geometry 9
2.1 Description in the CCA 9
2.2 Changes since the CCA 9
2.3 Effect of proposed repository changes 9
3 Culebra Hydrogeology 10
3.1 Description in the CCA 10
3.2 Changes since the CCA 11
3.3 Effect of proposed repository changes 12
4 Repository Fluid Flow 13
4.1 Description in the CCA 13
4.2 Changes since the CCA 13
4.3 Effects of proposed repository changes 14
5 Salado 15
5.1 Description in the CCA 15
5.2 Effect of proposed repository changes 15
6 Impure Halite 16
6.1 Description in the CCA 16
6.2 Effect of proposed repository changes 16
7 Salado Interbeds 17
7.1 Description in the CCA 17
7.2 Effect of proposed repository changes 18
8 Disturbed Rock Zone 19
8.1 Description in the CCA 19
8.2 Changes since the CCA 20
8.3 Effect of proposed repository changes 20
9 Actinide Transport in the Salado 21
9.1 Description in the CCA 21
9.2 Effect of proposed repository changes 22
10 Units Above the Salado 23
10.1 Description in the CCA 23

Information Only

10.1.1 The Unnamed Lower Member 23
10.1.2 The Tamarisk 23
10.1.3 The Magenta 23
10.1.4 The Forty-niner 24
10.1.5 The Dewey Lake 24
10.2 Effect of proposed repository changes 24
11 Transport of Dissolved Actinides in the Culebra 25
11.1 Description in the CCA 25
11.2 Effect of proposed repository changes 26
12 Transport of Colloidal Actinides in the Culebra 27
12.1 Description in the CCA 27
12.2 Effect of proposed repository changes 28
13 Exploration Boreholes 29
13.1 Description in the CCA 29
13.2 Changes since the CCA 31
13.3 Effect of proposed repository changes 32
14 Cuttings and Cavings 33
14.1 Description in the CCA 33
14.2 Changes since the CCA 33
14.3 Effect of proposed repository changes 34
15 Spallings 35
15.1 Description in the CCA 35
15.2 Changes since the CCA 35
15.3 Effect of proposed repository changes 35
16 Direct Brine Release 36
16.1 Description in the CCA 36
16.2 Changes since the CCA 37
16.3 Effect of proposed repository changes 37
17 Castile and Brine Reservoir 38
17.1 Description in the CCA 38
17.2 Changes since the CCA 38
17.3 Effect of proposed repository changes 39
18 Multiple Intrusions 40

Information Only

18.1 Description in the CCA 40
18.2 Effect of proposed repository changes 41
19 Climate Change 42
19.1 Description in the CCA 42
19.2 Effect of proposed repository changes 42
20 Creep Closure 43
20.1 Description in the CCA 43
20.2 Effect of proposed repository changes 44
21 Shaft and Shaft Seals 45
21.1 Description in the CCA 45
21.2 Changes since the CCA 46
21.3 Effect of proposed repository changes 46
22 Gas Generation 47
22.1 Description in the CCA 47
22.2 Changes since the CCA 47
22.3 Effect of proposed repository changes 48
23 Chemical Conditions 49
23.1 Description in the CCA 49
23.2 Changes since the CCA 51
23.3 Effect of proposed repository changes 51
24 Dissolved Actinide Source Term 52
24.1 Description in the CCA 52
24.2 Effect of proposed repository changes 52
25 Colloidal Actinide Source Term 54
25.1 Description in the CCA 54
25.2 Effect of proposed repository changes 56
26 References 57

Information Only

LIST OF ACRONYMS

AP	Analysis Plan
CARD	Compliance Application Review Document
CCA	Compliance Certification Application
CFR	Code of Federal Regulation
CMPR	Conceptual Model Peer Review
CRA	Compliance Recertification Application
DOE	Department of Energy
DBR	direct brine release
DRZ	disturbed rock zone
EPA	Environmental Protection Agency
FEP	feature, event, or process
PA	performance assessment
PCS	panel closure system
ROM	run-of-mine
WIPP	Waste Isolation Pilot Plant

Information Only

1 Introduction and Summary

This memorandum documents a review of conceptual models conducted while planning for the Additional Panels Performance Assessment (APPA). The plan for the APPA is documented in AP-185 [Hansen, 2020]. The review of conceptual models was not formally identified as an activity at the time AP-185 was issued.

Conceptual models are a set of qualitative assumptions used to describe a system or subsystem for a given purpose. At a minimum, these assumptions concern the geometry and dimensionality, initial and boundary conditions, time dependence, and the nature of the relevant physical and chemical processes associated with the disposal system. The assumptions should be consistent with one another and with existing information within the context of the given purpose. (US DOE, 1996, Section 6.4.1).

Conceptual models are derived from features, events, and processes (FEPs) that are deemed important to repository performance and guide the development of mathematical models for the repository system. Mathematical models comprise a set of equations that relate various physical quantities. Mathematical models are implemented in numerical models that approximate the solution to the mathematical model's equations; calculations are conducted using computational models (codes) that implement the numerical models.

The 24 WIPP conceptual models are identified in Table 1. Conceptual models were established at the time of the Compliance Certification Application (CCA). Several models have been modified since the CCA, as documented in Compliance Recertification Applications (CRAs).

Table 1. Conceptual models for the WIPP performance assessment

Conceptual Model	Description in the CCA (U.S. DOE, 1996)	Changes since the CCA
Disposal System Geometry	Section 6.4.2.1 Appendix PEER 1, Section 3.1.1	CRA-2004, Section 6.0.2.3.2 CRA-2004 CRA, Appendix PA, Section 4.6 CRA-2004, Appendix PEER 1, Section 3.1.2 CRA-2014, Section 44.6.2.2 CRA-2019, Appendix PA, Section PA-1.1
Culebra Hydrogeology	Section 6.4.6.2	CRA-2004, Appendix PA, Attachment TFIELD CRA-2014, Appendix TFIELD
Repository Fluid Flow	Section 6.4.3.2	CRA-2004, Section 6.0.2.3.2 CRA-2004, Appendix PA, Section 4.6 CRA-2004, Appendix PEER 1, Section 3.1.2 CRA-2014, Section 44.6.2.2 CRA-2019, Appendix PA, Section PA-1.1
Salado	Section 6.4.5	None

Information Only

Conceptual Model	Description in the CCA (U.S. DOE, 1996)	Changes since the CCA
Impure Halite	Section 6.4.5.1	None
Salado Interbeds	Section 6.4.5.2	None
Disturbed Rock Zone	Section 6.4.5.3 Appendix PEER 1, Section 3.7.1	CRA-2004, Section 6.0.2.3.2 CRA-2004, Appendix PA, Section 4.6 CRA-2004, Appendix PEER 1, Section 3.1.2
Actinide Transport in the Salado	Section 6.4.5.4 Appendix PEER 1, Section 3.8.1	None
Units Above the Salado	Section 6.4.6 Appendix PEER 1, Section 3.9.1	None
Transport of Dissolved Actinides in the Culebra	Section 6.4.6.2.1	None
Transport of Colloidal Actinides in the Culebra	Section 6.4.6.2.2	None
Exploration Boreholes	Section 6.4.7 Appendix PEER 1, Section 3.12.1	CRA-2004, Section 6.4.7.2.1
Cuttings and Cavings	Section 6.0.2.3.1	CRA-2004, Appendix PA, Attachment PAR, Section PAR 7.0 (Parameter 58) CRA-2014, Appendix PA, Section PA-1.1.5 CRA-2019, Appendix PA, Section PA-1.1.6.
Spallings	Section 6.4.7.1	CRA-2004, Section 6.0.2.3.2 CRA-2004, Appendix PA, Section 4.6 CRA-2004, Appendix PEER 1, Section 3.1.2
Direct Brine Release	Section 6.4.7.1	CRA-2009, Appendix PA, Section PA-2.11
Castile and Brine Reservoir	Section 6.4 8	CRA-2004, Section 6.0.2.3.8 CRA-2004, Section 6.4.8 CRA-2019, Appendix PA, Section PA-1.1.4
Multiple Intrusions	Appendix PEER 1, Section 3.17.1 Sections 6.3.2.2 6.4.12.3, 6.4.13.3, 6.4.13.4 and 6.4.13.5	None
Climate Change	Section 6.4. 9	None
Creep Closure	Section 6.4.3.1 Appendix PEER 1, Section 3.19.1	None
Shaft and Shaft Seals	Section 6.4.4	CRA-2004, Section 6.4.4

Information Only

Conceptual Model	Description in the CCA (U.S. DOE, 1996)	Changes since the CCA
		CRA-2019, Section 15.3.4.4 CRA-2019, Appendix PA, Section PA-1.1.2
Gas Generation	Section 6.4.3.3	CRA-2009, Appendix PA, Section PA-2.1.1 CRA-2014, Appendix PA, Section PA-1.1.8 CRA-2019, Appendix PA, Section PA-1.1.3
Chemical Conditions	Appendix PEER 1, Section 3.22.1 Section 6.4.3.4	CRA-2009, Appendix SOTERM, Section SOTERM-2.4.1.1 CRA-2014, Appendix PA, Section PA-4.2.5
Dissolved Actinide Source Term	Section 6.5.3.5 Appendix PEER 1, Section 3.23.1	None
Colloidal Actinide Source Term	Section 6.4.3.6 Appendix PEER 1, Section 3.24.1	None

Each conceptual model (in its current state) is reviewed to determine if the model's assumptions or implementation would be affected by the proposed additional panels. The review concluded that the following conceptual models are affected by the proposed changes to the repository:

- Disposal System Geometry
- Repository Fluid Flow
- Direct Brine Release

In addition, the review identified one conceptual model, the conceptual model for Actinide Transport in the Salado, as being indirectly affected by the proposed additional panels. The implementation of the Actinide Transport in the Salado conceptual model relies on the numerical models which implement the Disposal System Geometry and Repository Fluid Flow conceptual models. However, the features and processes that comprise the Actinide Transport in the Salado conceptual model are not directly affected by the proposed additional panels.

The remaining conceptual models were judged to be unaffected by the proposed repository changes.

Information Only

2 Disposal System Geometry

2.1 Description in the CCA

The Disposal System Geometry conceptual model is described in U.S. DOE (1996):

> *The Disposal System Geometry conceptual model expresses the dimensionality of the engineered system and surrounding geologic/hydrogeologic formations. The parameters of dimensionality are length, width, and height, which are expressed in individual grid blocks and remain constant for all scenarios and realizations. The processes that rely on the geometric assumptions and parameters of dimensionality are represented across the overall performance assessment system through a finite difference mathematical model called BRAGFLO. The principal processes that depend on the conceptual model for disposal system geometry are fluid flow and actinide transport.* (U.S. DOE, 1996, Appendix PEER 1, Section 3.1.1)

2.2 Changes since the CCA

In 2003, during preparation for the 2004 Compliance Recertification Application (CRA-2004), the Salado Flow Peer Review considered and concurred with changes to repository modeling which involved the Disposal System Geometry conceptual model. These changes included: specifying the "Option D" panel closure system; adjusting properties of the Disturbed Rock Zone (DRZ) and nearby halite and anhydrite materials to represent potential flow around repository shaft and panel closure features; replacement of the original 11-layer shaft seal model with a simplified two-layer system (U.S. DOE, 2004, Appendix PEER 1, Section 2.1.1).

In preparation for the 2014 Compliance Recertification Application, (CRA-2014) the U.S. DOE changed the panel closure system design from the "Option D" PCS to the run-of-mine salt panel closure system (ROMPCS) (U.S. DOE, 2014, Section 44.6.2.2).

In preparation for the 2019 Compliance Recertification Application (CRA-2019), , the U.S. DOE made the following changes to the model of the repository that affect the Disposal System Conceptual model (U.S. DOE, 2019, Appendix PA, Section PA-1.1):

- Removal of the PCS associated with the entrances of Panels 3, 4, 5 and 6.
- Abandonment of emplacement of waste in Panel 9.
- Inclusion of a fifth shaft (see the Shaft and Shaft Seals conceptual model).

2.3 Effect of proposed repository changes

The dimensionality of the excavated volume of the repository and the arrangement of waste panels is affected by the proposed additional panels. The mathematical models for repository dimensionality are not affected, but their implementation in the numerical and computational models is affected. A new grid which represents the volume of the new panels and the separation of the new panels from existing repository features is necessary. The processes of fluid flow and actinide transport are not affected in their conceptual, mathematical, numerical or computational forms.

Information Only

3 Culebra Hydrogeology

3.1 Description in the CCA

The Culebra hydrogeology conceptual model is described in U.S. DOE (1996).

> *The Culebra is conceptualized as a horizontal, confined aquifer. For fluid flow, it is conceptualized as a heterogeneous porous medium which is represented by variations in transmissivity. A heterogeneous velocity field is used for transport calculations, but all other rock properties are conceptualized as constant (homogeneous) across the model area. The Culebra is conceptualized as having two types of porosity; a portion of the porosity is associated with high-permeability features where transport occurs by advection, and the rest of the porosity is associated with low-permeability features where flow does not occur and retardation occurs by physical processes (diffusion) and chemical processes (sorption). This type of conceptual model is commonly referred to as double-porosity. In this conceptual model, transport and retardation of colloidal particles is also considered. In this section, the principal topic will be fluid flow in the Culebra. The transport and retardation of dissolved actinides will be discussed principally in Section 6.4.6.2.1. The transport and retardation of colloidal particles will be discussed principally in Section 6.4.6.2.2.*
>
> *In the Culebra conceptual model used in performance assessment, the spatial distribution of transmissivity in the Culebra is important. Other potentially important processes acting on Culebra flow and transport are climate change (Section 6.4.9 and Appendix MASS, Section MASS.17) and the effects of subsidence caused by potash mining in the McNutt (Section 6.4.6.2.3 and Appendix MASS, Section MASS.15.4).*
>
> *The conceptual model for the Culebra assumes that fluid fluxes and directions in the future will be the same as they are projected to be at repository closure, unless future mining within the site occurs, in which case changes to fluid flow are calculated. A steady-state flow field is used to represent this assumption. Conditions assumed at site closure are the subsidence effects of mining in the near future outside the site boundary, climate change, and a reasonable estimate of the hydraulic conditions that existed prior to disturbances to the Culebra caused by site characterization activities (see Appendix MASS, Sections MASS.15.4 and MASS.14.2), and Appendix TFIELD, Section TFIELD.2.2).*
>
> *The factors controlling fluid flow in the Culebra are conceptualized to be the hydraulic gradient, transmissivity distribution, and porosity. The hydraulic gradient and transmissivities used in performance assessment are coupled because they are calibrated to observed conditions by a process described in Appendix TFIELD (Section TFIELD.3). Flow fields are calculated with the code SECOFL2D using an assumption of homogeneous porosity in the Culebra. This single value is the total porosity for the Culebra, including both advective and diffusive porosity, as discussed below. Use of a single porosity for the flow calculation does not introduce inconsistency with transport calculations because (1) steady-state flow fields are used so flux through the system is not dependent on porosity, and (2) the velocity of liquid for transport is calculated based on a double-porosity model implemented in the code SECOTP2D. Thus, the important factors for flow*

Information Only

> *calculations are the hydraulic gradient and transmissivity variation.* (U.S. DOE, 1996, Section 6.4.6.2)

The Conceptual Model Peer Review (CMPR), conducted at the time of the CCA, found the Culebra hydrogeology model to be "inadequate to define variations in the transmissivity of the Culebra at the site scale" (U.S. DOE, 1996, Appendix PEER 1, Section 3.2.2.5). In the PA conducted for the CCA, Culebra transmissivity (T) fields were instead produced by "a numerical model based on extensive hydrogeologic testing" (U.S. DOE, 1996, Appendix PEER 1, Section 3.2.2.9). The CMPR determined that the Culebra hydrogeology conceptual model's "inadequacy was inconsequential for performance assessment because an extensive hydrologic data base was developed and serves as an adequate substitute to support numerical modeling" (U.S. DOE, 1996, Appendix PEER 1, Section 6.0). The numerical model that produced the T-fields used in the CCA relied on measured transmissivities and water levels in nearby boreholes.Although not formally named as such, the conceptual model for the effects of subsidence caused by potash mining is described along with the conceptual model for Culebra hydrogeology. The occurrence of future mining within the controlled area is represented by the Disturbed Performance Mining (M) Scenario:

> *Consistent with the criteria stated by the EPA in 40 CFR § 194.32 (b), for performance assessment calculations, the effects of potential future mining within the controlled area are limited to changes in hydraulic conductivity of the Culebra that result from subsidence (as described in Section 6.4.6.2.3).* (U.S. DOE, 1996, Section 6.3.2.1).

> *Subsidence effects caused by potash mining are included in this performance assessment because of specific criteria in the EPA's 40 CFR Part 194. For incorporating the effects of subsidence caused by mining, the DOE uses the conceptual model provided by the EPA in 40 CFR Part 194 and supporting documents.* (U.S. DOE, 1996, Section 6.4.6.2.3).

3.2 Changes since the CCA

In preparation for the CRA-2004, the methodology used to develop and calibrate the Culebra T-fields was changed (U.S. DOE, 2004, Appendix PA, Attachment TFIELD, Section TFIELD-1.0). The revised methodology incorporated data not available or used for the CCA, including dissolution of the upper Salado Formation, the thickness of overburden above the Culebra, and the spatial distribution of halite in the Rustler Formation above and below the Culebra. During its review of the CRA-2004, the U.S. EPA required the U.S. DOE to modify the approach taken to include the effects of mining (U.S. EPA, 2006c, Section 8.2.3). The U.S. EPA determined that the revised methodology "was based on generally accepted approaches, which the EPA considers as adequate" (U.S. EPA, 2006b, Section V).

In 2008, the Culebra Hydrogeology Conceptual Model peer review was conducted to review the conceptual approach to producing Culebra T-fields (Burgess, 2008). The peer review described the conceptual approach under review as:

> *The objective of the RCHCM is to provide a suite of transmissivity fields (T-fields) for the Culebra that are:*
>
> - *Geologically based,*
> - *Consistent with observed groundwater heads,*

Information Only

> • *Consistent with groundwater responses in the Culebra to pumping tests, precipitation, and anthropogenic impacts, and*
>
> • *Consistent with water chemistry*

The peer review concluded that "*the RCHCM* (revised Culebra hydrogeology conceptual model) *is adequate to develop T-fields for application in the site flow model*" although the panel noted three weaknesses in the RCHCM (Burgess, 2008, Section 8):

- lack of demonstration of consistency between flow patterns and geochemistry
- lack of consistency between basin-wide and T-field models as related to the method of handling vertical flow
- incomplete understanding of the basis of certain correlations employed in the RCHCM.

In preparation for the CRA-2014, the Culebra T-fields were re-calculated to take into account additional data available since the CRA-2004 (U.S. DOE, 2014, Appendix TFIELD, Section TFIELD-3.0.

3.3 Effect of proposed repository changes

The existing excavated areas of the repository are not conceptualized as affecting regional fluid flow, hydraulic gradients, or transmissivity in the Culebra. Subsidence caused by excavations at the repository horizon remains screened out of the performance assessment on the basis of low consequence (Kirkes, 2021). Effects of subsidence due to future potash mining are limited to changes in the hydraulic conductivity of the Culebra. Thus, the proposed additional waste panels would not affect the Culebra hydrogeology conceptual model nor the conceptual model for subsidence caused by future potash mining.

Information Only

4 Repository Fluid Flow

4.1 Description in the CCA

The repository fluid flow conceptual model is described in U.S. DOE (1996).

> *Fluid flow modeling within the repository is concerned with (1) fluid flow and distribution in the waste, (2) fluid flow to and from the Salado and shafts, and (3) fluid flow between the repository and intrusion boreholes. These are important in assessing gas generation rates (Section 6.4.3.3), repository pressure, and the mobility of radionuclides in the disposal system. Additional discussion of this topic is provided in Appendix MASS (Section MASS.7).*
>
> *Disposal region fluid flow is affected by the geometrical association of pillars, rooms, drifts, panel closures, possible borehole locations, the time-dependent properties of waste areas resulting from creep closure, flow interactions with other parts of the disposal system, and reactions that generate gas. As described in Section 6.4.3.1, creep closure changes disposal region porosity. Depending on material properties and conditions, brine may flow into the disposal region by moving down shafts and through the DRZ or operations region, or during disturbed conditions, through a borehole. Brine contained in the Salado may flow to the waste disposal region because of pressure gradients created by the excavation. Brine flow into the repository may be reduced as repository pressure increases, and brine may be expelled from the repository if pressure in the repository exceeds brine pressure in the immediately surrounding rock or borehole. Gas may be generated as waste decomposes, causing a pressure increase. Gas may flow away from the waste into lower pressure areas, which may include disturbed areas surrounding the repository, the interbeds, the shafts, or an intrusion borehole. Gas flow into intact, halite-rich rock is not expected because of the expected high threshold pressure of halite (see Section 6.4.5.1).*
>
> *Fluid flow in the disposal system is conceptualized using principles of multiphase flow, except for Culebra flow and transport modeling. In multiphase flow, a residual brine saturation (Sbr), is defined, which is the minimum saturation at which the brine phase has a nonzero relative permeability; below this saturation brine is immobile. In accordance with two-phase flow theory, the residual gas saturation (Sgr) in the disposal system corresponds to the gas saturation necessary to create an incipient gas-phase relative permeability; below this saturation waste-generated gas is immobile. The multiphase flow techniques adopted by the DOE are described in Appendix BRAGFLO (Section 4.8).* (U.S. DOE, 1996, Section 6.4.3.2).

4.2 Changes since the CCA

In 2003, during preparation for the CRA-2004, the Salado Flow Peer Review considered and concurred with changes to repository modeling which involved the Repository Fluid Flow conceptual model. These changes included: specifying the “Option D” panel closure system (PCS) (U.S. DOE, 1996, Appendix PCS); adjusting properties of the Disturbed Rock Zone (DRZ) and nearby halite and anhydrite materials to represent potential flow around repository shaft and panel closure features; replacement of the original 11-layer shaft seal model with a simplified two-layer system (U.S. DOE, 2004, Appendix PEER 1Appendix PEER 1 1, Section 2.1.1).

Information Only

In preparation for the CRA-2014, the U.S. DOE changed the panel closure system design from the "Option D" PCS to the run-of-mine salt panel closure system (ROMPCS) (U.S. DOE, 2014, Section 44.6.2.2).

In preparation for the CRA-2019 , the U.S. DOE made the following changes to the model of the repository that affect the Disposal System Conceptual model (U.S. DOE, 2019, Appendix PA, Section PA-1.1):

- Removal of the PCS associated with the entrances of Panels 3, 4, 5 and 6.
- Abandonment of emplacement of waste in Panel 9.
- Inclusion of a fifth shaft (see the Shaft and Shaft Seals conceptual model).

4.3 Effects of proposed repository changes

The dimensionality of the excavated volume of the repository and the arrangement of waste panels is affected by the proposed additional panels. As a consequence, the numerical and computational models which implement the repository fluid flow conceptual model are affected. A new grid which represents the volume of the new panels and the separation of the new panels from existing repository features is necessary. The processes of two-phase flow, gas generation and creep closure are not affected in their conceptual, mathematical, numerical or computational forms.

Information Only

5 Salado

5.1 Description in the CCA

The Salado conceptual model is described in U.S. DOE (1996).

> *The Salado Formation is the principle barrier between the waste and the environment and is the primary source of brine flowing into the repository. The conceptual model supports estimates of hydrologic processes and properties, as well as mechanical behavior of the halite-rich rocks of the Salado Formation.*
>
> *The layering and composition of the Salado impact the mechanical processes of room closure and the hydrologic processes (both gas and brine) that accompany room closure. A detailed stratigraphy, which defines the distribution of mechanical properties and processes, has been developed for use with the MD model (Munson et al. 1989). Christian-Frear and Webb (1996) asserts that a simplified model containing only impure halite and interbeds is sufficient for hydrologic considerations.*
>
> *Three flow mechanisms have been proposed based on the varied, mostly qualitative data about flow into the repository (Howarth et al. 1995). These are: 1) far-field flow in response to potentiometric gradients resulting from excavation through naturally interconnected pore spaces; 2) redistribution of pore fluids (pores not necessarily originally interconnected) due to fracture and creep around the excavations; and 3) flow due to consolidation of water-bearing clay layers. None of these mechanisms can be eliminated on the basis of the existing evidence, so an inflow model combining the estimated volumes of brine from each mechanism is proposed. No consideration of the role of brine included in halite crystals is mentioned, although fracturing and some intracrystalline creep mechanisms may liberate brine from this source.* (U.S. DOE, 1996, Appendix PEER 1, Section 3.4.1).

5.2 Effect of proposed repository changes

The proposed additional panels are similar in design to the existing waste panels and are located at approximately the same horizon as the existing waste panels. It is expected that the Salado surrounding the proposed additional panels will be similar to that around the existing panels. Thus, the additional panels do not present any new interactions with the Salado which have not been previously considered. Hence, the Salado conceptual model is unaffected by the proposed additional panels.

Information Only

6 Impure Halite

6.1 Description in the CCA

The impure halite conceptual model is described in U.S. DOE (1996). All halite rocks within the Salado are modeled as impure halite. The impure halite conceptual model

> *...explains the role of impurities in influencing the mechanical and hydraulic properties assumed for the halite-rich rocks of the Salado. The model supports the treatment of the distribution and stratigraphy of impurities in the Creep Closure and Salado conceptual models*. (Appendix PEER 1 Section 3.5.1, U.S. DOE 1996).

> *The DOE uses a single porous medium with spatially constant rock and hydrologic properties (Region 19 in Figures 6-13 and 6-14) in performance assessment to represent intact, halite-rich layers in the Salado and minor interbeds contained within those layers that are not explicitly represented. A comparison has been made between the simplified stratigraphy used in the performance assessment model and a model with a more detailed stratigraphy in the vicinity of the repository; this comparison supports use of the stratigraphic representation used for performance assessment. This model comparison is described in Christian-Frear and Webb (1996)*. (U.S. DOE, 1996, Section 6.4.5.1).

6.2 Effect of proposed repository changes

The proposed additional panels have no effect on the presence or influence of impurities in halite, and thus the impure halite conceptual model is unaffected.

Information Only

7 Salado Interbeds

7.1 Description in the CCA

The Salado interbeds conceptual model is described in U.S. DOE (1996) by means of text found in Appendix PEER 1 Section 3.6:

> *Three distinct anhydrite interbeds are modeled: representing MB138, anhydrite layers a and b, and MB139. The three intact interbeds have the same set of model parameters, and the parameters are initially spatially constant. Porosity and permeability can vary spatially during a simulation depending on the extent of interbed fracturing. The interbeds differ only in position and thickness.*
>
> *The three interbeds are explicitly represented because they exist in the disturbed region around the repository within which fluid is expected to be able to flow with relative ease compared to the surrounding formation. MB139 and anhydrite layers a and b are present within the disturbed rock zone (DRZ) that forms around excavations. MB138 is included along with a thick DRZ because of uncertainty in the extent and properties of the DRZ and the associated long-term isolation of MB138 from the repository.*
>
> *Brine flows between the Salado and the repository in response to fluid potential gradients that may form over time. Because of the low permeability of the impure halite and relatively small surface area involved, direct brine flow between the impure halite and the repository is relatively small. The interbeds, however, can serve as conduits for brine flow between the impure halite and the repository. Conceptually, brine flows laterally along higher permeability interbeds towards or away from the repository and vertically between the interbeds and the lower permeability halite. Because the interbeds have a very large contact area with adjacent halite-rich rock, even a very small flux from the halite into the interbeds (for brine inflow) or to the halite from the interbeds (for brine outflow) can accumulate into a significant quantity of brine. In this manner, halite serves as a source or sink for brine in the repository.*
>
> *Interbeds contain natural fractures that may be partially healed. If high pressure is developed in an interbed, its preexisting fractures may dilate or new fractures may form, altering its porosity and permeability. Pressure-dependent changes in permeability are supported by experiments conducted in the WIPP underground and in the laboratory (Beauheim et al. 1993). Accordingly, the DOE has implemented a porous-media model of interbed dilation and fracturing that causes the porosity and permeability of a computational cell in an interbed to increase as its pore pressure rises above a threshold value. Model details are presented in Appendix BRAGFLO (Section 4.10) and Appendix MASS (Section MASS.13.3). To the extent that it occurs, dilation or fracturing of interbeds is expected to increase the transmissivity of interbed intervals. The threshold pressure of dilated or fractured interbeds is expected to be low because apertures of the fractures increase; thus, fluid is expected to be able to flow outward readily if adequate pressure is available to dilate the interbeds.*
>
> *The model used to simulate the effects of interbed dilation or fracturing is explained in detail in Appendix BRAGFLO (Section 4.10). In summary, it assigns a fracture initiation pressure above the initial pressure at which local fracturing takes place, and changes in permeability and*

Information Only

> *porosity occur above this pressure. Below this fracture initiation pressure, an interbed has the permeability and compressibility assigned by LHS and representative of intact rock. Below the fracture initiation pressure, the initial sampled porosity is modified slightly with pressure caused by compressibility. Above the fracture initiation pressure, the local compressibility of the interbed is assumed to increase linearly with pressure. This greatly increases the rate at which porosity increases with increasing pore pressure. Additionally, permeability increases by a power function of the ratio of altered porosity to initial porosity. For numerical reasons (that is, to prevent unbounded changes in parameter values that would create numerical instabilities in codes), a pressure is specified above which porosity and permeability change no further.* (U.S. DOE, 1996, Appendix PEER 1, Section 3.6).

7.2 Effect of proposed repository changes

The proposed additional panels are located at approximately the same horizon as the existing waste panels (Sjomeling, 2019), and it is expected that the proposed additional panels will interact with the Salado interbeds in a similar manner as the existing panels. Hence, the Salado interbeds conceptual model is unaffected by the proposed additional panels.

Information Only

8 Disturbed Rock Zone

8.1 Description in the CCA

The disturbed rock zone conceptual model is described in U.S. DOE (1996).

> *The Disturbed Rock Zone model consists of a description of a fracture zone surrounding excavations that is created by induced stresses. At the WIPP, the primary DRZ exists in all rocks; the secondary DRZ is applicable only in viscoelastic rocks such as halite. The DRZ varies in depth away from the excavation and has been reported to be up to 50 m deep for large excavations. It exists in the repository roof, floor, and walls, and around shaft and borehole walls. Because of the distinctly different stress fields in each of these locations, the DRZ can have different properties at each location. For example, it is considered to disappear under appropriate conditions and with time in the borehole seals program, and is variously applied as it relates to the repository rooms and panels. Related models include Creep Closure, Shafts and Shaft Seals, Disposal Room Geometry, Repository Fluid Flow, Salado, and Salado Interbeds.*
>
> *Induced changes to the stress field occur immediately on the passage of mining equipment during excavation. In halite, as the salt adjusts to these changes through the creep process, further micro- and macro-fracturing progressively occur in the intact rock, adding to a fracture region known as the DRZ. This DRZ was first technically addressed and demonstrated by Borns et al. (1987, 1988, 1989, 1990). Van Sambeek et al. (1993) have referred to the mining-induced fractures as the initial DRZ and the progressive fracturing as the secondary DRZ. In this analysis, the Panel will not distinguish between these except for their applications. The characteristics of the DRZ include increased rock volume and permeability and decreased brine saturation due to drainage and drying, load bearing capacity, and lithostatic pressure. Clearly these properties could lead to the DRZ providing flow paths for fluids and gases from the repository to those zones that might carry them to the accessible environment. Studies by Munson et al. (1994) have characterized the DRZ and found it to be irregular in thickness and fracturing and able to heal with time under an applied confinement. Two versions of a creep model, applicable to room closure and DRZ development, have been formulated during this period. These are a model that includes both transient primary creep and steady state creep (MD model), which has been used in the porosity surface lookup table calculation of repository void space, and the MD model, with added tertiary creep fracture (MDCF), used to confirm DRZ thickness, fracture porosity, and healing characteristics. The MD model is central to the porosity surface calculation (SANTOS), which relates creep, waste compaction, and gas pressure to overall room closure rate. The DRZ is not considered in room closure calculations since all DRZ fracture porosity is assumed to be recovered by healing at final closure. For the waste room, the DRZ model is incorporated by assuming a high permeability and low porosity, with the result that the DRZ is unable to act as a constraint to brine or gas flow from the repository rooms and is unable to store brine. A primary reason for this approach is the uncertain behavior of the rock zone, which is dependent on many uncontrollable factors.* (U.S. DOE, 1996, Appendix PEER 1, Section 3.7.1).

Information Only

8.2 Changes since the CCA

In 2003, during preparation for the CRA-2004, the Salado Flow Peer Review considered and concurred with changes to repository modeling which involved the Disturbed Rock Zone conceptual model. These changes included: specifying the "Option D" panel closure system; adjusting properties of the Disturbed Rock Zone (DRZ) and nearby halite and anhydrite materials to represent potential flow around repository shaft and panel closure features; replacement of the original 11-layer shaft seal model with a simplified two-layer system. (U.S. DOE, 2004, Appendix PEER 1, Section 2.1.1).

8.3 Effect of proposed repository changes

The proposed additional panels are similar in design to the existing waste panels and are located at approximately the same horizon as the existing waste panels. It is expected that the Salado surrounding the proposed additional panels will be similar to that around the existing panels. Thus, the disturbed rock zone conceptual model is not affected by the proposed additional panels.

Information Only

9 Actinide Transport in the Salado

9.1 Description in the CCA

The conceptual model for actinide transport in the Salado is described in U.S. DOE (1996):

> *The only transport mechanism that will be used in this conceptual model is advection. The Actinide Transport in the Salado conceptual model previously addressed three mechanisms: 1) advection (transport with bulk flow of liquid); 2) dispersion (liquid velocity differences while moving through pores or surface irregularities); and 3) diffusion (molecular motion in presence of concentration gradients). These mechanisms are all standard contaminant transport phenomena. DOE assumed that these three transport mechanisms of actinides in brine represented the most important processes of actinide movement in the Salado Formation. All three mechanisms look at the transport of dissolved or colloidal actinides through the anhydrite interbeds (MB 138, MB 139, and anhydrite interbeds a and b).*
>
> *Three physical influences that may affect actinide transport in the interbeds have been left out of the conceptual model by DOE to promote a conservative philosophy. These influences are sorption of dissolved actinides on clays, retardation of colloidal actinides by surface features, and mineral precipitation containing trace actinides from brine. Sorption of actinides onto clay surfaces is a known reaction, and DOE is highly confident that it will occur; however, the model conservatively neglects the effect. With regard to retardation of colloidal actinides by surface features, it is assumed that offsetting interactions will occur. The philosophy is that colloids can be retarded by surficial features, but will travel faster than the average velocity of the bulk liquid. Precipitation of minerals as brines move into the interbeds due to chemical gradients is a possibility. Given the concept that the amount of precipitation will be minor, and that actinides will only occur in trace amounts in the crystal structures, DOE has decided to neglect this effect in the performance assessment.*
>
> *Three other mechanical processes may have a lesser impact on actinide transport in the Salado. These are fracture flow, channeling, and viscous fingering. Fracture flow is accounted for in the Salado Interbed model and takes into account increased porosity and permeability through fracture propagation and dilation. DOE expects that other fracture processes and effects not taken into account in the fracture model will be negligible. One process not incorporated, channeling, has offsetting effects. Channeling is the fluid movement through large apertures of a fracture network (i.e., locally high permeability). DOE believes this mechanism will be negated for two reasons. First, if gas is present in the undisturbed state, it will preferentially occupy areas of high permeability over brine. This will preclude these regions of fast transport from brines. Second, the incoming brine will be miscible with the interbed brine. Such miscibility will allow diffusion and mixing phenomena to broaden finger fronts (i.e., reduce concentration gradients) until they are indistinguishable from the advancing brine front.*
>
> *Gases may also penetrate interbed brines as a fingered front. However, such a mechanism will not affect actinide transport because the actinides of interest are only incorporated in the liquid phase. DOE also assumes that a liquid will not displace gases in the high-permeability regions (channels) due to capillary effects. (*U.S. DOE, 1996, Appendix PEER 1, Section 3.8.1).

Information Only

9.2 Effect of proposed repository changes

The proposed additional panels are similar in design to the existing waste panels and are located at approximately the same horizon as the existing waste panels. It is expected that the Salado surrounding the proposed additional panels will be similar to that around the existing panels. However, the implementation of the conceptual model for actinide transport in the Salado relies on flow fields calculated by the implementations of the Disposal System Geometry and Repository Fluid Flow conceptual models. Thus, the conceptual model for actinide transport in the Salado is indirectly affected by the proposed additional panels.

Information Only

10 Units Above the Salado

10.1 Description in the CCA

Units above the Salado include, in order from lower to higher: the unnamed lower member, the Culebra, the Tamarisk, the Magenta, the Forty-niner, the Dewey Lake, and the units above the Dewey Lake. A fundamental assumption in the conceptual model for units above the Salado is that lateral actinide transport through these formations within the next 10,000 years is possible only in the Culebra (U.S. DOE, 1996, Section 6.4.6). As a consequence, the conceptual model for Culebra hydrogeology is described separately.

The conceptual model for units above the Salado defines the hydrogeologic properties that govern flow and actinide transport in these units.

10.1.1 The Unnamed Lower Member

In performance assessment, this member is treated as impermeable, which prevents liquid flow and actinides from entering this unit. The DOE assumes that because of the low permeability of the unnamed lower member, any brine entering it adjacent to an intrusion borehole would be contained well within the site boundary for more than 10,000 years. Therefore, this treatment is conservative, regarding estimated releases into the Culebra, because allowing flow from a borehole or shaft into the unnamed lower member would, if anything, decrease flow into the Culebra. This would have a tendency to reduce the release of actinides from the Culebra to the accessible environment. In performance assessment, the thickness of the unnamed lower member is 118 feet (36 meters), and its permeability is zero. (U.S. DOE, 1996, Section 6.5.6.1).

10.1.2 The Tamarisk

In performance assessment, this member is treated as impermeable. This may cause an increase in flow through the adjacent Culebra and Magenta. This treatment is considered conservative in that allowing flow from the intrusion borehole or shaft into the Tamarisk would, if anything, decrease flow into the Culebra, which would tend to reduce the consequence of radionuclide release to the Rustler. In performance assessment, the thickness of the Tamarisk is assumed to be 81.4 feet (24.8 meters) and its permeability is effectively zero (Appendix PAR, Table PAR-29). (U.S. DOE, 1996, Section 6.5.6.3).

10.1.3 The Magenta

Transport of actinides through the Magenta to the accessible environment is not modeled. The assumption that no releases will occur from the Magenta is based on the hydraulic test results from wells on the WIPP site (Beauheim 1987, 110-118) that indicate that the Magenta is a porous medium with no hydraulically significant fractures (in contrast to the Culebra) and that its conductivity is lower than that of the Culebra. Early numerical simulations of flow and transport in the Magenta suggested much slower transport than in the Culebra (Barr et al. 1983, 26-27). Therefore, no radionuclides entering the Magenta will reach the accessible environment boundary within the 10,000-year time frame. Accordingly, the BRAGFLO model geometry reasonably approximates the effects of Magenta flow. The Magenta permeability is chosen conservatively as the lowest of measured values near the center of the WIPP site, in order to

Information Only

yield a lower reasonable amount of brine (and radionuclide) storage within the Magenta, while continuing to yield an upper bounding flow into the Culebra. (U.S. DOE, 1996, Section 6.4.6.4).

10.1.4 The Forty-niner

As with the Tamarisk and unnamed lower members, the Forty-niner is assigned a permeability of effectively zero in performance assessment (Appendix PAR, Table PAR-27). This treatment is considered conservative in that allowing flow from the intrusion borehole or shaft into the Forty-niner would, if anything, decrease flow into the Culebra, which would tend to reduce the consequence of radionuclide release to the Rustler. Its modeled thickness is 56.8 feet (17.3 meters). (U.S. DOE, 1996, Section 6.4.6.5).

10.1.5 The Dewey Lake

Release of actinides to the accessible environment from transport in the Dewey Lake is assumed not to occur even if contaminated brine reaches the unit because the sorptive capacity of this unit appears large. This assumption is based on an analysis (Wallace et al. 1995) that demonstrated that the potential sorption capacity of the Dewey Lake is sufficient to prevent releases for 10,000 years. This analysis consisted of (1) a literature review of sorptive capacity of redbeds and (2) an estimate of the minimum sorption required to prevent release of actinides that enter the Dewey Lake to the accessible environment in 10,000 years. Comparison of the sorption values for the Dewey Lake analogues established by literature review with the minimum sorption required to prevent release indicates that the likely sorptive capacity of the Dewey Lake is orders of magnitude greater than would likely be required to prevent release. Therefore, the DOE assumes that chemical retardation occurring in the Dewey Lake will prevent release within 10,000 years of any actinides that might enter it. (U.S. DOE, 1996, Section 6.5.6.6).

10.2 Effect of proposed repository changes

The existing excavated areas of the repository are not conceptualized as affecting regional fluid flow, hydraulic gradients, or transmissivity in the Culebra. Therefore, the repository also does not affect other units above the Salado. Subsidence caused by excavations at the repository horizon remains screened out of the performance assessment on the basis of low consequence (Kirkes, 2021). Thus, the proposed additional waste panels would not affect the conceptual model for units above the Salado.

Information Only

11 Transport of Dissolved Actinides in the Culebra

11.1 Description in the CCA

The conceptual model for transport of dissolved actinides in the Culebra is described in U.S. DOE (1996).

> *Actinides may be introduced into the Culebra by brine flowing up a borehole or by brine flowing up the shaft. Three principal processes have been demonstrated to occur naturally that affect the transport and retardation of dissolved actinides. Dissolved actinides will be carried by advection in the natural flow of Culebra groundwater. Dissolved actinides will diffuse into the matrix. Dissolved actinides will sorb to varying extents onto the different minerals lining pore walls or fractures. It is possible that dissolved actinides may participate as trace constituents in reactions between water and rock and be bound up in newly formed minerals, but this phenomenon is not included in the conceptual model. These processes are complicated to characterize because of known stratigraphic variation in the Culebra and expected heterogeneity in solution chemistry along the possible flow paths from the injection point to the accessible environment.*
>
> *The Culebra at the WIPP site is conceptualized as having very low permeability in the upper approximately 9.8 feet (3 meters), and variable permeability in the lower portion, which can be lower than the upper portion in regions where the Culebra as a whole is relatively impermeable. Thus, the bulk of the data indicates that the majority of the flow and transport takes place in the lower portions of the Culebra. Accordingly, for flow and transport calculations, an effective thickness of the Culebra of 13.1 feet (4 meters) is assumed.*
>
> *There is considerable variability in the structure and size of porous features in the Culebra, including fractures (of a variety of dimensions and interconnectedness), vugs, interparticle and intercrystalline porosity. The principal flow occurs within those features with the high permeability, and slower flow and diffusion are primary processes in the lower permeability features. Tracer test interpretations indicate that at some locations flow occurs predominantly through fractures (advective porosity is low) and at other locations slower transport indicates that flow is occurring in other permeable features such as vugs connected by microfractures, and possibly interparticle porosity (higher advective porosity). Tracer test interpretations also indicate that matrix diffusion is an important process in high-permeability regions of the Culebra. In other words at least two scales of porosity are needed to reasonably represent the transport processes in the Culebra (that is, a double-porosity model). At some locations of low permeability, fractures may be absent or filled with gypsum. An alternative conceptual model for transport at these locations is uniform single porosity with a high porosity. To simplify calculations, the uniform single porosity model was not implemented; the double porosity model implemented results in faster transport.*
>
> *The processes that occur in the advective porosity portion of the Culebra are advection (flow), dispersion (spreading caused by heterogeneity), diffusion within the advective porosity, and diffusion into the diffusive porosity. Important factors in this conceptual model are the velocities of fluid in the advective porosity, free-water diffusion coefficients, and dispersion coefficients. The most important factor is the fluid velocity. Free-water tracer diffusion coefficients are*

Information Only

specified for actinides. Dispersive spreading at the scale of disposal-system modeling is dominated by the effects of heterogeneities explicitly incorporated in the transmissivity fields input to SECOFL2D.

Chemical retardation of dissolved actinides is conceptualized to occur by sorption onto dolomite grains exposed in diffusive porosity because of the large amount of dolomite present in the Culebra. Chemical retardation increases if diffusive porosity is smaller because there is a larger volume of rock for sorption. Although clay minerals are present and would sorb actinides in the Culebra, their effects are not included in the conceptual model or parameter values specified. Effective properties for the rock matrix, which is assumed to be homogeneous, and solution chemistry are assumed and are incorporated directly in specification of the parameters for the retardation model (see Appendix MASS, Section MASS.15.2, and Appendix PAR, Parameters 49 through 57).

In summary, the conceptual model for dissolved actinide transport includes the following: transport in advective porosity, physical retardation (diffusion) into diffusive porosity, chemical retardation (sorption) in diffusive porosity, homogeneous rock properties, and a linear isotherm to describe the sorption process. Some of the more important parameters are advective porosity, diffusive porosity, tortuosity, matrix block length, molecular diffusion coefficients, Kd, and the grain density of dolomite in the Culebra. (U.S. DOE, 1996, Section 6.4.6.2.1).

11.2 Effect of proposed repository changes

The existing excavated areas of the repository are not conceptualized as affecting regional fluid flow, hydraulic gradients, or transmissivity in the Culebra. Subsidence caused by excavations at the repository horizon remains screened out of the performance assessment on the basis of low consequence (Kirkes, 2021). Thus, the proposed additional waste panels would not affect the conceptual model for transport of dissolved actinides in the Culebra.

Information Only

12 Transport of Colloidal Actinides in the Culebra

12.1 Description in the CCA

The conceptual model for transport of colloidal actinides in the Culebra is described in U.S. DOE (1996).

> *Colloidal particles are subject to many of the same processes that affect dissolved actinides, but because of their size several additional processes affect them. There are three process differences. Colloidal particles in general are preferentially carried in the center of pore throats by faster-moving fluid, which could cause slightly increased rates of transport compared to dissolved species. Colloidal particles can be filtered from flowing groundwater when they encounter small-aperture features in the pore network. Finally, colloidal particles may undergo different sorption processes than dissolved species.*
>
> *The primary distinction in the transport behavior of the different colloidal particles is whether particles diffuse into the matrix from fractures. This is controlled by the difference between the size of colloidal particles and the mean pore-throat diameters in the diffusive porosity of the Culebra. Colloidal particles that are smaller than the pore throats can diffuse into the diffusive porosity. Actinide intrinsic colloids and humic materials are small enough for this to occur. The conceptual model for these particles includes the processes of advection, diffusion, and dispersion in the advective porosity, diffusion into diffusive porosity, and sorption of actinides in diffusive porosity. This model is analogous to the model specified for dissolved actinides, although the parameter values are different. The conceptual model assumes that other retardation processes (for example, filtration) will not occur for actinide-intrinsic colloids and humic materials.*
>
> *In contrast, colloidal particles that are larger than pore throats will be excluded from the matrix and will remain in advective porosity. Microbes and mineral fragment are conceptualized as being larger than the mean pore-throat diameter in Culebra diffusive porosity. The conceptual model for these particles includes the processes of advection in advective porosity and filtration by small-aperture features that occur within the advective porosity. See Appendix MASS (Section MASS.15.3 and MASS Attachment 15-9) for additional discussion.*
>
> *Experiments have demonstrated that mineral fragments and microbes are attenuated so effectively by the advective porosity in the Culebra that it was deemed unnecessary to include those colloids in performance assessment calculations. Under the neutral to slightly basic geochemical conditions expected in the Culebra, humic substances were found to not influence the sorption behavior of dissolved actinides. Therefore, actinides associated with humic substances were treated as dissolved species in the performance assessment calculations. The only actinide-intrinsic colloid found to exist in significant concentrations was the Pu(IV)-polymer. At the WIPP, the total amount of Pu(IV)-polymer introduced to the Culebra was found to be insignificant with respect to the EPA normalized release limit and so was not included in transport calculations. See Appendix SOTERM (Section SOTERM.6) and Appendix MASS (Section MASS.15.3.1) for details. See Appendix MASS (Section MASS.15.3.3) for alternative modeling approaches considered.*

Information Only

> *Indigenous microbes, humics, and mineral fragment colloids in the Culebra may react with actinides introduced to the Culebra in dissolved form to create new colloidal actinides. Newly formed actinide-bearing microbial and mineral colloids, however, will be attenuated similarly to colloidal actinides introduced from the repository. Therefore, disregarding the impact of newly formed microbial and mineral fragment colloidal actinides is conservative. Experimental results indicate that humics do not interact with dissolved actinides under Culebra geochemical conditions. Consequently, the quantity of newly formed humic actinides will be insignificant.* (U.S. DOE, 1996, Section 6.4.2.2).

12.2 Effect of proposed repository changes

The existing excavated areas of the repository are not conceptualized as affecting regional fluid flow, hydraulic gradients, or transmissivity in the Culebra. Subsidence caused by excavations at the repository horizon remains screened out of the performance assessment on the basis of low consequence [Kirkes, 2021]. Thus, the proposed additional waste panels would not affect the conceptual model for transport of colloidal actinides in the Culebra.

Information Only

13 Exploration Boreholes

13.1 Description in the CCA

The conceptual model for exploration boreholes is described in U.S. DOE (1996).

> *The Exploration Borehole conceptual model addresses drilling locations. methods, and frequencies within the WIPP controlled area, borehole sealing, and long-term fluid flow through the sealed borehole. Short-term flow through the unsealed borehole is addressed in the Direct Brine Release conceptual model. The Exploration Borehole conceptual model is limited to a single borehole penetrating the repository. The Multiple Intrusion conceptual model describes conditions when more than one borehole is assumed to penetrate a waste panel.* [Appendix PEER 1, Section 3.12.1, U.S. DOE 1996]
>
> *An exploration borehole may be drilled on the WIPP site for natural resources investigation and may by chance penetrate a waste panel in the repository. Such boreholes are assumed to be drilled by individuals who have no knowledge of the buried waste, after active institutional control of the site has ceased. The conceptual model for exploration boreholes is based in large pan on proscriptive requirements of EPA 40 CFR 194. The EPA requirements are paraphrased as follows:*
>
> - *The regulatory time frame is the time period beginning at disposal and ending 10,000 years after disposal [40 CFR 194.21].*
> - *Both deep drilling (to or below a depth of 2,150 feet) and shallow drilling (less than a depth of 2,150 feet) that may potentially affect the disposal system during the regulatory time frame are assessed [40 CFR 194.33(a)]. The approximate depth of the repository is 2,150 feet.*
> - *Exploratory drilling is assumed to be inadvertent and intermittent [40 CFR 194.33(b)(1)].*
> - *Exploratory drilling for those resources provided by the waste in the disposal system or the engineered barriers designed to isolate such waste need not be considered [40 CFR 194.33(b)(1)].*
> - *Drilling events in the Delaware Basin are assumed to occur at random intervals in time and space during the regulatory time frame [40 CFR 194.33(b)(2)].*
> - *The frequency of deep drilling within the WIPP controlled area is assumed to be the sum of the rates of deep drilling for each resource in the Delaware Basin over the past 100 years [40 CFR 194.33(b)(3)].*
> - *The total rate of shallow drilling at WIPP is assumed to be the sum of the rates of shallow drilling for each resource in the Delaware Basin over the past 100 years; however. in considering the historical rate of all shallow drilling, the DOE may, if justified, consider only the historical rate of shallow drilling for resources of similar type and quality to those in the controlled area [40 CFR 194.33(b)(4)].*
> - *Future drilling practices and technology are assumed to remain consistent with practices in the Delaware Basin at the time the CCA is prepared, including the types and amounts of drilling fluids; borehole depths, diameters, and seals; and the fraction of boreholes that are sealed [40 CFR 194.33(c)(1)].*

Information Only

- *Natural processes are assumed to degrade or otherwise affect the capability of boreholes to transmit fluids over the regulatory time frame [40 CFR 194.33(d)(2)].*
- *The effects of techniques used for resource recovery following drilling need not be considered [40 CFR 194.33(d)]*

In developing a conceptual model that incorporates these assumptions, DOE has considered the following:

- *Shallow boreholes will not intercept or affect the integrity of the repository and therefore need not be considered.*
- *Present drilling practices include the relative economic value of the target resource; on this basis, the objectives of exploration drilling at the WIPP site are assumed to be oil and gas because these are the only commercially viable resources for which exploration drilling would occur to or below the depth of the repository horizon.*
- *Although commercially viable reserves of potash are known to be within the WIPP controlled area, inadvertent penetration of the repository during exploratory drilling for this resource was not considered because such reserves lie above the repository depth.*
- *The frequency of deep borehole drilling is estimated based only on historical frequencies of drilling for resources of similar type and quality to those found at the WP site.*

Above text quoted from U.S. DOE (1996), Appendix PEER 1, Section 3.12.1.

All exploratory boreholes are assumed to be drilled in search of hydrocarbon resources and all are therefore assumed to penetrate entirely through the Salado and Castile Formations.

Drilling is assumed to be conducted by standard rotary methods. At the time of repository penetration, the borehole is assumed to have been cased to the bottom of the Rustler Formation, following current standard practices. After drilling has progressed through the salt section, an intermediate casing is installed to the bottom of the Castile. Below that depth a third, final production casing is installed, which typically extends to the ground surface during production, but is only cemented near the production zones. On abandonment, the production casing is commonly cut above the cemented zone and reclaimed (Thompson et al. 1996, p. 6). Fluid and solids that flow through the open borehole immediately on repository penetration are described in the aforementioned Direct Brine Release, Cuttings/Cavings, and Spallings conceptual models. Long-term fluid flow through the sealed borehole is described in the following paragraphs.

On abandonment, three different scenarios have been adopted by DOE to describe the range of current borehole plugging practices. These are (1) a single, continuous cement plug extending from the top of the Salado to the bottom of the Castile; (2) two 40-m cement plugs, one at the bottom of the Castile (top of the Bell Canyon) and one at the bottom of the Rustler; and (3) three 40-m cement plugs, consisting of the two plugs described above plus an additional plug near the Salado/Castile contact below the repository. In addition, all boreholes have approximately 15-m long concrete surface plugs (Thompson et al. 1996, p. 3).

Degradation of the plugs generally follows the scenarios and rationale presented by Thompson et al. (1996). The continuous plug is not considered to degrade over time because of its structural integrity and the very low brine flow through it. The surface plug is also not considered to

Information Only

degrade over time because of the lack of physical or chemical stresses in the near-surface environment. In the two- and three-plug scenarios the steel casing in the Salado and Castile is expected to be locally pined and leak within a few decades after abandonment. In these scenarios, within 200 years after abandonment the 40-m concrete plug and remaining casing above the repository and the open casing below the repository are assumed to fail completely from both mechanical and chemical stresses. Simultaneously, with the exception of the concrete plugs below the repository, the entire borehole is assumed to be filled with degraded concrete, corrosion products, and sloughed native materials that are assigned the hydraulic properties of silty sand in accordance with regulatory guidance. Because of increased stresses and halite creep rates below the repository, the borehole filling below the repository is subsequently assumed to be compacted, with a concurrent decrease in permeability. The cement plugs below the repository, however, are assumed to maintain their integrity for the duration of the 10,000-year regulatory time frame because degradation rates will be significantly reduced due to a less aggressive chemical environment (see 23 May 1996 Draft CCA, Section 6.4.7.2.2 (DOE 1996, p. 6-74). Long-term brine flow is expected to occur to or from the repository through the degrading upper borehole plugs as a function of brine availability and repository pressure.

For long-term flow, the borehole is assumed to be plugged immediately after repository penetration by randomly selecting one of the three plugging scenarios in accordance with its probability of occurrence. The borehole plugs are degraded according to the following assumptions. The continuous plug, the surface plug, and the 40-m plugs below the repository will maintain their initial permeability of 5 x 10^{-17} m^2 throughout the 10,000-year regulatory time frame. The 40-m plug above the repository maintains its initial permeability of 5 x 10^{-17} m^2 for 200 years. The borehole between the plugs is assumed to remain open during this period and is assigned a permeability of 1 x 10^{-9} m^2. The casing is not specifically addressed in the long-term flow model and is assumed to not be present. After 200 years, the upper 40-m plug is assumed to fail and the entire borehole between plugs is assumed to have filled with a material with the properties of silty sand, whose permeability is sampled within the range of 1 x 10^{-11} m^2 to 1 x 10^{-14} m^2. Beginning 1,200 years after waste panel penetration, the permeability range of the filling material in the lower borehole below the repository is reduced by one order of magnitude to 1 x 10^{-12} m^2 to 1 x 10^{-15} m^2. The porosity of all borehole materials is held at a constant, conservatively high value of 0.32. Pore compressibility is assumed to be zero, giving the medium the approximate compressibility of brine. Two-phase brine and gas flow is modeled using a zero threshold pressure and zero residual brine and gas saturations. (U.S. DOE, 1996, Appendix PEER 1, Section 3.12.1).

13.2 Changes since the CCA

In preparation for the CRA-2004, the U.S. DOE changed values for two parameters related to borehole plugs, as mandated by the U.S. EPA. The initial permeability of the plug was assigned a value of 1 x 10^{-17} m^2, and the permeability of the material filling the borehole above the repository after failure of the plugs was assigned a range of 1 x 10^{-11} m^2 to 1 x $10^{-16.3}$ m^2. (U.S. DOE, 2004, Section 6.4.7.2.1).

Information Only

13.3 Effect of proposed repository changes

The proposed additional panels do not present any change to repository features that would alter the conceptual features of an intrusion borehole, or the long-term fluid flow within the borehole. The conceptual model for drilling frequency or drilling location does not depend on the area or shape of the repository. Thus, although the number of intrusions occurring in simulations of the future evolution of the repository is anticipated to increase due to the addition of the proposed waste panels, the exploration borehole conceptual model is not affected by the proposed additional panels.

Information Only

14 Cuttings and Cavings

14.1 Description in the CCA

The cuttings and cavings conceptual model is described in U.S. DOE (1996). Cuttings are solid materials removed by drill bit, and cavings are solid materials eroded from the borehole wall and brought to the surface in the circulating drilling fluid.

> *In a rotary drilling operation, the volume of material brought to the surface as cuttings is the cylinder defined by the thickness of the unit being drilled and the diameter of the drill bit. The quantity of radionuclides released as cuttings is therefore a function only of the activity of the intersected waste and the diameter of the intruding drill bit. Like all parameters that describe future drilling activities, the diameter of a drill bit that may intersect waste is speculative. The DOE uses a constant value of 12.25 inches (0.311 meters), consistent with bits used at the WIPP depth in the Delaware Basin today. The activity of the intersected waste may vary depending on the type of waste intersected, and the DOE considers random penetrations into remote-handled (RH)-TRU waste and each of the 569 different waste types identified for contact-handled (CH)-TRU waste.*
>
> *The volume of particulate material eroded from the borehole wall and brought to the surface as cavings may be affected by the drill bit diameter, the effective shear resistance of the intruded material, the speed of the drill bit, the viscosity of the drilling fluid and the rate at which it is circulated in the borehole, and other properties related to the drilling process. The most important of these parameters, after drill bit diameter, is the effective shear resistance of the intruded material. In the absence of data describing the reasonable and realistic future properties of degraded waste and backfill, the DOE has used conservative parameter values based on the properties of fine-grained sediment. Other properties are assigned fixed values consistent with current practice.* (U.S. DOE, 1996, Section 6.0.2.3.1).

14.2 Changes since the CCA

Subsequent to the CCA, the U.S. EPA required the U.S. DOE to change its method for estimating waste shear strength resistance and to base the estimate on particle size distributions rather than the fine-grained sediment analog. The CRA-2004 used a different range and distribution for this parameter (U.S. DOE, 2004, Appendix PA, Attachment PAR, Section PAR 7.0, sheet for Parameter 58: Effective Shear Resistance to Erosion).

In preparation for the CRA-2014, results of experiments performed on surrogate materials for degraded waste were used to refine the range of values for the waste shear strength. (U.S. DOE, 2014, Appendix PA, Section PA-1.1.5). In EPA's review of the CRA-2014, the U.S. EPA requested that DOE reconsider a subset of the data used to develop the distribution for the waste shear strength parameter (U.S. EPA, 2017a). In response the U.S. DOE modified the parameter distribution for the CRA-2019 (U.S. DOE, 2019, Appendix PA, Section PA-1.1.6).

Information Only

14.3 Effect of proposed repository changes

The proposed additional panels do not present any change to repository features that would alter the conceptual features of an intrusion borehole, or to the form or properties of the waste. Therefore, the cuttings and cavings conceptual model is not affected by the proposed additional panels.

Information Only

15 Spallings

15.1 Description in the CCA

Spallings are solid material carried into an intrusion borehole during rapid depressurization of the waste-disposal regions (U.S. DOE, 1996, Section 6.0.2.3). The spallings conceptual model for the CCA is described in U.S. DOE (1996), Appendix PEER 1, Section 3.14.1. The CMPR and the U.S. EPA found the original spallings conceptual model to be inadequate, but also found that the model results were acceptable for use in the CCA (U.S. DOE, 2004, Section 9.3.1.3.5.1).

15.2 Changes since the CCA

In preparation for the CRA-2004 the U.S. DOE developed a replacement spallings model, which a peer review (U.S. DOE, 2004, Section 9.3.1.3.5) found to be adequate (U.S. DOE, 2004, Appendix PEER 1, Section 3.1.2) and which the EPA accepted.

The conceptual model for spallings is summarized in the context of the software (DRSPALL) which implements the model (SNL, 2003):

> *DRSPALL is based on the theory of one-dimensional time-dependent compressible isothermal fluid flow. Somewhat different forms of that theory are used, depending on whether the flow is in the wellbore or in the repository, and whether the wellbore currently penetrates the repository or not. The wellbore and repository flows are coupled at a specified boundary by a set of conditions. Schematic diagrams of the flow geometry prior to and after penetration are shown in Figure 3-1 and Figure 3-2, respectively. Throughout the process, the drillbit can move downward as a function of time, removing salt or waste material. Flow in the well is treated as a compressible, viscous, multi-phase mixture of mud, gas, salt, and possibly waste solids. Flow in the repository is treated as viscous, compressible single-phase gas flow in a porous solid. At the cavity forming the repository-wellbore boundary (following penetration) waste solids freed by drilling, tensile failure, and associated fluidization may enter the wellbore flow stream. Between the well and the repository, flow is treated according to the state of penetration, as described later*. (SNL, 2003, Section 3.0)

Spallings is conceptualized to occur in three stages:

- pre-penetration, before the drill bit intersects the waste panel volume;
- transition, occurring as the drill bit near the waste panel volume when the repository and wellbore are in hydraulic communication;
- post-penetration, when the drill bit has penetrated the repository.

Further details describing the spalllings conceptual model during each stage are found in SNL (2003), Sections 3.1 through 3.6.

15.3 Effect of proposed repository changes

The proposed additional panels do not present any change to repository features that would alter the conceptual features of an intrusion borehole, or to the form or properties of the waste. Therefore, the spallings conceptual model is not affected by the proposed additional panels.

Information Only

16 Direct Brine Release

16.1 Description in the CCA

The direct brine release conceptual model is described in U.S. DOE (1996).

> *Direct brine release refers to the possibility that brine containing actinides may flow from the waste panels up a borehole to the surface during drilling (Appendix MASS, Section MASS.16.2). It is conceptualized that direct brine release to the surface will not occur every time a borehole penetrates the waste panels but rather that it can occur only when two conditions are met. The first condition is the presence of mobile brine in the waste panels. Because of brine consumption by corrosion and low initial saturation, it is possible for liquid saturations below the residual saturation to exist in the repository, in which case direct brine release cannot occur. The second condition is the pressure in the waste panels must be greater than the pressure at the base of the column of drilling mud. Drillers in the Delaware Basin use a salt-saturated mud with a specific gravity of about 1.23 while drilling through the Salado. This corresponds to a pressure of approximately 8 megapascals at the repository horizon (see Appendix MASS, Section MASS.16.2, and MASS Attachment 16-2). If fluid in the waste panels is below this pressure, no direct brine release during drilling can occur because liquid flow in the repository will be away from the borehole.*
>
> *In the conceptual model, resolution of the details of flow near the borehole is considered important, as the changing physical conditions over the short duration of this flow can significantly impact estimates of the total volume released. It is not assumed that a direct brine release would be noticed by the driller (EPA 1996a, 61 FR 5230). Also important to the conceptual model is how long direct brine release occurs. There are several ways in which the direct brine release could be stopped. A driller might detect higher flow rate to the mud pit and take action to mitigate consequences. Alternatively, direct brine release will stop when the driller cases the hole after reaching the base of the salt section. As discussed in Appendix MASS (MASS Attachment 16-2) and Appendix DEL (Section 7.5), the DOE assumes that for low volumes of fluid flow, the borehole will be controlled and cased within 72 hours after the penetration of the repository. In all cases, all fluid flow to the surface during drilling is assumed to cease within 11 days after penetration of the repository.*
>
> *In the conceptual model for direct brine release, several other assumptions are made that relate to other conceptual models. The processes of direct solids release from cuttings, cavings, spall, and direct brine release are treated separately, although the direct brine release model does account for the effects of solids removal (spall) on fluid flow near the well bore. Direct brine release will affect the pressure and saturation in the repository. However, it is assumed that these effects are negligible over the long-term because of their transient and local nature, and they are not accounted for in long-term (10,000-year) BRAGFLO disposal system calculations. This assumption simplifies modeling because it allows detailed consideration of direct brine release over a short time period, without having to couple the results of these calculations back into the disposal system simulations.*

Information Only

> *The area over which fluid flow can occur during direct brine release is assumed to be the rooms and drifts of waste panels, the DRZ, room pillars, and panel closures. Because local scale, short-duration flow is important, the geometry of the waste panels is considered important and is represented in the model. It is assumed that the flow interactions with the Salado other than the DRZ are not important during direct brine release. For this model, pillars are arbitrarily assumed to have the properties of the DRZ rather than intact halite, although in reality their properties are probably like a DRZ at their edge and like intact halite in their core. Since the DRZ permeability is greater than the permeability of intact halite, this assumption is conservative. A two-dimensional geometry is used parallel to the repository horizon, with a 1° dip from north to south.* (U.S. DOE, 1996, Section 6.4.7.1).

16.2 Changes since the CCA

In preparation for the CRA-2009, the U.S. DOE changed the maximum duration of a direct brine release from 11 days to 4.5 days. (U.S. DOE, 2009, Appendix PA, Section PA-2.11).

16.3 Effect of proposed repository changes

Repository features considered in the Direct Brine Release conceptual model are affected by the proposed additional panels. Although the mathematical model that implements the Direct Brine Release conceptual model is not affected, the implementation of that mathematical model (e.g., computational grid) is affected by the additional waste panels.

Information Only

17 Castile and Brine Reservoir

17.1 Description in the CCA

The conceptual model for the Castile and for brine reservoirs in the Castile is described in U.S. DOE (1996), Section 6.4.8.

> *For performance assessment, the Castile is conceptualized as unimportant because of its expected low permeability (based on similarities to the Salado), unless a borehole penetrates both the repository and a brine reservoir in the Castile. Two regions are specified in the Castile horizon in the disposal system geometry: the Castile (Region 29 in Figure 6-13) and a reservoir (Region 30 in Figure 6-13). The Castile region is assigned an extremely low permeability, which prevents it from participating in fluid flow processes, consistent with the concept that it is unimportant*. (U.S. DOE, 1996, Section 6.4.8).

Castile brine reservoirs are conceptualized as uncertain in occurrence, spatial extent and volume. The original conceptual model for a Castile brine reservoir is described in U.S. DOE (1996), Section 6.4.8:

> *Where they exist, Castile brine reservoirs in the northern Delaware Basin are believed to be fractured systems, with high-angle fractures spaced widely enough that a borehole can penetrate through a volume of rock containing a brine reservoir without intersecting any fractures and therefore not produce brine. They occur in the upper portion of the Castile (Popielak et al. 1983, G-2). Appreciable volumes of brine have been produced from several reservoirs in the Delaware Basin, but there is little direct information on the areal extent of the reservoirs or the interconnection between them. The WIPP-12 data indicate that fractures in the network have a variety of apertures and permeabilities, and they deplete at different rates. Brine occurrences in the Castile behave as reservoirs—that is, they are bounded systems—rather than as aquifers such as groundwater in the Culebra and Magenta. The properties that need to be specified for brine reservoirs are pressure, permeability, compressibility, total brine volume, and porosity.* (U.S. DOE, 1996, Section 6.4.8).

In its review of the CCA, the U.S. EPA found that "DOE's discussion of the size, orientation, and repressurization potential of the Castile brine reservoirs was not well supported" (U.S EPA, 1998b, page 14-30). As a result, the U.S. EPA required the U.S. DOE to conduct an analysis termed the PA Verification Test (PAVT) (U.S. EPA, 1997) that used different parameters describing the occurrence and hydraulic properties of the Castile brine reservoirs (U.S. EPA, 1998a). In light of that analysis, the U.S. EPA "found that the original brine reservoir characteristics were, in fact, acceptable." (U.S. EPA, 1998b, page 14-31).

17.2 Changes since the CCA

Subsequent to the review of the CCA, the U.S. EPA mandated that the U.S. DOE adopt the PAVT parameters in WIPP PA (U.S. DOE, 2004, Section 6.0.2). The PAVT parameters related to the hydrologic properties of Castile brine reservoirs have been used in WIPP PA since the CRA-2004. (U.S. DOE, 2004, Table 6-1).

The parameter (termed PBRINE) describing the likelihood that a drilling intrusion intersects a Castile brine reservoir has undergone several modifications since the CCA. The current quantification of PBRINE

Information Only

is found in U.S. EPA (2017b). The U.S. DOE adopted the distribution described in U.S. EPA (2017b) in the CRA-2019 (U.S. DOE, 2019, Appendix PA, Section PA-1.1.4).

In U.S. EPA (2017b), quantification of the PBRINE parameter relies primarily on data from a 1987 geophysical survey conducted over the footprint of the existing ten waste panels (The Earth Technology Corporation, 1987). The proposed additional panels lie to the north and west of the existing waste panels, where no geophysical survey data are available.

17.3 Effect of proposed repository changes

The current distribution of the PBRINE parameter is based on all available data. The proposed additional panels have no effect on properties of the underlying Castile formation. The conceptual model for the Castile and Castile brine reservoirs is not affected if an assumption is made that the likelihood that reservoirs are present under the proposed waste panels, and the extent of any such reservoirs, is the same as for the existing waste panels. For these reasons the conceptual model for the Castile and Castile brine reservoirs is not affected by the proposed additional panels.

Information Only

18 Multiple Intrusions

18.1 Description in the CCA

The conceptual model for multiple intrusions is described in several sections of U.S. DOE (1996).

> *The Multiple Intrusion conceptual model is an extension of the Exploration Borehole model that describes fluid flow between the repository and multiple exploratory boreholes penetrating a single waste panel. The borehole drilling methods and frequencies, borehole plugging, and plug degradation discussed in the Exploration Borehole model in Section 3.12 are the same for multiple intrusion boreholes. Short-term flow through unsealed boreholes is addressed in the Direct Brine Release conceptual model in Section 3.15.* (U.S. DOE, 1996, Appendix PEER 1, Section 3.17.1).

U.S. DOE (1996) Section 6.3.2.2 describes the Disturbed Performance Deep Drilling Scenario that conceptualizes the effect on the repository and releases to the accessible environment resulting from a future drilling intrusion. The Exploration Borehole conceptual model describes the features and properties of an intrusion borehole.

The occurrence of future drilling intrusions is conceptualized as a stochastic process with a constant drilling rate:

> *Drilling events are assumed to be random in time and space.* (U.S. DOE, 1996, Section 6.4.12.3).

Drilling intrusion events are categorized as E1 or E2:

> *The DOE has distinguished two types of deep drilling events by whether or not the borehole intersects a Castile brine reservoir. A borehole that intersects a waste disposal panel and penetrates a Castile brine reservoir has been designated an E1 event. … A borehole that intersects a waste panel but does not penetrate a Castile brine reservoir has been designated an E2 event*. (U.S. DOE, 1996, Section 6.3.2.2).

The effects of intrusions on the repository and the resulting releases are modeled by three disturbed performance scenarios (U.S. DOE, 1996, Section 6.3.2.2):

- The E1 scenario, in which one drilling intrusion of type E1 occurs in a waste panel.
- The E2 scenario, in which one or more drilling intrusions of type E2 occurs in a waste panel.
- The E1E2 scenario, in which any number of drilling intrusion occur in the same waste panel and at least one intrusion is of type E1.

Individual intrusions are classified as either E1 or E2, depending on whether the intrusion penetrates a Castile brine reservoir. When multiple intrusions occur in the same waste panel, the Multiple intrusions conceptual model describes how flow and transport results are determined. The Multiple intrusions conceptual model relates any sequence of intrusions to one of the three disturbed performance scenarios.

Information Only

Table 2. Summary of multiple intrusion scenarios

Sequence of First Two Boreholes	Basis for Brine Flux and Radionuclide Transport
E2 followed by E1	E2 scenario until the time of the second intrusion, thereafter E1E2 scenario
E1 followed by E2	E1 scenario until the time of the second intrusion, thereafter E1E2 scenario
E1 followed by E1	E1 scenario until the time of the second intrusion, thereafter E1E2 scenario
E2 followed by E2	E2 scenario

Adapted from U.S. DOE (1996), Appendix PEER 1, Table 3.17.1.

In the case of a third or subsequence drilling intrusion, the rules in the above table are applied. To summarize, effects and releases from any sequence of only E2 intrusions are conceptually modeled by the effect and releases calculated for the E2 scenario, because

> *In cases of two E2 penetrations, long-term brine release volume is assumed to be the same as for a single E2 penetration because flow will be controlled by the rate at which brine can be supplied by the Salado halites, rather than the rate at which brine can flow in the borehole*. (U.S. DOE, 1996, Appendix PEER 1, Section 3.17.1).

Effects and releases from any sequence including one or more E1 intrusions are modeled by:

- the results of the scenario corresponding to the type of the first intrusion until the time of the first E1 intrusion following the initial intrusion;
- the results of the E1E2 scenario after each additional E1 intrusion until the time of the following E1 intrusion.

18.2 Effect of proposed repository changes

Because the proposed additional waste panels are similar in design to the existing waste panels and do not affect the properties of intrusion boreholes, the emplaced waste, the Salado or Castile brine reservoirs, multiple intrusions will affect the proposed waste panels in the same manner as the existing waste panels are affected. Although the implementation of the Multiple intrusion conceptual model is affected by the introduction of additional panels, the proposed additional panels do not affect the Multiple intrusion conceptual model.

Information Only

19 Climate Change

19.1 Description in the CCA

The climate change conceptual model is described in U.S. DOE (1996).

> *The present climate at the WIPP and the geologic record of past climate change in southeastern New Mexico are discussed in Section 2.5 and Appendix CLI. Although meaningful quantitative predictions of future climate for the next 10,000 years are not feasible for the WIPP (or any location), effects of reasonably possible climate changes on disposal system performance must be considered. For the WIPP, uncertainty about these effects is incorporated in the performance assessment by considering the effects of various possible future climates on groundwater flow and potential radionuclide transport in groundwater. Direct effects of climate change that do not involve groundwater flow do not affect the long-term performance of the WIPP because of its depth below the land surface. Examples of such direct effects are changes in wind patterns, thermal effects related to changes in surface temperature, and near-future impacts on surface facilities. Long-term effects of climate change on the near-surface portions of the shaft seal system (see Section 6.4.4) are not incorporated in the analysis because BRAGFLO modeling conducted for this performance assessment indicates that system performance is unaffected by the behavior of the upper portion of the shaft seal system. Additional aspects of climate change screened out from the performance assessment, including glaciation at the site and possible future anthropogenic changes, are discussed in Appendix SCR (Sections SCR.1.6.2 and SCR.3.6.1).*
>
> *The effects of postulated climate change on groundwater flow have been evaluated outside of the performance assessment calculations using a regional three-dimensional groundwater basin model based on the concept of basin hydrology introduced in Section 2.2.1.1. For the purposes of the regional analysis, climate-related factors that might affect groundwater flow, such as precipitation, temperature, and evapotranspiration, are treated through a single model parameter, potential recharge, which controls the rate at which water is added to the model at the water table. As described in Appendix MASS (Section MASS.17 and MASS Attachment 17-1), changes in this parameter allow simulation of regional groundwater flow under a range of different future states in which the climate may be wetter, the water table may be higher, and groundwater velocity in all units may increase. These and other simulations discussed in Appendix MASS (Section MASS.15 and MASS Attachment 15-7), show that the regional, three-dimensional effects of climate change can be reasonably approximated in performance assessment through direct scaling of specific discharge in the two-dimensional, steady-state groundwater velocity field for the Culebra.* (U.S. DOE, 1996, Section 6.4.9).

19.2 Effect of proposed repository changes

The proposed additional panels will have no effect on regional groundwater flow, and thus the proposed additional panels do not affect the climate change conceptual model.

Information Only

20 Creep Closure

20.1 Description in the CCA

The creep closure conceptual model is described in U.S. DOE (1996).

> *Salt creep occurs naturally in the Salado halite in response to deviatoric stress. Inward creep of rock and the repository response is a process generally referred to as creep closure. Creep closure of excavated regions begins immediately because of excavation-induced deviatoric stress. If the rooms were empty, closure would proceed to the point where the void volume created by the excavation would be eliminated as the surrounding formation returns to a uniform stress state. In the waste disposal region, waste consolidation will continue until loading in the surrounding rock is uniform, at which point salt creep ceases. The amount of waste consolidation that occurs and the time it takes to consolidate are governed by properties of the waste (waste strength, modulus, etc.), properties of the surrounding rock, the dimensions and location of the room, and the quantities of fluids present in the room*. (U.S. DOE, 1996, Section 6.4.3.1)
>
> *Closure of the repository occurs naturally in the Salado halite as a response to the imbalance of forces created by excavation of the repository rooms and passages. Weak and plastic rock salt begins immediately to flow into the excavated spaces by processes dominated by creep. The rate of closure is the combined result of creep rates inherent to salt, repository temperatures and pressures, and resistance provided by repository contents. The creep rate proceeds to the limits determined by resistance from gas, brine, waste, backfill, or other contents in the repository until the void space is closed to the final porosity dictated by waste and seal material properties, contained fluid pressure, and lithostatic pressure. Roof fall in the disposal rooms, which may have significant impact on flow at least in the short term, is not included in the model.*
>
> *Both brine and gas content of the repository vary with time. Brine inflow/outflow is partly controlled by gas pressures. The relationship between gas outflow rates and gas generation rates influences pressures within the repository. Gas pressure results from the alteration of waste by biogenic and corrosion-based processes. The rate of the corrosion process is dependent on brine availability. Repository gas and brine pressures are limited by the minimum pressures at which gas or brine would be forced out of the repository via identified flowpaths through fractured interbeds within the Salado. The threshold pressures for initiation of outflow through these fractured anhydrite interbeds are therefore a key consideration in limiting resistance to closure due to gas and brine pressures. The fractures in the interbeds are essentially horizontal, so the pressures necessary to open the fractures or to initiate new fractures must be greater than the lithostatic load. Further, some resistance to gas release may result from travel through the fractured, rock-bolted halite between the repository and the interbeds. Resistance to gas outflow due to stress cage effects at the repository boundary and gas pressures necessary to maintain very extensive fractures may result in repository pressures larger than interbed threshold pressures. Gas pressures, which are some amount greater than the lithostatic pressure, are therefore possible at some times during the repository gas generation history. Internal gas pressures greater than the stress imbalance that drives creep inflow are conceivable. Internal pressures may contravene stresses in the salt and repository closure may cease, or*

Information Only

> *repository inflation may occur in some scenarios. The stoichiometric treatment of time histories of gas generation and the volumetric model based on creep closure rates and waste compaction are combined in the SANTOS computer code to provide repository void volume estimates through time as part of lookup tables called the "porosity surface."* (U.S. DOE, 1996, Appendix PEER 1, Section 3.19.1).

20.2 Effect of proposed repository changes

Because the proposed additional waste panels are similar in design to the existing waste panels and do not affect the properties of the Salado or the disturbed rock zone, creep closure around the proposed waste panels will proceed in the same manner as for the existing waste panels. Thus, the proposed additional panels do not affect the creep closure conceptual model.

Information Only

21 Shaft and Shaft Seals

21.1 Description in the CCA

The conceptual model for the shaft and shaft seals is described in U.S. DOE (1996).

> *The four shafts connecting the repository to the surface are represented in performance assessment with a single shaft, represented by Regions 2 through 11 on Figures 6-13 and 6-14. This single shaft has a cross section and volume equal to the total cross section and volume of the four real shafts it represents and is separated from the waste disposal regions in the model by the true north-south distance from the waste to the nearest shaft (the Waste Shaft). Upon closure of the repository, the shafts will be sealed as described in Section 3.3.1. The seal system is represented in performance assessment by discretizing 11 model regions in the shaft. These regions are as follows: an earthen fill region above the Rustler; a compacted clay column in the Rustler; an asphalt region at the top of the Salado; three concrete sections within the Salado; an upper Salado compacted clay column; a thick section of compacted crushed salt; a lower Salado compacted clay column separated into upper and lower segments; and a concrete monolith at the repository horizon (see Appendix SEAL, Section 4 and Appendix A). The concrete components in the Salado represent the concrete asphalt waterstops in the seal system design. Seal material parameter values used in the performance assessment are provided in Table 6-13.*
>
> *Conceptually, the shafts are assumed to be surrounded by a DRZ in the Salado. Within the bedded halite, the DRZ begins to form immediately after excavation and develops progressively as a function of unloading as the formation creeps toward the excavated area. From a sealing perspective, the most important characteristic of the DRZ is the higher permeability that results from dilatant deformation and the increased pore volume.*
>
> *The properties of the DRZ are known to vary with the type of adjacent material, time, and depth. When the shaft seals are emplaced, back pressures will progressively develop over time as the surrounding salt creeps inward. The back pressure applied by the seal material will progressively reduce the magnitude of the stress differential, which is the source for the DRZ microfracturing mechanism. The back pressure also results in a higher mean stress, which induces healing of the DRZ. The shaft DRZ permeability will, over time, approach that of the intact halite. Also, since the creep rate of the salt surrounding the shafts depends on depth, the back pressures supplied by the seal materials will result in DRZ healing at rates that increase with depth. The relative stiffness of the seal material is a factor, as well.*
>
> *In the performance assessment model, the radial extent of the DRZ around the shaft seal materials is an input parameter obtained by numerical model calculations and is corroborated by field data (see Appendix SEAL, Section 8 and SEAL Appendix C). The permeability of the DRZ around the shaft versus distance is assumed to follow a log linear relationship. Permeability of the DRZ at the shaft wall is based on experimental data collected in the air intake shaft (Dale and Hurtado 1996) and Room M (Van Pelt 1995). More information on how the DRZ is incorporated into the shaft parameters is contained in Appendix PAR (Parameter 12).*
>
> *The DRZ surrounding the shaft is not represented explicitly in the BRAGFLO mesh (Figures 6-13 to 6-15). Rather, the mesh has been simplified to represent only the cross-sectional area of the four*

Information Only

> *WIPP shafts, and the permeability values for the various seal components at different times have been adjusted to account for the presence of the shaft DRZ. This adjustment, which yields effective permeabilities, can be done because in Darcy flow the flux through a porous medium is a linear function of the product of the permeability of the medium and the cross-sectional area across which flow occurs. Thus, the flux that would occur through a shaft and its surrounding DRZ can be modeled equivalently using the shaft cross-sectional area with a higher seal component permeability. Equations for the derivation of the effective permeabilities are given in Appendix PAR (Parameter 12) and Appendix IRES (Section IRES.2).* (U.S. DOE, 1996, Section 6.4.4).

21.2 Changes since the CCA

In the CCA, the shaft seal system was represented by 11 discrete model regions each with different material properties and a sequence of time-dependent material property changes. In 2003, prior to the CRA-2004, the shaft seal system representation was replaced with a simplified, two layer system with fewer time-dependent changes that maintains equivalent permeability to the original 11-layer system (U.S. DOE, 2004, Section 6.4.4). The Salado Flow Peer Review concurred that the simplified shaft model "conservatively represents the behavior of seal components and is valid." [U.S. DOE, 2004, Appendix PEER 1, Section 2.1.2 (see Section 3.1.2.2 therein)] The simplified shaft seal model has been used in WIPP PA from the CRA-2004 to present.

The U.S. DOE has notified the U.S. EPA of the planned addition of a 5th shaft (U.S. DOE, 2019, Section 15.3.4.4). The new shaft is planned to be similar in construction as the four existing shafts, and all shafts are planned to employ the shaft seal system described in U.S. DOE (1996), Appendix SEAL. In the CRA-2019, the proposed new shaft's volume is combined with the volume of the four existing shafts, and all shafts are represented as a single feature in the PA models (U.S. DOE, 2019, Appendix PA, Section PA-1.1.2).

21.3 Effect of proposed repository changes

The repository design which includes the proposed additional panels is predicated on the five shafts (four existing and one proposed). No changes to the shaft systems are anticipated to be necessary accommodate the additional panels. Consequently, the proposed additional panels do not affect the shaft and shaft seal conceptual model.

Information Only

22 Gas Generation

22.1 Description in the CCA

The original gas generation conceptual model is described in U.S. DOE (1996).

> *Gas will be produced in the repository because of a variety of chemical reactions, primarily those occurring between brine, metals, microbes, cellulosics and similar materials, plastics, and rubber materials, and via liberation of dissolved gases to the gas phase. The dominant processes are anoxic corrosion of metals in the waste containers and the waste and microbial degradation of cellulosics, plastics, and rubbers in the waste. Anoxic corrosion reactions will occur between brine and steel, aluminum, and aluminum alloys, producing H_2. Microbial degradation of cellulosics may produce a variety of gases; however, for the waste inventory and expected conditions, CO_2 and CH_4 (methane) are expected to be the dominant gases for the process. Radiolysis has been demonstrated by laboratory experiment and model calculations to be insignificant (see Appendix MASS, Section MASS.8; Appendix SCR, Section SCR.2.5.1.3).*
>
> *Performance assessment uses the average stoichiometry model to estimate gas generation occurring in the waste disposal region. … The average stoichiometry model accounts for the formation of gas by anoxic corrosion of steels and microbial degradation of cellulosics, including plastics and rubbers. For the purpose of calculating repository pressure and gas flow, the density and viscosity of the generated gas are assumed to be those of H_2. In the average stoichiometry model, gas is assumed to be generated at a rate dependent on the availability of brine in the computational cell.*
>
> *It is assumed that there is no passivation of anoxic corrosion of steel by CO_2 and H_2S produced by microbial degradation because microbial gas generation is too slow and also because CO_2 will be removed from the gaseous phase by reaction with MgO backfill.*
>
> *Microbial degradation occurs in only half of the realizations because of uncertainties in viability of the microbial colonies (Appendix MASS, Section MASS.8 and MASS Attachment 8-2). Like anoxic corrosion, microbial degradation is represented by a generic equation, given along with other details in Appendix BRAGFLO (Section 4.13). … It is assumed that the microbial degradation process neither produces nor consumes water, but its rate is dependent on the amount of liquid present in a computational cell.*
>
> *Microbial degradation may consume plastic and rubber materials in the repository. The DOE assumes that in half of those simulations in which microbial degradation of cellulosics occurs, microbial degradation also acts on plastic and rubber materials in the waste disposal region.* (U.S. DOE, 1996, Section 6.4.3.3).

22.2 Changes since the CCA

In the CCA, microbial degradation of cellulosics, plastics and rubbers was modeled as occurring by denitrification, sulfate reduction and methanogenesis. The probability of microbial degradation occurring was set to 0.5; the conditional probability (conditional on microbial degradation occurring) that degradation is limited to cellulose was set to 0.5, and the conditional probability (condition on

Information Only

microbial degradation occurring) that degradation consumes cellulose, plastics and rubbers was set to 0.5. Gas generation was modeled as occurring at a constant rate (zero-order reaction).

In preparation for the CRA-2009 (U.S. DOE, 2009, Appendix PA Section PA-2.1.1), the methanogenesis biodegradation reaction was removed, while gas generation by denitrification and sulfate reduction were retained. The probability of gas generation by microbial action was increased to 1.0, and the conditional probability that degradation is limited to only cellulose was set to 0.75. Gas generation rates were altered to include a brief initial period of rapid gas generation at a constant rate, followed by a sustained period of slower generation at a constant rate (Nemer and Stein, 2005). In addition, the U.S. DOE removed the iron sulfidation reaction as a simplification of the gas generation model, because sulfidation produces one mole of gas for each mole of gas consumed (U.S. DOE, 2009, Appendix PA, Section PA-4.2.5).

In preparation for the CRA-2014 (U.S. DOE, 2014, Appendix PA, Section PA-1.1.8), the U.S. DOE modified the gas generation conceptual model to include a new brine-producing reaction, the conversion of hydromagnesite to magnesite (Clayton, 2013). The U.S. DOE reinstated the iron sulfidation reaction as part of the gas generation conceptual model and made corresponding changes to the chemical conditions conceptual model (Sect. 23.2) (U.S. DOE, 2014, Appendix PA, Section PA-4.2.5).

In preparation for the CRA-2019 (U.S. DOE, 2019, Appendix PA, Section PA-1.1), the U.S. DOE reversed the determination that radiolysis is insignificant and included gas generation from radionuclides in solution and in wetted-solid form in the conceptual model for gas generation (U.S. DOE, 2019, Appendix PA, Section PA-1.1.3). At the request of the U.S. EPA, the U.S. DOE again removed the iron sulfidation reaction as part of the gas generation conceptualmodel and made corresponding changes to the chemical conditions conceptual model (Sect. 23.2) (U.S. DOE, 2019, Appendix PA, Section PA-1.1.9).

22.3 Effect of proposed repository changes

The proposed additional panels do not present any changes to repository features or the properties of the waste that would affect the conceptual models for gas generation. Therefore, the gas generation conceptual model is not affected by the proposed additional panels.

Information Only

23 Chemical Conditions

23.1 Description in the CCA

The chemical conditions conceptual model is described in U.S. DOE (1996).

> *The chemical conditions of the repository are a major influence on actinide solubility. It has been estimated that under specific chemical conditions (low pH), the actinide solubility may increase over expected values by up to five orders of magnitude. This model has used engineering systems to limit such variability. DOE has assumed that equilibrium has been established between the brine in the repository (Castile or Salado), waste forms, and primary minerals. In addition to this basic chemical assumption, a series of other assumptions were made to help facilitate computer code calculations. The assumptions are discussed in further detail below. The defense of model assumptions is presented in Appendix SOTERM, which was not available for the peer review.*
>
> *Major variables in this conceptual model include brine compositions (fixed chemistry Salado and Castile brines), ligand concentrations, pH, fCO2, oxidation conditions, mineral stabilities, cement inventories, actinide inventories, and MgO backfill. Of these variables, some can be held constant because of the MgO backfill. The reaction of MgO and CO2 acts to buffer the pH of the repository and allows other variables to be fixed. The two major variables that will now be constrained are fCO2 (low fugacity) and pH (between 9 and 10, depending on brine composition).*
>
> *Certain assumptions are critical to this model. Brine and waste are modeled as a uniform mix of dissolved and solid phases. Thermodynamic equilibrium is assumed for dissolved actinides but not for redox reactions amongst the actinides. Further, chemical homogeneity and solubility equilibrium are assumed. This allows for the assumption of instantaneous reactions. Chemical microenvironments are not believed to persist for this reason. DOE assumes there will not be conditions whereby supersaturation can exist for long periods of time. Temperatures will increase a total of approximately 5.4°C (radioactive decay and exothermic reactions), and it is assumed that there will be negligible effects due to this increase.*
>
> *DOE believes that calculating mixing of brine from different sources is not amenable to performance assessment. Therefore brine compositions are fixed by performance scenarios. Undisturbed performance and E2 scenarios dictate the use of Salado brine. This is because the Castile Formation is not penetrated. Scenarios E1 and E1-E2 use Castile brine as the solvent for chemical conditions.*
>
> *Oxidation states of the repository are believed to be reduced. This judgment is based on the thought that available oxygen will be consumed early by oxic corrosion or aerobic microbes. Furthermore, large quantities of iron from 55-gallon drums are consumed by anoxic corrosion, producing hydrogen gas and ferrous iron. Although reducing conditions are expected, redox reactions between dissolved actinides in possible oxidation states are not addressed. DOE assumes this will produce conservative results and increase the total dissolved actinide source term.*

Information Only

Experimental data have shown that acidic conditions greatly enhance the solubility of actinides. Although cement materials in the waste will hydrate to $Ca(OH)_2$, CO_2 produced by microbial degradation of cellulosics will overwhelm this component and force the brine to low pH values. To reduce the potential for highly accelerated actinide dissolution, DOE decided to add MgO to the repository as backfill. The simplified reactions of concern are:

$$MgO + H_2O = Mg(OH)_2$$

$$Mg(OH)_2 + CO_2 = MgCO_3 + H_2O$$

In large enough quantities, the backfill will act as a getter of CO_2 and thereby buffer the liquid, produce low CO_2 fugacities, and provide alkaline conditions in the repository.

Because the addition of MgO will buffer the CO_2 fugacity, many processes that create time-dependent changes in the repository have been negated. The other assumptions imparted on the chemical conditions model, such as fixed ligand inventory, mineral equilibrium (halite, anhydrite, brucite), fixed brine compositions, and fixed actinide inventories have produced a fairly simple system. There is no need for a large computer code to replicate the conditions of the repository. Rather, fixed or calculated (EQ3/6) parameters (pH, fCO_2, phase equilibria, buffering equilibria) from this model are used as input to other, more complex conceptual models. (U.S. DOE, 1996, Appendix PEER 1 Section 3.22.1).

The major assumptions of the Chemical Conditions conceptual model have been listed in the model description above. To summarize, the assumptions are as follows:

1. *Brine and waste are modeled as a uniform mix of dissolved and solid phases.*
2. *Thermodynamic equilibrium is assumed for dissolved actinides but not for redox reactions among the actinides.*
3. *Chemical homogeneity and solubility equilibrium are assumed. This allows for the assumption of instantaneous reactions.*
4. *DOE assumes there will not be conditions whereby supersaturation can exist for long periods of time.*
5. *It is assumed that there will be negligible effects due to the temperature increase (by radioactive decay and exothermic reactions) of approximately 5.4°C.*
6. *Brine compositions are fixed by performance scenarios.*
7. *Oxidation states of the repository are assumed to be reduced.*
8. *All CO_2 will be fixed by available $Mg(OH)_2$, thereby buffering the pH of the repository.*
9. *Actinide and ligand inventories are fixed.*

Above text quoted from U.S. DOE (1996), Section 3.22.2.2.

Information Only

23.2 Changes since the CCA

In preparation for the CRA-2009, the U.S. DOE modified the Chemical Conditions conceptual model to reflect an assumption that anhydrite beds act as an unlimited source for sulfate for processes in the repository, namely microbial degradation of CPR, both before and after brine inundation (U.S. DOE, 2009, Appendix SOTERM, Section SOTERM-2.4.1.1).

In preparation for the CRA-2014, the U.S. DOE extended the Chemical Conditions conceptual model to account for brine production and consumption by: iron sulfidation, microbial degradation of CPR, MgO hydration, conversion of hydromagnesite to magnesite (U.S. DOE, 2014, Appendix PA, Section PA-4.2.5). Previously, the brine production and consumption model had considered only anoxic corrosion of steel.

23.3 Effect of proposed repository changes

The proposed additional panels do not present any changes to repository features or the properties of the waste that would affect the conceptual models for chemical conditions. Therefore, the chemical conditions conceptual model is not affected by the proposed additional panels.

Information Only

24 Dissolved Actinide Source Term

24.1 Description in the CCA

The dissolved actinide source term conceptual model is described in U.S. DOE (1996).

> *Actinides may be mobilized either by dissolution in brine as aqueous species, by bioaccumulation or sorption onto colloidal particles, or by condensation into colloidal forms as actinide-intrinsic colloids that could be carried by brine (see Section 6.4.3.6 for a discussion of colloidal actinides). The dissolved actinide source term model calculates the dissolved concentration of each actinide in solution by applying the modeled solubility for the particular oxidation state, as determined by the oxidation state distribution for that actinide, at the repository conditions presented in Section 6.4.3.4. Several oxidation states are not stable in the chemically reducing conditions described in Section 6.4.3.4. The unstable oxidation states are Np(VI), Pu(V), Pu(VI), and Am(V), as described in Appendix SOTERM (Section SOTERM.4).*
>
> *Thorium will exist only in the IV oxidation state (see Appendix SOTERM, Section SOTERM.4.1). Am and Cm will exist in only the III oxidation state (see Appendix SOTERM, Sections SOTERM.4.4 and SOTERM.4.5). For the remaining actinides, Pu, U, and Np, it is uncertain whether repository conditions will favor the lower or higher of the remaining oxidation states (see Appendix SOTERM, Sections SOTERM.4.2, SOTERM.4.3, and SOTERM.4.6). The DOE has captured the range of possible behavior by assuming that in half the realizations, conditions within the repository are extremely reducing and the solubility of all three of these actinides will be adequately represented by the solubility of their lower oxidation states. In the other half of the realizations, the solubilities of these actinides are well represented by the solubilities of the higher of the possible oxidation states. The factors controlling the aqueous actinide concentration in a possible oxidation state are equilibrium with anhydrite, halite, MgO, and brine.* [U.S. DOE, 1996, Section 6.4.3.5]
>
> *Several oxidation states can be screened out or substantially constrained. Oxidation states initially screened out are Np (4). Pu (+5), Pu (+6). and Am (+5). The screening rationale are described in Appendix SOTERM (not provided to the Panel for review). Actinides limited to a single oxidation state are Th (4). Am (+3), and Cm (+3). The model then assumes that the remaining three actinides will exist in only one oxidation state, but is unsure which of two possible states it will be. Therefore, the modeling assumes half the realizations will be in the reduced state (U +4, Np +4, and Pu +3) and half in the more oxidized state (U 4, Np +5, and Pu 4).*
>
> *As mentioned above, the dissolved actinide source term model incorporates a very critical assumption, that of oxidation state analogy. It assumes that all actinides in the same oxidation state (ex. +III) will form the same aqueous species and isostructural solid phases*. (U.S. DOE, 1996, Appendix PEER 1, Section 3.23.1).

24.2 Effect of proposed repository changes

The proposed additional panels do not present any changes to repository features or the properties of the waste that would affect the conceptual models for the dissolved actinide source term. Therefore,

Information Only

the conceptual model for the dissolved actinide source term is not affected by the proposed additional panels.

Information Only

25 Colloidal Actinide Source Term

25.1 Description in the CCA

The colloidal actinide source term conceptual model is described in U.S. DOE (1996).

> *Colloidal actinides are discussed in greater detail in Appendix SOTERM (Section SOTERM.6). Colloidal particles form in the repository by a variety of processes, including waste degradation, microbial activity, rock decomposition, and chemical condensation. These particles may also be carried into the repository by liquids moving from the Salado or through boreholes. Because of the presence of soils, nutrients, and cellulosic substrates for microbial action in WIPP waste (see Appendix BIR), humic substances and microbes will be present in disposal room brines, or may form in situ. Actinide-intrinsic colloids may form in the disposal rooms from condensation of dissolved actinides. Mineral fragments, as well as humic substances and microbes, may provide surfaces on which dissolved actinides may sorb.*
>
> *Four types of colloidal particles are believed to cover the range of possible behavior of all colloid types (see Appendix SOTERM, Section SOTERM.6.1.2). The four particle types considered in performance assessment are microbes, humic and fulvic acids (humic substances), actinide-intrinsic (intrinsic), and mineral fragments. The concentration of actinides carried by each colloidal particle type depends on many of the same chemical conditions that govern the concentration of dissolved actinides.*
>
> *Actinide concentration associated with humic substances and microbes are linked to dissolved actinide concentrations through proportionality constants based on experimental results. For humic substances, actinide complexation constants from WIPP-specific experiments or from published literature are coupled with experimentally determined site-binding densities and solubilities of different types of humic substances in WIPP brines. For microbes, actinide uptake was experimentally determined through experiments with WIPP-relevant bacteria cultures. Actinide concentrations associated with mineral fragment-type colloidal particles are estimated based on results from experiments designed to determine mobile concentrations in brines, coupled with site-binding densities of mineral substrates. For the Pu(IV)-polymer, actinide concentrations are determined through solubility experiments conducted from over- and undersaturation over a range of pmH values. Intrinsic colloids of other actinides were determined to be of negligible importance and are eliminated from performance assessment calculations. For more discussion on this topic refer to Appendix SOTERM (Section SOTERM.6.3.2.2).*
>
> *Actinides associated with microbes and humics are related to the concentration of dissolved dissolved actinides in the repository through proportionality constants determined from interpretation of WIPP-relevant experiments and the literature (Appendix SOTERM, Sections SOTERM.6.3.3 and SOTERM.6.3.4). The proportionality-constant relationship is not based rigorously on thermodynamic equilibrium but is simply an empirical relationship. The concentration of actinides associated with the Pu(IV)-polymer is a constant value determined from experimental results at the pmH conditions dictated by the presence of MgO backfill. Likewise, the concentration of actinides associated with mineral colloids is also a constant value,*

Information Only

not linked to the concentration of dissolved actinides. Actinides associated with humics and microbes represent most of the colloidal actinide source term. Consequently, the colloidal actinide source term is closely related to the dissolved actinide source term. As discussed in Section 6.4.6.2, however, the source terms are considered separately for transport in the Culebra. (U.S. DOE, 1996, Section 6.4.3.6).

The Colloidal Actinide Source Term conceptual model describes the concentration of actinides sorbed to or contained in mobile colloidal particles in the disposal rooms and also describes the stable colloids that must be quantified for transport in the Culebra. The actinides addressed with this model are thorium (Th), uranium (U), neptunium (Np), plutonium (Pu), americium (Am), and curium (Cm). Presently, transport of colloids in the Culebra have not been rigorously modeled because of the complexities of coupling hydrogeology, geochemistry, and colloid chemistry. Because of the chemical complexities of the integrated system and high ionic strength brines present, an attempt has been made to characterize the major colloid types believed to be present in the repository.

The four types described are "hard sphere" carrier colloids (mineral fragments), microbes, soft sphere carrier colloids or hydrophilic colloids (humic and fulvic acids), and intrinsic colloids (true colloids). These particles develop from a variety of processes in the repository, including waste degradation, microbial activity, rock decomposition, and chemical condensation. Intrinsic colloids form by condensation of dissolved actinides in the disposal rooms. Mineral fragments and humic substances provide surfaces that dissolved actinides may sorb to. Microbes actively bioaccumulate actinides intracellularly and also act as substrates for surficially extracellular sorption (Francis 1985).

Four major decisions have been made that greatly simplify this conceptual model. First, DOE has elected to disregard the effects of competition associated with the equilibrium between dissolved actinides and actinides associated with colloidal particles. Therefore, the two source terms are not inexorably linked, resulting in an overestimation of the total concentration of mobile actinides that may leave the repository. Second, in the event that the sum of the concentrations of the dissolved actinide and colloidal actinide source terms for a particular element exceed the inventory limited concentration of that element, then a partitioning scheme is utilized. Instead of basing the partitioning on an equilibrium approach, DOE has decided to use an approach based on conservatism. The concentration of a particular actinide in the inventory is first made available to the most efficient transport mode. If the inventory is not used up, then the next most efficient transport mechanism is filled. This rationale is continued until the inventory is exhausted by assignment to the five groups of transport vehicles (four colloidal and dissolved actinide source terms). Third, thermodynamic equilibrium is achieved by actinide intrinsic and humic colloids. And fourth, DOE has assumed that microbes and mineral fragments are present in constant quantities in the aqueous phase. This allows a steady state quantity on which the actinides can sorb.

Because of the effect of high ionic strength brines on mineral fragment colloids, which collapses the electric double layer surrounding the colloid, Van der Waals forces can cause agglomeration and settling of such colloids. Laboratory experiments using WIPP brines indicate that this settling effect largely negates mineral fragments as an effective transport mechanism. Thus,

Information Only

> *DOE has conservatively assigned a mineral fragment concentration for each actinide to be 10^{-9} m/L, one order of magnitude higher than the detection limit of the experiments.* (U.S. DOE, 1996, Appendix PEER 1, Section 3.24.1).

Note that the cited value of 10^{-9} m/L for the mineral fragment concentration in the quoted text is different from the value of 2.6×10^{-8} m/L used in the CCA (U.S. DOE, 1996, Appendix SOTERM, Table SOTERM-14).

> *Microbes have a large study base at WIPP, primarily to provide data for the gas generation program. This information has also been helpful in the Colloidal Actinide Source Term model. The source term concentrations associated with microbes are based on actinide uptake experimentally determined from experiments with relevant bacteria cultures.*
>
> *Humic and fulvic acids are of particular concern because of their well known capability to complex metal cations, including actinides. These soft sphere carrier colloids are not affected by high ionic strength brines, so they may be important in the transport of actinides at WIPP. To determine humic substance concentrations, actinide complexation constants from WIPP experiments or from literature are coupled with site binding densities and solubilities of humic substances in WIPP brines.*
>
> *Intrinsic colloids are well represented by the Pu(IV) polymer. The mechanism of formation of this polymer has not yet been identified; however, it is known to be stable in high concentrations in highly acidic environments. There is some evidence that the polymerization is strongly linked to hydrolysis, and that it produces an amorphous macromolecule that becomes crystalline with time. This polymer is typically on the order of nanometer size range. Hence, it is assumed to act like a hard sphere carrier colloid. … Other actinide intrinsic colloids (especially Am) were found to have negligible importance.* (U.S. DOE, 1996, Appendix PEER 1, Section 3.24.1).

25.2 Effect of proposed repository changes

The proposed additional panels do not present any changes to repository features or the properties of the waste that would affect the conceptual models for the colloidal actinide source term. Therefore, the conceptual model for the colloidal actinide source term is not affected by the proposed additional panels.

Information Only

26 References

Burgess, A., T. Doe, T. Lowenstein, and J.A. Thies. 2008. Waste Isolation Pilot Plant Culebra Hydrogeology Conceptual Model Peer Review Final Report. Carlsbad, NM: U.S. Department of Energy. ERMS 551513

Clayton, D. 2013. Justification of Chemistry Parameters for Use in BRAGFLO for AP-164, Rev. 1. March 13, 2013. Sandia National Laboratories, Carlsbad, NM. ERMS 559466.

Hansen, C.W. 2020. Analysis Plan for the Additional Panels Performance Assessment. AP-185, Revision 0. June 8, 2020. Sandia National Laboratories, Carlsbad, NM. ERMS 573557.

Kirkes, R. 2021. Features, Events and Processes Assessment for the Additional Panels Performance Assessment. Date. Sandia National Laboratories, Carlsbad, NM. ERMS 574493.

Nemer, M. and J. Stein. 2005. Analysis Package for BRAGFLO: 2004 Compliance Recertification Application Performance Assessment Baseline Calculation. July 27, 2005. Sandia National Laboratories, Carlsbad, NM. ERMS 540527

Sandia National Laboratories (SNL). 2003. Design Document for DRSPALL Version 1.00, Document Version 1.10. September 9, 2003. Sandia National Laboratories, Carlsbad, NM. ERMS 529878

Sjomeling, D. 2019. "2:30 Meeting Information," an email to Paul Shoemaker with the attachment "West Mains and Panels peer review info Final 091219.pdf." Nuclear Waste Partnership LLC, Carlsbad, NM. October 17, 2019. ERMS 572682.

The Earth Technology Corporation. 1987. Final Report for Time Domain Electromagnetic (TDEM) Surveys at the WIPP Site. SAND87-7144. Prepared for Sandia National Laboratories, Albuquerque, New Mexico.

U.S. Department of Energy (DOE). 1996. Title 40 CFR 191 Compliance Certification Application for the Waste Isolation Pilot Plant. DOE/CAO-1996-2184. U.S. Department of Energy, Carlsbad Area Office, Carlsbad, NM.

U.S. DOE . 2004. Title 40 CFR Part 191 Compliance Recertification Application for the Waste Isolation Pilot Plant. 10 vols. DOE/WIPP 2004-3231. U.S. Department of Energy, Carlsbad Field Office, Carlsbad, NM.

U.S. DOE. 2009. Title 40 CFR Part 191 Compliance Recertification Application for the Waste Isolation Pilot Plant. DOE/WIPP 2009-342. U.S. Department of Energy, Carlsbad Field Office, Carlsbad, NM.

U.S. DOE. 2014. Title 40 CFR Part 191 Compliance Recertification Application for Waste Isolation Pilot Plant. DOE/WIPP 2014-3503. U.S. Department of Energy, Carlsbad Field Office, Carlsbad, NM.

U.S. DOE. 2019. Title 40 CFR Part 191 Compliance Recertification Application for the Waste Isolation Pilot Plant. DOE/WIPP-19-3609. U.S. Department of Energy, Carlsbad Field Office, Carlsbad, NM.

U.S. Environmental Protection Agency (EPA). 1998a. Technical Support Document for Section 194.23: Parameter Justification Report. EPA Air Docket A93-02-V-B-14. Washington, DC: U.S. Environmental Protection Agency Office of Radiation and Indoor Air.

Information Only

U.S. EPA. 1998b. Compliance Application Review Documents for the Criteria for the Certification and Recertification of the Waste Isolation Pilot Plant's Compliance with the 40 CFR Part 191 Disposal Regulations: Final Certification Decision. CARD 14: Content of Compliance Application. EPA Air Docket A93-02-V-B-2. Washington, DC: U.S. Environmental Protection Agency Office of Radiation and Indoor Air.

U.S. EPA. 2006a. Technical Support Document for Section 194.23 Review of the 2004 Compliance Recertification Performance Assessment Baseline Calculation. EPA Air Docket A98-49-II-B1-16. Washington, DC: U.S. Environmental Protection Agency Office of Radiation and Indoor Air.

U.S. EPA. 2006b. 40 CFR Part 194 Criteria for the Certification and Recertification of the Waste Isolation Pilot Plants Compliance with the Disposal Regulations: Recertification Decision. Fed. Reg. Vol. 71. No. 68, pp. 18010-180921.

U.S. EPA. 2017a. Technical Support Document for Section 194.23, EPA Review of Proposed Modification to the Waste Shear Strength Parameter TAUFAIL. July 2017. Office of Radiation and Indoor Air.

U.S. EPA. 2017b. Technical Support Document for the Probability of Encountering Castile Brine Beneath the WIPP Waste Panels Using the TDEM Block Method. June 2017. Washington, DC: Office of Radiation and Indoor Air.

Zeitler, T.R. 2019. A Summary of EPA/DOE Defined Parameters to be Implemented in the CRA-2019 PA. Carlsbad, NM: Sandia National Laboratories. ERMS 570879.

Information Only