# U.S. DEPARTMENT OF ENERGY CARLSBAD FIELD OFFICE

### **QUALITY ASSURANCE PROGRAM DOCUMENT**

DOE/CBFO-94-1012

**REVISION 14** 



Effective: November 06, 2023

This document supersedes DOE/CBFO-94-1012, Revision 13.



### **Department of Energy**

Washington, DC 20585

July 21, 2023

MEMORANDUM FOR MARK BOLLINGER

MANAGER

CARSLBAD FIELD OFFICE

FROM: GREGORY SOSSON, PE GREGORY SOSSON Date: 2023,07.21 12:47:32 -04'00

DEPUTY ASSISTANT SECRETARY FOR

SAFETY, SECURITY, AND QUALITY ASSURANCE

SUBJECT Approval of the U.S. Department of Energy, Carlsbad Field

Office (CBFO), Quality Assurance Program Document (QAPD),

DOE/CBFO-94-1012, Revision 14

The Department of Energy (DOE) Office of Environmental Management (EM), Office of Standards and Quality Assurance (EM-3.113) has completed review of the submittal of the CBFO QAPD, Revision 14.

During the review, it was noted that the QAPD referenced DOE Order (O) 414.1D, *Quality Assurance*, instead of the current revision (Change 2) of DOE Order. EM-3.113 confirmed with your staff that CBFO QAPD, Revision 14 was prepared using DOE O 414.1D (Change 2). To ensure proper documentation of requirements and prior to implementation, ensure the CBFO QAPD, Revision 14 is updated to reflect that DOE O 414.1D (Change 2) was used in the preparation of the revision. Resubmittal of the QAPD is not necessary for this directed change.

Pursuant to DOE Order 414.1D (Change 2), the CBFO QAPD is approved for implementation with the directed change noted above.

If you have any questions or concerns, please feel free to contact Michael Pribish at (865) 221-0246 or michael.pribish@orem.doe.gov.

cc: Darren Jolley, CBFO
Gregory Sosson, EM-3 (Acting)
John Jones, EM-3
Kristen Ellis, EM-4 (Acting)
Dae Chung, EM-5
Brenda Hawks, EM-3.11
Michael Pribish, EM-3.113
Jim Davis, EM-3.113

### memorandum

Carlsbad Field Office Carlsbad, New Mexico 88221

DATE: 8/3/2023

REPLY TO

ATTN OF: CBFO:QAD:DMJ:AB:23-0521

SUBJECT: Interim Change Notice #1 for DOE/CBFO-94-1012, Carlsbad Field Office Quality

Assurance Program Document, Revision 14

то: Distribution

Interim Change Notice (ICN) #1 to the DOE/CBFO-94-1012, *Carlsbad Field Office Quality Assurance Program Document*, Revision 14, is effective November 6, 2023. This ICN is necessary to address the following process clarifications:

To ensure proper documentation of requirements and for the implementation of Revision 14 of the *Carlsbad Field Office Quality Assurance Program Document* (CBFO QAPD), it was verified by the U.S. Department of Energy (DOE) Office of Environmental Management (EM), Office of Standards and Quality Assurance (EM-3.113), that the CBFO QAPD, Revision 14, was prepared utilizing DOE Order 414.1D (Change 2), the most current version of the Order.

All references to DOE Order 414.1D, *Quality Assurance*, represent equivalency to DOE Order 414.1D (Change 2).

If you have any questions regarding this ICN, please contact me at (575) 725-1567.

DARREN JOLLEY Digitally signed by DARREN JOLLEY Date: 2023.08.03 16:31:41-06'00'

Darren Jolley, Director CBFO Quality Assurance Division

# U.S. DEPARTMENT OF ENERGY CARLSBAD FIELD OFFICE

### **QUALITY ASSURANCE PROGRAM DOCUMENT**

### DOE/CBFO-94-1012

#### **REVISION 14**



Effective: November 06, 2023

Prepared by: /Signature on File/ 06/21/2023

Darren Jolley Date

Director, CBFO Quality Assurance Division

Approved by: /Signature on File/ 06/21/2023

Mark Bollinger Date

Manager, Carlsbad Field Office

#### **POLICY STATEMENT**

The Carlsbad Field Office (CBFO) manages the U.S. Department of Energy (DOE) National TRU Program, including the Waste Isolation Pilot Plant (WIPP). The mission of the CBFO is the safe, permanent disposal of transuranic (TRU) waste from generator sites across the nation in the deep geologic repository at WIPP. To meet this mission, the CBFO manages compliant and efficient characterization, packaging, transportation, and disposal of defense TRU waste from the generator sites to the WIPP. The CBFO is a key representative in international technical and policy forums to improve global management of radioactive waste.

The CBFO implements a Quality Assurance (QA) program to help fulfill this mission. The CBFO QA program complies with applicable federal, state, and local regulations and with DOE orders and requirements.

The CBFO works to establish a culture and work environment that promotes safety and compliance, encourages setting and maintaining effective standards, identifies and resolves problems, emphasizes a continual pursuit of improvement, and fosters mutual respect and effective communication within the CBFO and among its participants, their suppliers, the public, and other stakeholders.

The CBFO *Quality Assurance Program Document* (QAPD) establishes QA program requirements for achieving quality for all work sponsored by the CBFO, using a graded approach. The CBFO and organizations supporting the CBFO shall implement the applicable requirements of this QAPD within their systems for management and control of these activities.

It is the responsibility of all personnel assigned to CBFO-sponsored activities to promote quality; identify, document, and resolve concerns when possible; and recommend and implement improvement to the quality of items, services, and processes. The CBFO Quality Assurance Division independently verifies the achievement of quality. The CBFO managers establish and cultivate principles and practices that integrate QA program requirements and performance standards into their management practices and control systems. Additionally, CBFO managers continually provide their staff with the proper training, resources, oversight, and support to achieve the qualifications necessary to fulfill CBFO organizational and mission objectives.

The CBFO QA program requirements described in this QAPD have my full endorsement and complete support. Implementation of the applicable QAPD requirements, responsibilities, and authorities is mandatory for all CBFO personnel.

In support of this policy statement, all CBFO personnel are expected to demonstrate their personal commitment to the achievement of quality through their active involvement in the implementation of the CBFO QA program.

/Signature on File/	06/21/2023
Mark Bollinger	Date
Manager, Carlsbad Field Office	

#### **CHANGE HISTORY**

#### Revision:

### Changes to the QAPD

- Rev. 1 The QAPD has been substantially rewritten, the structure has been reorganized, and the content has been supplemented to broaden its scope from a CAO internal requirements and participant guidance document to a CAO program-wide requirements document. The document elements that defined the extent of applicability regarding specific QA program requirements have been clarified through the identification of "general" and "additional" requirements. Requirements for the grading of management controls have been clarified and more fully developed. The requirement for Sandia National Laboratories (SNL) and Westinghouse Waste Isolation Division (WID) QAPDs was deleted. A requirement was added for each organization to prepare, submit for review, and maintain a QA implementing procedures matrix. Revisions were made to incorporate all the requirements of 40 CFR Part 194, ANSI/NCSL Z540-1, and stakeholder comments. The use of the terms "will" and "shall" are interchangeable and denote requirements. Editorial changes were made throughout.
- Rev. 2 The section describing the organization and responsibilities for CAO personnel have been deleted from section 1 and incorporated into a policy statement (Appendices C and D). The QA program document hierarchy (Table I-1) has been updated to reflect current regulatory requirements commitment and guidance documents.

Requirements have been clarified in the areas of 1) grading, 2) the control of conditions adverse to quality, and 3) the preparation and maintenance of document review comments.

Section 6.0, *Software*, has been rewritten to include both general and additional requirements. Definitions in the glossary have been added, deleted, and clarified. Editorial changes have been made throughout the document.

Rev. 3 Changes in Revision 3 have been limited to those necessary to achieve full compliance with the Waste Analysis Plan (WAP) in the WIPP Hazardous Waste Facility Permit and to incorporate certain TRU waste QA requirements contained in the CAO QAPP, which is to be inactivated. Refer to the following list of pages affected by Revision 3.

### List of Pages Affected by QAPD Revision 3

Change History	iv to v
Table of Contents	vi to xii
List of Acronyms	xiii to xiv
Introduction	I-1 to I-2
Section I - Management	1-1 to 1-23
Appendix A - Glossary	A-1 to A-10
Appendix B - References	B-1
Appendix C - CAO Organization	C-1 to C-2
Appendix D - CAO QA Manager Responsibilities	D-1 to D-2
Appendix E - TRU Sites Organization	E-1 to E-4

The pages in Revision 3 that are not listed above (sections 2.0 through 6.0) remain effective.

Rev. 4 The changes in Revision 4 were made to incorporate the DOE name change from the Carlsbad Area Office (CAO) to the Carlsbad Field Office (CBFO) and reflect current CBFO organization titles and responsibilities, rewrite the Quality Improvement section, update the source requirements documents listed in Table I-1, make changes to capture the wording used in the requirements documents, add more specific detail to the QA functional responsibilities of the CBFO management, and eliminate divisions between "general requirements" and "additional requirements." Editorial, formatting, and paragraph number changes have been made throughout the document. Change markings are present for those revisions that affect content. Changes related to editorial and formatting

specific sections:

	List of Acronyms and Abbreviations	ix - x
Table I-1	QA Program Source Documents	xii
1.1.1	Organization	1-1
1.1.1.4.B	Interface Responsibilities	1-4
1.1.2.2	Procedures Matrix	1-5
1.1.2.3	Applicability of QAPD Requirements	1-5
1.1.2.4	Grading Items and Activities and Applying Management Controls	1-6
1.2.1	Qualification Requirements	1-8
1.2.2	Training Requirements	1-8
1.3	Quality Improvement	1-9 to 1-15

revisions are not marked. Technical revisions were made to the following

1.4.B	Documents	1-15
1.5.2	Generating QA Records	1-17 to 1-18
1.5.4	Classifying QA Records	1-19 to 1-20
1.5.6.1	Records Classification and Disposition	1-22
2.1.3.A	Item Identification and Control	2-2
2.2	Design Control	2-5
2.2.9	Design Change	2-11
2.3.5.A	Procurement Document Review and Approval	2-14
2.3.7.1	Source Verification	2-16
2.3.7.4	Supplier Certificate of Conformance	2-17
2.3.9	Commercial Grade Items	2-18
2.4.2	Qualification of Nondestructive Examination Personnel	2-21
3.2.A	Independent Assessment	3-1
3.2.2.8.B	Reporting Audit Results	3-8 to 3-9
5.4	Qualification of Existing Data	5-4 to 5-6
5.5	Quality Assurance Compliance Data (new section)	5-6
Appendix A	Glossary	A-1 to A-2, A-5 to A-7, A-9 to A-10
Appendix C	CBFO Organization, Responsibilities, and Interfaces	C-1
Appendix D	CBFO Quality Assurance Manager Responsibilities	D-1 to D-2
Appendix E	TRU Waste Characterization and Certification Organizational and Individual Responsibilities	E-1

Rev. 5 The changes in revision 5 were made to address an Environmental Protection Agency (EPA) finding from the annual EPA QA audit conducted on January 7 – 9, 2003. This finding concerned the language in the QAPD regarding the responsibilities for achievement and verification of quality not matching the requirements from NQA-1. In addition to the change made to address the EPA finding, the following changes were made:

- The requirement for program participants to maintain a QAPD procedures matrix has been deleted; because this matrix is not required by NQA-1, 2, or 3, or other regulatory document.
- The requirement for organizations receiving records to return a receipt acknowledgment to the sender has been deleted, because this also is not required by NQA-1, 2, or 3, or other regulatory document.
- The requirement that CBFO and participant organization ensure that they comply with the Federal Acquisition Regulations was deleted because the QAPD is not the appropriate document to specify this requirement.
- The requirement to maintain records related to the characterization of the mixed transuranic waste form as lifetime QA records was deleted. Records classification of mixed waste characterization records is specified in the Hazardous Waste Facility Permit.
- The requirement to maintain audit and surveillance checklists as QA records was deleted, because this is not a requirement of NQA-1, 2, or 3, or other regulatory document.
- The requirement for calibration laboratories to comply with ANSI/NCSL Z540-1 was deleted because this is not a requirement of NQA-1, 2, or 3, or other regulatory document.
- The safety analysis report for the HalfPACT shipping package was added as a regulatory source document to Table I-1
- Section 5.5 was deleted. The requirements for data quality evaluation during scientific investigation planning are addressed in Section 5.1.G of the QAPD. Section 5.5 was redundant and specified requirements for the content of compliance applications, which was not appropriate for the QAPD.
- Changes were also made to correct typographical errors and incorrect section references.

Technical revisions were made to the following specific sections:

Section	Section Title
	Policy Statement
	Introduction
1.1.1	Organization
1.1.1.1.D	Management
1.1.1.3	Quality Assurance Management
1.1.2.2	Procedures Matrix (deleted)
1.2.1	Qualification Requirements
1.3.2.5	Disposition of Nonconforming Items or Data
1.5.4.B and E	Classifying QA Records
1.5.6.A	Storage, Preservation, Safekeeping, and Disposition of
	QA Records
2.1.B	Work Processes

2.3	Procurement
2.3.4	Procurement Document Requirements
2.4.6	Use and Control of M&TE
2.4.7	Calibration
3.2.2.10	Audit Records
Appendix C	CBFO Organization, Responsibilities, and Interfaces
Appendix D	CBFO Quality Assurance Manager Responsibilities

Rev. 6 The changes in Revision 6 were made to implement the new CBFO organization chart that was approved on May 15, 2004.

Revisions were made to the following specific sections:

	List of Acronyms and Abbreviations
	Introduction
Appendix C	CBFO Organization, Responsibilities, and Interfaces
Appendix D	CBFO Quality Assurance Manager Responsibilities
Appendix E	TRU Waste Characterization and Certification
	Organizational and Individual Responsibilities

Rev. 7 The changes in Revision 7 were the direct result of DOE EM 3-2 comments relative to compliance with DOE O 414.1B.

Revisions were made to the following specific sections:

Policy Statement
List of Acronyms and Abbreviations
Section 1.3
Section 2.3
Program Source Documents
Appendices C and D

Rev. 8 The changes in Revision 8 were made to address thirteen minor findings and one concern from an EPA inspection of CBFO's QA program (Ref: Letter from Gitlin to Moody dated April 18, 2006). Document citations were added to include remote-handled waste packaging. The exemption of National Environmental Policy Act (NEPA)-related software from the requirements of the QAPD was deleted. The applicability of software QA to safety software was clarified. Editorial changes related to the June 26, 2006 reorganization of the CBFO were also incorporated.

	List of Acronyms and Abbreviations
	Introduction
1.1.2.1	Quality Assurance Program Documents

1.2.2	Training Deguirements
	Training Requirements
1.3.2.3	Reporting Nonconformances
1.5.3	Indexing QA Records
1.5.6	Storage, Preservation, Safekeeping, and Disposition of
	QA Records
1.5.6.1	Records Disposition
2.3.1	Procurement Planning Requirements
2.3.7	Acceptance of Items or Services
2.3.8	Control of Supplier Nonconformances
2.4.2	Qualification of Nondestructive Examination Personnel
2.4.7	Calibration
3.2.2.1	Scheduling Audits
6.1	Applicability
6.6.2.4	Testing Phase
6.7.3	Validation
Appendix A	Glossary
Appendix B	References
Appendix C	CBFO Organization, Responsibilities, and Interfaces
Appendix D	CBFO Quality Assurance Manager Responsibilities
Appendix E	TRU Waste Characterization and Certification
	Organizational and Individual Responsibilities

Rev. 9 The QAPD was revised to clarify that reliance on administrative controls alone is not sufficient for differentiating between waste that is acceptable for shipment to WIPP and waste that does not meet the WIPP waste acceptance criteria. The classification of conditions adverse to quality related to the Hazardous Waste Facility Permit was also clarified. The language regarding reporting nonconformances was revised to comport with the November 16, 2006 Permit Modification. The requirements for records disposition were revised to comport with the Class 1 Permit Modification that was approved by NMED on September 13, 2007.

Revisions were made to the following specific sections:

1.3.2.3	Reporting Nonconformances
1.3.2.4	Segregating Nonconforming Items
1.3.3.2	Classification of Conditions Adverse to Quality
1.3.3.5	Corrective Action Planning
1.5.6.1	Records Disposition

Rev. 10 The QAPD was revised to address CBFO Corrective Action Report (CAR) 08-026 regarding the adequacy of the test control requirements as stated in Rev. 9 of the QAPD. The requirement for the use of administrative controls to differentiate waste that is acceptable for shipment to WIPP was clarified to address as low as reasonably achievable (ALARA) considerations for remote-handled waste. Editorial revisions to the reference document sections were made to address changes to

documents since the last revision of the QAPD. Several minor clarification changes were made in response to comments during CBFO internal review. Revisions were also made to address the recent reorganization of CBFO.

Revisions were made to the following specific sections:

1.3.2.4	Segregating Nonconforming Items
1.3.3.2	Classification of Conditions Adverse to Quality
1.5.2	Generating QA Records
1.5.3	Indexing QA Records
1.5.6	Storage, Preservation, Safekeeping, and Disposition of
	QA Records
1.5.6.1	Records Disposition
2.4.4	Test Requirements
Appendix B	References
Appendix E	TRU Waste Characterization and Certification
	Organizational and Individual Responsibilities

Rev. 11 The QAPD was revised to comport with the April 1, 2010, Permit Modification. The time allowed for reporting nonconformances to data quality objectives first identified at the Site Project Manager Level was changed from 5 to 7 days.

Revisions were made to the following specific sections:

1.3.2.3 Reporting Nonconformances
-----------------------------------

Rev. 12 The QAPD was revised to address updates/revisions to the acronyms list, CBFO organizational position description changes, consistent use of the term HWFP for references to the Permit or RCRA language, revised requirements/commitment documents, addition of the TRUPACT-III and associated certificate of compliance, identification of the current management and operating contractor, management of nonconformances, procurement requirements, additions/corrections to the glossary, additions/corrections to the reference list, and minor editorial/grammatical changes throughout the document.

Policy Statement	
List of Acronyms and Abbreviations	
Introduction	
Table I-1 QA Program Source Documents	
Section 1.1.1 Organization	
Section 1.1.1.1 Management	
Section 1.1.1.2	Employees
Section 1.1.1.3	QA Management

Section 1.1.1.4	Communication and Interface Responsibilities	
Section 1.1.1.6	· · · · · · · · · · · · · · · · · · ·	
Section 1.1.2.1	Quality Assurance Program Documents	
Section 1.1 2.2		
Section 1.1.2.3		
	Management Controls	
Section 1.2.1	Qualification Requirements	
Section 1.2.2	Training Requirements	
Section 1.3	Quality Improvement	
Section 1.3.2.3	Reporting Nonconformances	
Section 1.3.3.2	Classification of Conditions Adverse to Quality	
Section 1.3.3.3	Remediation of Conditions Adverse to Quality	
Section 1.3.3.4	Significant Conditions Adverse to Quality	
Section 1.3.3.5	Corrective Action Plans	
Section 1.3.3.7	Corrective Action Follow-up	
Section 1.3.3.8	Recurring Conditions Adverse to Quality	
Section 1.4.3		
Section 1.5	Records	
Section 1.5.1		
Section 1.5.2	- J - 1	
Section 1.5.3	Classifying QA Records	
Section 1.5.5.1		
Section 1.5.6	Correcting Information in QA Records	
Section 2.1.3	Item Identification and Control	
Section 2.2.2	Design Process	
Section 2.2.8	Qualification Testing	
Section 2.3	Procurement	
Section 2.3.4	Procurement Document Requirements	
Section 2.3.7.1		
Section 2.3.9	Commercial Grade Items	
Section 2.4.1	Qualification of Inspection and Test Personnel	
Section 2.4.4	Test Requirements	
Section 2.4.4.1	Test Planning	
Section 3.2	Independent Assessment	
Section 6.1		
Section 6.4.2	NQA-2 Part 2.7 Requirements for Software	
Procurement		
Section 6.6.2	NQA-2 Part 2.7 Requirements	
Appendix A	Glossary	
Appendix B	References	
Appendix C	CBFO Organization, Responsibilities, and Interfaces	
Appendix D Responsibilities of the Director of the CBFO Quality		
	Assurance Division	
Appendix E	TRU Waste Characterization and Certification	
	Organizational and Individual Responsibilities	

Rev. 13 The QAPD was revised to make changes to section 6 – Software Requirements. Basis of changes was software applicability defined in ASME NQA-2-1990 Part 2.7 and DOE O 414.1D. Major changes to section 6 include the applicability of software to the QAPD. The requirements for software applicability have been updated and clarified to determine which software must be evaluated against the QAPD. Software is to be classified based on the impact of the software using a graded approach. Requirements for software procurement have been revised requiring the organization providing software services to provide a Software Quality Assurance plan that is to be reviewed and approved by the purchaser. Requirements for software used in design analysis have been added. Other changes were made to sections covering commercial grade dedication of software, software developed under other QA programs, the software development life cycle, software verification and validation, software configuration management, documentation, problem reporting and corrective action, access control and support software. Minor editorial/grammatical changes were also incorporated throughout the document.

	Table of Contents	
	List of Acronyms and Abbreviations	
Table I-1 QA Program Source Documents		
Section 1.1.1	Organization	
	ŭ	
Section 1.2.2	Training Requirements	
Section 1.3.2.2	Identifying Nonconforming Items or Data	
Section 1.3.2.3	Reporting Nonconformances	
Section 1.3.3.5	Corrective Action Plans	
Section 1.3.3.9	Quality Trending	
Section 1.5.6	Records Disposition	
Section 2.2	Design Control	
Section 2.2.2	Design Process	
Section 2.2.3	Design Analyses	
Section 2.3.9	Commercial Grade Items	
Section 2.4.4.1	Test Planning	
Section 5.4	Qualification of Existing Data	
Section 3.2.2.6	Lead Auditor Qualification	
Section 6	Software Requirements	
Section 6.1	Applicability	
Section 6.2	Basic Requirements for Inventory and Classification	
	of Software	
Section 6.3.1	Basic Requirements for Software Quality Assurance	
Section 6.4.1	Basic Requirements for Software Procurement	
Section 6.4.2	NQA-2 Part 2.7 Supplemental Requirements for	
	Software Procurement	
	<u> </u>	

Section 6.5	Software Used in Design Analysis	
Section 6.5.1	Software Used in Design Analysis	
Section 6.5.1	n 6.5.1 Basic Requirements for Software Used in Design Analysis	
Section 6.6 Software Developed Under Other QA Programs		
Section 6.6.1 Basic Requirements for Software Developed Und Other QA Programs		
Section 6.6.2	Supplemental Requirements for Software Developed	
Section 0.0.2	Under Other QA Programs	
Section 6.7	Software Development and Life Cycle	
Section 6.7.1	Basic Requirements for Software Development and	
	Life Cycle	
Section 6.7.2	NQA-2 Part 2.7 Supplemental Requirements for	
	Software Development and Life Cycle	
Section 6.7.2.1	Requirements Phase	
Section 6.7.2.2	Design Phase	
Section 6.7.2.3	Implementation Phase	
Section 6.7.2.4		
Section 6.7.2.5	Installation and Check Out	
Section 6.7.2.6	Operations and Maintenance Phase	
Section 6.7.2.7		
Section 6.8	Software Verification and Validation	
Section 6.8.1	Basic Requirements for Verification and Validation	
Section 6.8.2	Section 6.8.2 NQA-s Part 2.7 Supplemental Requirements for	
Verification and Validation		
Section 6.8.2.1	Verification	
Section 6.8.2.2	Requirements	
Section 6.8.2.3	Design	
Section 6.8.2.4	Implementation	
Section 6.8.2.5	Testing	
Section 6.8.3	Validation	
Section 6.9	Software Configuration Management	
Section 6.9.1	Basic Requirements for Software Configuration	
	Management	
Section 6.9.2	NQA-2 Part 2.7 Supplemental Requirements for	
	Software Configuration Management	
Section 6.9.2.1	Configuration Identification	
Section 6.9.2.2	Configuration Change Control	
Section 6.9.2.3		
Section 6.10	Documentation	
Section 6.10.1	Basic Requirements for Documentation	
Section 6.10.2	NQA-2 Part 2.7 Supplemental Requirements for	
	Documentation	
Section	Procurement Documentation	
6.10.2.1		
Section	Requirements Documentation	
6.10.2.2		

Section	Design and Implementation Documentation	
6.10.2.3	Besign and implementation Becamentation	
Section	Verification and Validation Documentation	
6.10.2.4		
Section	Change Documentation	
6.10.2.5	onange z commentation	
Section	User Documentation	
6.10.2.6		
Section	Error Documentation	
6.10.2.7		
Section 6.11	Problem Reporting and Corrective Action	
Section 6.11.1 Basic Requirements for Problem Reporting and		
	Corrective Action	
Section 6.11.2	NQA-2 Part 2.7 Supplemental Requirements for	
	Problem Reporting and Corrective Action	
Section 6.12	Access Control	
Section 6.13	Support Software	
Section 6.13.1	Software Tools	
Section 6.13.2	System Software	
Appendix A	Glossary	
Appendix B		
Appendix C	CBFO Organization, Responsibilities, and Interfaces	
Appendix D	Responsibilities of the Director of the CBFO Office of	
	Quality Assurance	
Appendix E	TRU Waste Characterization and Certification	
	Organization and Individual Responsibilities	

Rev. 14 The QAPD was revised to address management assessment results, audit results from EM QA, and updates to EM-QA-001. Additionally, revisions were made to address the newly published DOE transportation and records management orders. Finally, updates were incorporated to update this document as a result of recent CBFO reorganization. Due to the extensive changes, no change bars are present.

	Policy Statement	
	List of Acronyms and Abbreviations	
Introduction		
Table I-1 QA Program Source Documents		
1.1	Organization and Quality Assurance Program	
1.1.1	Organization	
1.1.1.1	Management	
1.1.1.2	Employees	
1.1.1.3	QA Management	
1.1.1.4	Communication and Interface Responsibilities	

1.1.1.6	Resolution of Disputes	
1.1.2.2	Applicability of QAPD Requirements	
1.1.2.3	Grading Items and Activities and Applying	
	Management Controls	
1.1.2.4	Planning Work	
1.1.2.5	Deleted	
1.2.2	Training Requirements	
1.3.2.3	Reporting Nonconformances	
1.3.3.1	Identifying Conditions Adverse to Quality	
1.3.3.4	Significant Conditions Adverse to Quality	
1.4.1	Document Preparation, Review, Approval, and	
	Issuance	
1.4.3	Document Changes	
1.5	Records	
1.5.1	Generating QA Records	
1.5.3	Classifying QA Records	
1.5.8	Electronically Managing Quality Assurance Records	
2.1	Work Processes	
2.1.1	Work	
2.1.3	Item Identification and Control	
2.1.4	Special Processes	
2.2	Design Control	
2.3	Acquisition/Procurement	
2.3.1	Acquisition/Procurement Planning Requirements	
2.3.7	Control of Supplier Generated Documents	
2.3.8	Control of Changes in Items or Services	
2.3.9.2	Receiving Inspection	
2.4	Inspection and Testing	
2.4.4.1	Test Procedures	
2.4.5	Monitoring, Measuring, Testing, and Data Collection	
	Equipment	
3.1 Management Assessment		
4.3	Handling, Storing, and Shipping Samples	
5	Scientific Investigation Requirements	
6	Software Requirements	
6.1	Applicability	
6.2		
Classification of Software		
Appendix A	Glossary	
Appendix B	References	
Appendix E TRU Waste Characterization and Certification		
''	Organizational and Individual Responsibilities	

### **TABLE OF CONTENTS**

POLI	CY STATEMENT	3
CHAI	NGE HISTORY	4
INTR	ODUCTION	20
SEC1	FION 1 – MANAGEMENT REQUIREMENTS	24
1.1	ORGANIZATION AND QUALITY ASSURANCE PROGRAM (DOE O 414.1D, Attachment 2, Criterion 1a)	
1.2	PERSONNEL QUALIFICATION AND TRAINING (NQA-1-1989, Basic Requirement 2)	32
1.3	QUALITY IMPROVEMENT	33
1.4	DOCUMENT CONTROL (NQA-1-1989, Basic Requirement 6, Supplement 6S-1, Section 1 2(c))	
1.5	RECORDS (NQA-1-1989, Basic Requirement 17; Supplement 17S-1, Section 2.1, and Sect 2.3; 36 CFR 1236; DOE O 243.1C)	
SEC1	FION 2 – PERFORMANCE REQUIREMENTS	53
2.1.	WORK PROCESSES (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)	53
2.2	DESIGN CONTROL (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)	57
2.3	ACQUISITION/PROCUREMENT (Control of Purchased Items and Services) (NQA-1-1989/I O 414-1D/10 CFR 830.122)	
2.4	INSPECTION AND TESTING (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)	73
SEC1	FION 3 – ASSESSMENT REQUIREMENTS	82
3.1	MANAGEMENT ASSESSMENT (DOE O 414.1D, Criterion 9 and NQA-3-1989, Paragraph 2	.4) 82
3.2	INDEPENDENT ASSESSMENT	82
SEC1	FION 4 – SAMPLE CONTROL REQUIREMENTS	92
4.1	SAMPLE CONTROL	92
4.2	SAMPLE IDENTIFICATION	92
4.3	HANDLING, STORING, AND SHIPPING SAMPLES	93
4.4	DISPOSITION OF NONCONFORMING SAMPLES	94
SEC1	FION 5 – SCIENTIFIC INVESTIGATION REQUIREMENTS	95
5.1	PLANNING SCIENTIFIC INVESTIGATIONS (NQA-3-1989, Paragraph 2.1)	95
5.2	PERFORMING SCIENTIFIC INVESTIGATIONS (NQA-3-1989, Paragraphs 3.1, 4, and 11S)	
5.3	DATA DOCUMENTATION, CONTROL, AND VALIDATION	
5.4	QUALIFICATION OF EXISTING DATA (NQA-3-1989, Supplement 3SW-1, Section 9)	98
SEC1	FION 6 – SOFTWARE REQUIREMENTS	101
6.1	APPLICABILITY (DOE O 414.1D, Attachment 4; NQA-2-1989, Part 2.7, Paragraph 2.1)	101
6.2	BASIC REQUIREMENTS FOR INVENTORY, GRADING, AND CLASSIFICATION OF SOFTWARE (DOE O 414.1D, Attachment 4, Paragraph 2A.(2))	102
6.3	SOFTWARE QUALITY ASSURANCE	
64	SOFTWARE PROCUREMENT (DOF O 414 1D. Attachment 4. Paragraph 2a)	105

6.5	SOFTWARE USED IN DESIGN ANALYSIS (DOE O 414.1D, Attachment 4, Paragraph 2.a(4)	` ' '
6.6	SOFTWARE DEVELOPED UNDER OTHER QA PROGRAMS	. 106
6.7	SOFTWARE DEVELOPMENT AND LIFE CYCLE (DOE O 414.1D, Attachment 4, Paragraphs 2.a(4)(c, e, and f))	
6.8	SOFTWARE VERIFICATION AND VALIDATION (DOE O 414.1D, Attachment 4, Paragraph 2.a(4)(h))	.112
6.9	SOFTWARE CONFIGURATION MANAGEMENT (DOE O 414.1D, Attachment 4, Paragraph 2.a(4)(c))	. 115
6.10	DOCUMENTATION (DOE O 414.1D, Attachment 4, Paragraph 2a.(2))	.117
6.11	PROBLEM REPORTING AND CORRECTIVE ACTION (DOE O 414.1D, Attachment 4, Paragraph 2.a(4)(i))	. 119
6.12	ACCESS CONTROL (NQA-2-1989, Part 2.7, Section 9)	. 120
6.13	SUPPORT SOFTWARE (DOE O 414.1D, Attachment 4, Paragraph 1.b)	. 120
APPEN	IDIX A – GLOSSARY	. 122
APPEN	IDIX B – REFERENCES	. 134
APPEN	IDIX C – CBFO ORGANIZATION, RESPONSIBILITIES, AND INTERFACES	. 136
APPEN	IDIX D – RESPONSIBILITIES OF THE DIRECTOR OF THE CBFO QUALITY ASSURANCE DIVISION	. 138
APPEN	IDIX E – TRU WASTE CHARACTERIZATION AND CERTIFICATION ORGANIZATIONAL	140

### LIST OF ACRONYMS AND ABBREVIATIONS

ASME American Society of Mechanical Engineers

ASNT American Society of Nondestructive Testing

ASTM American Society for Testing and Materials

CAP corrective action plan

CAQ condition adverse to quality

CAR corrective action report

CAS contractor assurance system

CBFO Carlsbad Field Office

CFR Code of Federal Regulations

CGD Commercial Grade Dedication

CGI Commercial Grade Item

CO Certifying Official

CRA Compliance Recertification Application

CRD Contractor Requirements Document

DOE U.S. Department of Energy

DQO data quality objective

EM Office of Environmental Management

EPA U.S. Environmental Protection Agency

HWFP Hazardous Waste Facility Permit

ISMS Integrated Safety Management System

M&O management and operating contractor

M&TE measuring and test equipment

NARA National Archives and Records Administration

NDE nondestructive examination

NFPA National Fire Protection Association

NMED New Mexico Environment Department

NQA Nuclear Quality Assurance

NRC Nuclear Regulatory Commission

O Order

P Policy

### LIST OF ACRONYMS AND ABBREVIATIONS (cont.)

QA quality assurance

QAD Quality Assurance Division

QAPD Quality Assurance Program Document

**Quality Assurance Program** 

QAPjP Quality Assurance Project Plan

QC quality control

QAP

S/CI suspect/counterfeit items

SCAQ significant condition adverse to quality

SOP standard operating procedure

SQA software quality assurance

SSC structure, system, or component

SSQA safety software quality assurance

TRU transuranic

TRUPACT Transuranic Package Transporter

UL Underwriters Laboratories

V&V verification and validation

WAP Waste Analysis Plan

WIPP Waste Isolation Pilot Plant

#### INTRODUCTION

The Carlsbad Field Office (CBFO) Quality Assurance Program Document (QAPD) describes and establishes the CBFO Quality Assurance (QA) program. The provisions of this QAPD apply to all programs and projects managed by the CBFO, which require a QA program, including activities related to Compliance Re-Certification Application (CRA), waste characterization and certification, repository performance assessment, waste isolation, waste transportation, nuclear and industrial safety, environmental protection, contractor assurance, and management and operation of the Waste Isolation Pilot Plant (WIPP). This document identifies the sources of all applicable QA program requirements. The subject requirements are based on criteria contained, or incorporated by reference, in source documents listed in Table I-1. These documents have been placed into one of three categories:

- A. Regulatory documents, including those incorporated by reference, that define the requirements necessary for the WIPP to be granted a certificate of compliance by the Federal Government, and permit(s) by state governmental agencies to dispose of transuranic (TRU) and mixed TRU wastes in the WIPP repository, or that define requirements applicable to the management of the WIPP as a DOE nonreactor nuclear facility.
- B. Commitment documents that are imposed by DOE management, such as EM-QA-001, Office of Environmental Management (EM) Quality Assurance Program (QAP).
- C. Guidance documents that provide additional information that is useful in developing and implementing the CBFO QA program.

The purpose of the QAPD is to describe the applicability and requirements of the CBFO QA program as applied within the CBFO management infrastructure. In this context, the management infrastructure includes all CBFO program participants that substantially contribute to the WIPP project (e.g., Sandia National Laboratories as Science Advisor; the WIPP management and operating [M&O] contractor, Los Alamos National Laboratory – Carlsbad Operations, the CBFO Technical Assistance Contractor, and various other contractors performing work under the direction of the CBFO). This process provides due consideration to the extent of source requirement applicability, a graded-approach, available guidance, and the current foreseeable activities expected to be performed under the direction of the CBFO.

The requirements in this QAPD are based on the principle that work is planned, documented, performed under controlled conditions, and periodically assessed to establish work item quality and process effectiveness to promote improvement. Management, line personnel, and organizations are responsible for planning and achieving quality and for promoting continuous improvement. Quality assurance organizations and personnel are responsible for the verification of the achievement of quality. This QAPD further delineates the quality contributions expected of all personnel and encourages their active participation in implementing the CBFO QA program. The CBFO's implementation of applicable requirements is identified in the DOE/CBFO-14-

3540, *Quality Assurance Implementation Plan and Requirements Flow Down*. The CBFO performs oversight of all other program participants through graded approach and risk assessment.

**Table I-1 QA Program Source Documents** 

MAJOR REGULATORY REQUIREMENTS DOCUMENTS	TITLE
40 CFR Part 191	Environmental Radiation Protection Standards for Management and Disposal of Spent Nuclear Fuel, High-Level and Transuranic Radioactive Wastes
40 CFR Part 194	Criteria for the Certification and Re-Certification of the Waste Isolation Pilot Plant's Compliance with the 40 CFR Part 191 Disposal Regulations
36 CFR Chapter 12, Subchapter B	Records Management
10 CFR Part 830	Nuclear Safety Management
10 CFR Part 71	Packaging and Transportation of Radioactive Material
10 CFR Part 21	Reporting of Defects and Noncompliance
ASME NQA-1-1989 (incorporated by reference in 40 CFR Part 194)	Quality Assurance Program Requirements for Nuclear Facilities
ASME NQA-2a-1990 addenda, Part 2.7 (incorporated by reference in 40 CFR Part 194)	Quality Assurance Requirements of Computer Software for Nuclear Facility Applications
ASME NQA-3-1989 excluding Section 2.1 (b) and (c) and Section 17.1 (incorporated by reference in 40 CFR Part 194)	Quality Assurance Program Requirements for the Collection of Scientific and Technical Information for Site Characterization of High-Level Nuclear Waste Repositories
NQA-1-2019 (Includes only Subparts 2.17, 3.1-17.1 and 3.1-17.2 for electronic records)	Quality Assurance Requirements for Nuclear Facility Applications
DEAR/FAR	Department of Energy Acquisition Regulations/Federal Acquisition Regulations
NM 48901 39088 – TSDF/WIPP	WIPP Hazardous Waste Facility Permit
NRC Certificate Number 9212	RH-TRU 72-B Certificate of Compliance
NRC Certificate Number 9218	TRUPACT-II Certificate of Compliance
NRC Certificate Number 9279	HalfPACT Certificate of Compliance
NRC Certificate Number 9204	10-160B Certificate of Compliance
NRC Certificate Number 9305	TRUPACT-III Certificate of Compliance
NUREG-1297 (1988) (incorporated by reference in 40 CFR Part 194)	Peer Review for High-Level Nuclear Waste Repositories
COMMITMENT DOCUMENTS	TITLE
DOE P 450.4A	Integrated Safety Management Policy
DOE O 414.1D	Quality Assurance
DOE O 226.1B	Implementation of Department of Energy Oversight Policy
DOE O 243.1C	Records Management Program
*DOE O 460.1D	Hazardous Materials Packaging And Transportation Safety
EM-QA-001	Office of Environmental Management (EM) Quality Assurance Program (QAP)
SNT-TC-1A-1980	American Society of Nondestructive Testing (ASNT)  "Recommended Practice No. SNT-TC-1A, Personnel Qualification and Certification in Nondestructive Testing," August 1980

### Table I-1 QA Program Source Documents (cont.)

DOE-STD-1073-2016	Configuration Management
GUIDANCE DOCUMENTS	TITLE
DOE G 414.1-2B	Quality Assurance Program Guide
DOE G 414.1-1C	Management and Independent Assessments Guide
DOE G 414.1-4	Safety Software Guide for Use with 10 CFR 830 Subpart A, Quality Assurance Requirements, and DOE O 414.1C, Quality Assurance
NUREG/BR-0167 (1993)	Software Quality Assurance Program and Guidelines
NQA-1-2008/2009 Part IV, subpart 4.1	Guide on Quality Assurance Requirements for Computer Software
DOE-HDBK-1230-2019	Commercial Grade Dedication Application Handbook

<sup>\*</sup> CBFO received an exemption from requirements of DOE Order (O) 460.1D, *Hazardous Materials Packaging and Transportation Safety*, (Order) to the Carlsbad Field Office (CBFO) along with the WIPP management and operating (M&O) contractor. Certain responsibilities and requirements in the Order overlap with equivalent responsibilities and requirements for compliance with the Waste Isolation Pilot Plant (WIPP) Land Withdrawal Act (LWA).

This exemption is limited to the following requirements and responsibilities in DOE O 460.1D for the aforementioned package designs:

- Paragraphs 4.a.(2)(c), 5.c.(3), and Attachment 1 (Contractor Requirements Document CRD).
- Paragraph 3.c directly submit requests and applications to the Nuclear Regulatory Commission (NRC) for package certificate amendments, renewals, exemptions (per 10 CFR 71 Subpart B), or special package authorizations.
- Paragraphs 4.a.(4)(b), 5.c.(10), and Attachment 1, CRD, Paragraph 4 directly report §71.95(a) violations to NRC.
- Paragraph 4.a.(4)(c), 5.c.(10), and Attachment 1, CRD, Paragraph 4 approve corrective actions in response to §71.95(a) violations.

### **SECTION 1 – MANAGEMENT REQUIREMENTS**

This section describes the fundamental elements related to the organization and management of the CBFO QA program, as well as the fundamentals to be applied in managing the work of the program.

### 1.1 ORGANIZATION AND QUALITY ASSURANCE PROGRAM (DOE O 414.1D, Attachment 2, Criterion 1a)

This section describes the QA requirements for the organizational structure, functional responsibilities, levels of authority required, and interfaces for those managing, performing, and assessing the work to implement the CBFO QA program. In addition, this section describes the basic elements of the QA program and their applicability.

### 1.1.1 Organization (NQA 1-1989, Part II, Section 1)

Effective implementation of the CBFO QA program is dependent on program participant efforts at all levels. The organizational structures and the responsibility assignments of program participants shall be such that those organizations that have been assigned responsibility for performing the work are responsible for achieving and maintaining quality. Management is responsible for defining quality, developing appropriate plans to attain quality, and supporting the workers in pursuit of quality. Program participant QA organizations are responsible for verifying the achievement of quality in the implementation of the CBFO QA program. The CBFO organizational and individual responsibilities are also addressed in Appendices C and D. Organizational and individual responsibilities for TRU waste characterization and certification, repository performance assessment, waste isolation, waste transportation, nuclear safety, environmental protection, and management and operation of the WIPP are addressed in Appendix E. Several CBFO documents have been written which define its organization, internal and external interfaces, and organizational rolls and responsibilities as follows:

- A. DOE/CBFO-14-3514, CBFO Program Management Plan
- B. DOE/CBFO-09-3441, Safety Management Functions, Responsibilities and Authorities Manual
- C. DOE/CBFO-09-3442, CBFO Integrated Safety Management System Description
  - External/contract organizations develop their own applicable interface documents.
  - External/contract organizations shall maintain a current organization chart.

# 1.1.1.1 Management (DOE O 414.1D, Attachment 2, Criterion 1b and NQA 1-1989, Supplement S1, Section 2.1)

- A. Management has overall responsibility for successfully accomplishing assigned activities in accordance with applicable sections of this QAPD. Management provides the necessary planning, organization, direction, control, resources, and support to achieve defined objectives. Management is responsible for planning, performing, scheduling, providing resources, and improving the work.
- B. Management is responsible for establishing and implementing policies, plans, and procedures that control the quality of work, consistent with the provisions of this QAPD.
- C. Management quality responsibilities include:
  - 1. Ensuring that adequate technical and QA training is provided for personnel performing activities subject to this QAPD
  - 2. Ensuring compliance with all applicable regulations, DOE orders and requirements, and applicable Federal, State, and local laws through the performance of internal/external assessments, audits, and surveillances
  - 3. Ensuring that personnel adhere to procedures for the generation, identification, control, and protection of QA records
  - 4. Exercising the authority and responsibility to stop unsatisfactory work such that cost and schedule do not override environmental, safety, or health considerations
  - 5. Developing, implementing, and maintaining schedules, plans, policies, and procedures that implement this QAPD
  - 6. Identifying, investigating, reporting, and correcting conditions adverse to quality
  - 7. Maintaining overall responsibility for the quality of work
  - 8. Developing, implementing, and maintaining metrics and trending reports for assigned areas of responsibility, processes, and implementing procedures
  - 9. Implement and report regularly scheduled management assessments
- D. Quality achievement is the responsibility of those performing the work. Line organizations are responsible for achieving and ensuring quality in their areas.
- E. Management empowers employees by delegating authority and decision making to the lowest appropriate level in the organization.

### 1.1.1.2 Employees (NQA 1-1989, Supplement S1, Section 2.1)

Each program participant employee is responsible for the quality of his or her work and for promptly reporting all existing, developing, or potential conditions adverse to quality to the responsible management for evaluation and action. Work shall be verified by other persons in the organizational structure not directly responsible for performing the assigned work. Employees are responsible to stop work when dangerous or significant noncompliant conditions are observed.

### 1.1.1.3 QA Management (DOE O 414.1D, Criterion 1 and NQA 1-1989, Part II, Section 1, Paragraphs 1 and 2 and Part II, Section 2)

The CBFO and CBFO program participants' QA management have the authority and overall responsibility to independently assess the organization's effective implementation of the QA program to verify the achievement of quality.

### A. The QA management shall:

- 1. Schedule and conduct QA assessments
- 2. Ensure preparation, review, and issuance of QA plans and procedures that implement the provisions of this QAPD
- 3. Review and approve supplier and subcontractor QA plans. A CBFO program participant's QA plan submitted to CBFO for approval may be considered approved by CBFO 90 calendar days after submittal, unless the QA plan is approved or rejected at an earlier date.
- 4. Track or perform trend analysis of conditions adverse to quality, and report quality problem areas to senior level management
- 5. Provide for the administrative processing of documentation concerning conditions adverse to quality
- 6. Have direct access to responsible management at a level where necessary action can be affected
- 7. Be sufficiently independent from cost and schedule considerations to minimize impact on quality program decisions
- 8. Have the organizational freedom to communicate with management at all levels
- 9. Have no additional assigned responsibilities unrelated to the QA program that would prevent attention to QA matters
- 10. Develop, establish, and interpret QA policy and ensure effective implementation

- 11. Interface with the management of other departments or organizations, participants, and other stakeholders on QA matters
- 12. Assist departments and organizations with quality planning, documentation, quality measurement, and problem identification and resolution
- 13. Provide guidance to other organizations concerning QA-related matters and issues
- 14. Verify the stipulations of this QAPD are addressed within each implementing organization
- B. The QA organization shall have sufficient authority, access to work areas, and organizational freedom to:
  - 1. Identify conditions adverse to quality
  - 2. Recommend solutions
  - 3. Verify implementation and effectiveness of solutions
  - 4. Ensure unsatisfactory conditions are controlled until proper disposition has occurred
- 1.1.1.4 Communication and Interface Responsibilities (NQA-3-1989, Sections 2.5 and 16.1, DOE O 414.1D, Criterion 1a and NQA 1-1989, Supplement S1, Section 3.1)
- A. Communication Responsibilities

Participating organizations at all management levels shall establish communication channels that provide timely dissemination of information pertinent to quality performance, such as:

- 1. The status of development and implementation of the QA program
- 2. The status and resolution of significant conditions adverse to quality
- 3. The lessons learned from significant conditions adverse to quality and other adverse conditions
- 4. Quality management practices and improvement
- 5. Metrics and analysis results (due quarterly to the CBFO Quality Assurance Division [QAD] Director)

6. Management, surveillance, and audit assessment results with associated corrective actions

#### B. Interface Responsibilities

- 1. Where more than one organization is involved in the execution of activities covered by this QAPD, the responsibility and authority of each organization shall be clearly established, defined, and documented. The external interfaces between organizations, the internal interfaces between organizational units, and interface changes shall be documented. Interface responsibilities shall be defined and documented and shall include the requirements for management, performance, and assessment.
- 2. CBFO-sponsored activities, performed by organizations external to the CBFO, include, but are not limited to, CRA, waste characterization and certification, repository performance assessment, waste isolation (disposal), waste transportation, nuclear and industrial safety, environmental protection, and management and operation of the WIPP facility. Responsible CBFO organizations shall ensure the effective implementation of the CBFO QA program.
- 3. The QA program shall be integrated with the Integrated Safety Management System (ISMS) as required by DOE Policy (P) 450.4, *Integrated Safety Management Policy*, dated 4-25-11, and DOE Acquisition Regulation 48 Code of Federal Regulations (CFR) 970.5204-2 (i.e., the Department of Energy Acquisition Regulations [DEAR] ISMS clause).
- 4. DOE G 414.1-2B, Quality Assurance Program Guide, Paragraph 4.1.4, Table 1, describes where the ISMS and QA Program intersect. DOE G 414.1-2B, Paragraph 4.1.4 recommends, where the DOE O 414 QA criteria and ISMS principles and functions overlap closely, utilizing the same implementation process for both. Likewise, a single process (e.g., procedure or plan) that satisfies quality and safety requirements at the facility level or activity level should be written and implemented. The CBFO shall integrate these processes within its organization where applicable. All external organizations following this QAPD shall meet the above referenced requirements and integrate its safety and quality processes in the areas defined in DOE G 414.1-2B, Table 1.
- 5. All CBFO DOE organizations are required to perform effective contract oversight in accordance with DOE O 226.1B, *Implementation of Department of Energy Oversight Policy*. DOE G 414.1-2B describes integration of QA Criteria into DOE O 226.1B and outlines how oversight requirements overlap with QA requirements (see DOE G 414.1-2B, Paragraph 4.1.5, Table 2). The CBFO will integrate these oversight processes within its organization as applicable. All external government organizations following this QAPD shall meet the requirements of DOE O 226.1, as applicable.

 Contractors implementing DOE O 226.1B shall develop a contractor assurance system (CAS). The CBFO shall monitor and evaluate each CAS system to ensure work performed under its contracts meets the applicable requirements of the CAS.

### 1.1.1.5 Delegation of Work (NQA 1-1989, Supplement S1, Sections 3.1 and 3.2)

Individuals or organizations responsible for establishing, planning, accomplishing, and assessing the work may delegate work to other appropriate and similarly qualified individuals or organizations. However, the individuals or organizations making the delegation shall retain overall responsibility for the delegated work.

### 1.1.1.6 Resolution of Disputes

Differences of opinion involving the definition and implementation of QA program requirements will be brought to the attention of the QAD Director and line management within the applicable CBFO participant organization. If not resolved, the issues will be elevated to the CBFO Manager, as needed to reach resolution.

### 1.1.2 Implementation of the CBFO QA Program

### 1.1.2.1 Quality Assurance Program Documents

Program participants shall develop and follow plans and procedures that effectively implement the requirements of this QAPD, including the mandatory requirements listed in Table I-1, *QA Program Source Documents*. Program participants shall submit their QAPDs to the CBFO Manager for review and approval.

### 1.1.2.2 Applicability of QAPD Requirements

The terminology "items or activities important to CRA, waste characterization and certification, repository performance assessment, waste isolation, waste transportation, nuclear and industrial safety, environmental protection, and management and operation of the WIPP facility" are all important WIPP elements to which quality standards and requirements apply. The QAPD requirements are applicable to all WIPP functions with a focus on the work performed on the following items and activities:

- A. WIPP site activities or operations that process or store radioactive waste, perform waste management activities involving radioactive materials, or design, manufacture, or assemble items for use with radioactive materials in such a form and quantity that a nuclear hazard exists
- B. Waste characterization and certification activities
- C. Environmental monitoring, monitoring the performance of the disposal system, and sampling and analysis activities

- D. All additional geologic, geophysical, geochemical, hydrologic, and meteorologic information
- E. Computations, codes, models, and methods used to demonstrate compliance with disposal regulations
- F. Expert judgment elicitation to support applications for recertification or determination of compliance
- G. Design of the disposal system and actions taken to ensure compliance with design specifications
- H. The collection of data and information used to support compliance certification application and/or any modifications to the CRA
- I. Other systems, structures, components, and activities important to the isolation of waste in the disposal system
- J. Those items and activities related to Nuclear Regulatory Commission (NRC) licensed packaging (e.g., Transuranic Package Transporter Model II [TRUPACT-II] and Model III [TRUPACT-III], HalfPACT, RH-72B, CNS 10-160B, SC-30G2, SC-30G3, SC-55G1, and SC-55G2), design, purchase, fabrication, handling, shipping, storage, cleaning, assembly, inspection, testing, operation, maintenance, repair, and modification or components of packaging that are important to safety
- K. Activities associated with the packaging and transportation of offsite shipments and onsite transfers of hazardous material, including radioactive materials, in accordance with DOE O 460.1D requirements.

### 1.1.2.3 Grading Items and Activities and Applying Management Controls (DOE O 414.1D, Paragraph 4.a.(1))

- A. The graded approach is the process by which the level of analysis, documentation, verification, and other controls necessary to comply with QA program requirements are developed commensurate with the following factors:
  - 1. The importance of an item or activity with respect to safety, waste isolation, security, and regulatory compliance
  - 2. The importance of the data to be generated
  - The need to demonstrate compliance with specific regulatory design and QA requirements
  - 4. The impact on the results of performance assessments and engineering analyses

- 5. The magnitude of a hazard or the consequences of failure
- 6. The life-cycle stage of a facility or item
- 7. The programmatic mission of a facility
- 8. The particular characteristics of a facility, item, or activity (e.g., complexity, uniqueness, history, or the necessity for special controls or processes)
- 9. The relative importance of radiological and non-radiological hazards
- B. The extent of management and QA controls applied to an item or activity will vary as a function of the degree of confidence needed to achieve the desired quality of the item or activity. The grading process provides the flexibility to design and implement controls that best suit the facility or activity. The use of the graded approach shall determine the appropriate level of controls necessary to manage the items, systems, and activities necessary to ship TRU waste to WIPP.
- C. Grading methods for each organization shall provide for:
  - 1. The assignment of management and QA control levels
  - 2. The definitive criteria used in selecting those levels
  - 3. Detailed descriptions of the management and QA control provisions corresponding to those levels, based on the above requirements
- D. The CBFO utilizes MP 1.2, Grading Activities and Determination of Quality Levels, as its implementing process. Program participant procedures that establish and implement a graded approach for items and activities under the cognizance of the CBFO shall be submitted to the CBFO QAD Director for approval for use in CBFO programs.

### 1.1.2.4 Planning Work (DOE O 414.1D, Criterion 1.b)

Planning shall be performed and documented to ensure work is accomplished under suitably controlled conditions. As appropriate, planning elements shall include:

- A. Definition of work scope, objectives, intended use of the data, and a listing of the primary tasks involved
- B. Identification of scientific approaches or technical methods used to collect, analyze, or study results of applicable work
- C. Identification of field and laboratory testing standards and quality criteria

- D. Identification of applicable requirements documents (appropriate nationally recognized standards shall be used whenever possible)
- E. Identification of field and laboratory testing equipment or other equipment
- F. Identification of, or provisions for the identification of, required records and the recording of objective evidence of the results of the work performed
- G. Identification of prerequisites, special controls, specific environmental conditions, processes, or skills
- H. Identification of computer software
- I. Proposed schedules

# 1.2 PERSONNEL QUALIFICATION AND TRAINING (NQA-1-1989, Basic Requirement 2)

Personnel shall be trained and qualified to ensure they are capable of performing their assigned tasks and to ensure job proficiency is maintained.

### 1.2.1 Qualification Requirements (NQA-1-1989, Supplement 2S-4, Section 5)

Qualification requirements for CBFO and participant positions or job functions shall be established for activities important to CRA, waste characterization and certification, repository performance assessment, waste isolation, waste transportation, nuclear and industrial safety, environmental protection, and management and operation of the WIPP facility. At a minimum, these positions include managers, designers, scientists, independent assessment personnel, operators, maintenance personnel, technicians, and inspectors.

The responsible organization shall:

- A. Analyze each position to determine the tasks and responsibilities of the position subject to the QAPD. The analysis shall identify minimum education, experience, and training prerequisites for each position involved in the planning, performance, or verification of activities subject to the QAPD, commensurate with the scope, complexity, and nature of the work.
- B. Ensure personnel selected to perform, verify, or peer review activities subject to the QAPD have education, experience, and training commensurate with the minimum requirements specified. The qualification of an individual shall be based upon evaluation of education, experience, and technical qualifications, when compared to the established requirements for the position.
- C. Document the analysis and evaluation.

# 1.2.2 Training Requirements (NQA-1-1989, Supplement 2S-4, Section 2, DOE O 414.1D, DOE O 426.1, DOE-STD-1150-2013, DOE-STD-1172-2011)

The CBFO and participant personnel performing activities important to CRA, waste characterization and certification, repository performance assessment, waste isolation, waste transportation, nuclear and industrial safety, environmental protection, and management and operation of the WIPP facility shall receive related training in accordance with the following requirements. Training shall emphasize the correct performance of work, describe why the applicable quality and nuclear and industrial safety requirements exist, describe the fundamentals of the work, the analyzed hazards of the work, and the context. Training shall be subject to ongoing review to determine instruction and training program effectiveness and shall be upgraded whenever needed improvements or enhancements are identified. Management shall:

- A. Ensure personnel receive indoctrination and training, including on-the-job and hands-on training as needed, to achieve initial proficiency; maintain proficiency; and adapt to changes in technology, methods, job responsibilities authority, and QA implementing procedures, prior to performing any tasks subject to the QAPD.
- B. Ensure personnel receive indoctrination in the following:
  - 1. General criteria, including applicable QA plans, codes, regulations, and standards
  - 2. Specific criteria, including applicable Quality Assurance Project Plans (QAPjPs) and implementing procedures
  - 3. Federal personnel directly responsible for the oversight of quality requirements governing defense nuclear facilities must be qualified in accordance with the DOE Federal Technical Capability Program.
  - 4. Federal personnel directly responsible for oversight of safety software quality assurance (SSQA) activities of defense nuclear facilities must be qualified in SSQA in accordance with the DOE Federal Technical Capability Program.
- C. Ensure records generated during qualification, general indoctrination and training, or specific skill training activities are collected and maintained as QA records.

#### 1.3 QUALITY IMPROVEMENT

Quality improvement is a management process carried out to improve items, services, products, or processes. All aspects of work that affect quality and the management system are subject to continuous improvement through assessment and feedback processes.

Line management shall establish processes for identifying and capturing deficiencies in

work and implementing effective corrective actions to resolve those deficiencies. The corrective actions shall be complete as soon as practical, shall identify responsibility, and shall be founded on firm technical bases derived from a complete analysis of the causes of the deficiencies in order to prevent recurrence. As a result of the analysis, the lessons learned from the deficiencies shall be disseminated to the appropriate organizations across the DOE complex to facilitate Department-wide continuous improvement.

Quality-related program deficiencies are addressed in section 1.3.3.3, Remediation of Conditions Adverse to Quality.

### 1.3.1 Quality-Affecting Problems

Quality-affecting problems and items, services, and processes that do not meet established requirements shall be identified, documented, reported, controlled, and corrected. Quality-affecting problems may be identified by the organization or by an external source.

#### 1.3.1.1 Problem Identification

All personnel shall be responsible for identifying quality-affecting problems and shall be encouraged by management to suggest improvements. The CBFO and participant organizations foster a "no-fault" attitude for quality problems and prioritize and focus resources on preventive actions and on those quality problems that have the greatest potential for:

- A. Posing adverse risks to the environment and human health
- B. Adversely impacting the quality, safety, and reliability of waste operations
- C. Affecting the ability to meet quality requirements

### 1.3.1.2 Problem Types

Quality-affecting problems may involve:

- A. Noncompliance with a QA program requirement. A noncompliance is classified as a condition adverse to quality (CAQ) or significant condition adverse to quality (SCAQ).
- B. Nonconforming items, including suspect/counterfeit items or data, that do not conform to specified requirements.

#### 1.3.2 Nonconformances

Items or data that do not conform to established requirements shall be controlled to prevent inadvertent installation or use.

### 1.3.2.1 Documenting and Evaluating Nonconforming Items

Documentation and evaluation of nonconforming items must include:

- A. Clear identification and description of the characteristics that do not conform to specified criteria
- B. Review of nonconformance documentation and proposed recommended disposition of the nonconforming item or data. The review shall include a determination of the need for corrective action in accordance with the requirements of section 1.3.3, *Corrective Action*. In addition, organizations affected by the nonconformance shall be notified.
- C. Evaluations and approvals of recommended dispositions
- D. Verification that personnel performing evaluation or recommending disposition have demonstrated competence in the specific area they are evaluating or dispositioning, and have an adequate understanding of the requirements
- E. Implementing procedures that specify the responsibility and authority for reviewing, evaluating, approving the disposition, and closure of the nonconformance

#### 1.3.2.2 Identifying Nonconforming Items or Data

- A. Nonconforming items shall be physically identified by marking, tagging, segregation, or other methods that do not adversely affect the end use. The identification shall be legible and easily recognizable, and shall be traceable to the reporting documentation.
- B. If physical identification of each nonconforming item is not practical, the container, package, or segregated storage area, as appropriate, shall be physically identified as specified in 1.3.2.2.A.
- C. Nonconforming data should be labeled or stored in such a way as to prevent its inadvertent use.

# 1.3.2.3 Reporting Nonconformances (40 CFR § 194.23 (c)(4); DOE O 232.2, Admin Chg 1)

The CBFO has contracted management of equipment and facilities to participant organizations. The CBFO and other participant organizations affected by a

nonconformance shall be notified. The CBFO shall be notified in writing within 7 calendar days of identification of any non-administrative nonconformance related to applicable requirements specified in the WIPP Hazardous Waste Facility Permit (HWFP) Waste Analysis Plan (WAP), which is first identified at the site project manager's signature release level (i.e., a failure to meet a data quality objective [DQO]). The nonconformance report shall be submitted to the CBFO within 30 calendar days of identification of the deficiency.

Nonconformances related to defects or failure to comply with requirements applicable to NRC-licensed packaging (e.g., TRUPACT-II, TRUPACT-III, HalfPACT, RH 72-B) shall be reported to the CBFO Office of National TRU Program Waste Certification and Disposal. NRC and DOE HQ Packaging Certification Program are notified per the requirement in Paragraph 4.a.(4)(b) of DOE O 460.1D. The WIPP M&O contractor will evaluate issues and nonconformances for reporting to the NRC in accordance with 10 CFR Part 21, Reporting of Defects and Noncompliance, or 10 CFR Part 71, Packaging and Transportation of Radioactive Material, and provide the results of this evaluation to the CBFO.

Non-administrative nonconformances related to requirements in the applicable CRA, particularly for data, performance assessment models and their parameterization should be tracked, as required by 40 CFR § 194.23 (c)(4).

The Office of Environment, Safety, Health and QA shall be notified of any noncompliances that are determined to be reportable in accordance with DOE O 232.2, Admin Chg 1, Occurrence Reporting and Processing of Operations Information. The Order promotes organizational learning consistent with the DOE's ISMS goal of enhancing mission safety, and sharing effective practices to support continuous improvement and adaptation to change.

#### 1.3.2.4 Segregating Nonconforming Items

- A. Further processing, delivery, installation, or use of nonconforming items shall be controlled pending the evaluation and approval of the disposition.
- B. Nonconforming items shall be segregated, when practical, by placing them in a clearly identified and designated hold area until properly dispositioned.
- C. If segregation is impractical or impossible due to physical condition, other precautions shall be employed to preclude inadvertent use.

D. Reliance solely on other precautions (i.e., administrative controls) to differentiate contact-handled waste containers that are acceptable for shipment to WIPP from those containers that do not meet the WIPP acceptance criteria is not allowed. To address as low as reasonably achievable radiation exposure goals, dual independent administrative controls may be used to differentiate remote-handled waste containers that are acceptable for shipment to WIPP from those containers that do not meet the WIPP acceptance criteria.

### 1.3.2.5 Disposition of Nonconforming Items or Data

The disposition of nonconforming characteristics shall be accomplished as follows:

The nonconformance characteristics shall be reviewed, and recommended dispositions of nonconforming items or data shall be proposed and approved in accordance with documented procedures. Personnel performing evaluations to determine a disposition shall have demonstrated competence in the specific area they are evaluating, have adequate understanding of the requirements, and have access to pertinent background information.

- A. The dispositions "use-as-is", "reject", "repair", or "rework" for nonconforming items or "reject" or "rework" for data shall be identified and documented.
- B. The technical justification for the acceptability of a nonconforming item that has been dispositioned "use-as-is" or "repair" shall be documented.
- C. Items that do not meet original design requirements that are dispositioned "use-asis" or "repair" shall be subject to design control measures commensurate with those applied to the original design, and
  - 1. If changes to the specifying document are required to reflect the as-built condition, then the disposition shall require action to change the specifying document to reflect the accepted nonconformance.
  - 2. Any document or QA record change required by the disposition of the nonconformance shall be identified in the nonconformance documentation and, when a document or record is changed, the justification for the change shall reference the nonconformance documentation.
- D. The disposition of an item to be reworked or repaired shall contain a requirement to re-examine (inspect, test, or examine by nondestructive examination) the item to verify acceptability. Repaired or reworked items shall be re-examined using the original process and acceptance criteria unless the nonconforming item disposition has established alternate acceptance criteria.

E. Nonconforming laboratory data must be re-evaluated for accuracy and other identified DQOs. Erroneous data should be evaluated for recollection or replaced with new results. Erroneous calculations should be corrected and dispositioned as "reworked."

### 1.3.2.6 Quality Trending of Nonconformances

Nonconformance documentation shall be periodically analyzed by the QA organization to identify quality trends in accordance with section 1.3.3, *Corrective Action*.

## 1.3.3 Corrective Action (DOE O 460.1D, Paragraphs 4.a.(4)(c), 5.c.(10), Attachment 1, CRD, Paragraph (4))

### 1.3.3.1 Identifying Conditions Adverse to Quality

A CAQ occurs when a QA requirement has not been met (see Appendix A for a detailed definition).

Corrective action documentation related to 10 CFR 71.95 (a) violations shall be approved by the CBFO Manager or designee. The approved documentation shall be transmitted to the DOE Certifying Official (CO).

### 1.3.3.2 Classification of Conditions Adverse to Quality

Classification of CAQs is based on the effect a CAQ has on compliance to regulatory requirements for safety, operability, TRU waste characterization, TRU waste site certification, TRU waste containment, TRU waste disposal, management and operation of WIPP, and the effective implementation of the QAPD. Corrective action plans (CAPs), as described in section 1.3.3.5, shall be developed for any identified CAQs that are determined to be noncompliant with an HWFP condition or requirement.

### 1.3.3.3 Remediation of Conditions Adverse to Quality

- A. CAQs shall be documented and reported to the appropriate levels of responsible management for evaluation and resolution, and to the QA organization for tracking.
- B. Responsible management shall determine the extent and impact of the adverse condition and, at a minimum, complete remedial action as soon as practical.

# 1.3.3.4 Significant Conditions Adverse to Quality (DOE O 460.1D, Paragraph 5.c.[10])

A. Implementing documents shall include criteria for determining if a CAQ is significant, based on the criteria in the definition of CAQ included in Appendix A.

- B. SCAQs shall be investigated, documented, and reported to senior management (including extent of condition, cause, and impact on completed work) by the management responsible for the condition, and shall be reported to the QA organization for tracking.
- C. Responsible management shall determine when an SCAQ related to the WIPP HWFP WAP (i.e., significant deficiency against the WAP, or a deficiency against a waste characterization process currently certified by the CBFO at a TRU waste site) requires accelerated corrective action, and shall establish the required time interval for corrective action completion.
- D. Any CAQ that meets the definition of DOE O 460.1D, Paragraph 5.c.(10) shall be processed as an SCAQ with a 30-day reporting to the DOE CO.

#### 1.3.3.5 Corrective Action Plans

CAPs are required for CAQs when more than remedial action is required for resolution. SCAQ CAPs shall address all of the following:

- A. Remedial Actions: actions necessary to resolve the initial problem
- B. Investigative Actions: assessment of the extent and impact of the SCAQ
- C. Cause Analysis: identification of the apparent, contributing and/or root cause, as appropriate, for the SCAQ
- D. Actions to Preclude Recurrence: actions necessary to prevent recurrence of the SCAQ
- E. Schedule: milestones for completion of the CAP, including expected completion dates and identification of responsible individuals

#### 1.3.3.6 Work Suspension

If a work suspension condition has been identified, responsible management shall take appropriate action to lift and close the work suspension, based on the resolution of the related SCAQ. The QA organization shall verify and document the completion of applicable corrective actions prior to any management action releasing the work suspension.

#### 1.3.3.7 Corrective Action Follow-up

A system shall be established to verify the effective implementation of scheduled corrective actions and to complete corrective actions in a timely manner. The QA organization shall evaluate the adequacy of corrective actions planned for resolving quality-related deficiencies resulting from assessments, assign responsibility for follow-

up verification, and perform and document verification results. If results of verification are unsatisfactory, the CAP shall be revised appropriately, and corrective actions and verification performed.

#### 1.3.3.8 Recurring Conditions Adverse to Quality

For recurring CAQs and SCAQs, management shall:

- A. Determine the events leading up to the conditions
- B. Develop an understanding of the technical and work activities associated with the conditions
- C. Identify any generic implications and impacts on completed work
- D. Determine whether similar quality problems, or precursors to the problems, have been identified
- E. Determine the effectiveness of corrective actions that have been taken
- F. Consider suspending work associated with the applicable activity, as appropriate
- G. Suggest actions that can be taken by the responsible organization to preclude recurrence, as appropriate

#### 1.3.3.9 Quality Trending (NQA-3-1989, Section 16.1)

The need for quality improvement is accomplished through quality analysis and trending. To provide reliable trending information, the following activities shall be performed:

- A. Quality performance data shall be identified, collected, and routinely analyzed to identify opportunities to improve items, services, activities, and processes. This analysis shall consider information from external sources and not be limited to one type of work or to one organization.
- B. The analyses shall be performed semi-annually to provide for prompt identification of trends adverse to quality. Reports of CAQs, including those identified during quality assurance audits as corrected during the audit/surveillance, shall be evaluated to identify trends adverse to quality and causes, with results reported to the organization responsible for corrective actions.
- C. Program participants will report trending information to responsible management and to the applicable organization.

# 1.4 DOCUMENT CONTROL (NQA-1-1989, Basic Requirement 6, Supplement 6S-1, Section 1 and 2(c))

- A. Documents shall be prepared, reviewed, approved, issued, used, and revised to prescribe processes, specify requirements, and/or establish design.
- B. Based on the priorities listed in section 1.1.2.2, Applicability of QAPD Requirements, documents that specify requirements, prescribe processes, or establish design important to CRA, waste characterization and certification, repository performance assessment, waste isolation, waste transportation, nuclear and industrial safety, environmental protection, and management and operation of the WIPP facility, such as instructions, procedures, drawings, test plans, management plans, technical reports, performance reports, and test reports, shall be controlled according to the requirements listed below to ensure that the correct documents are being used.

# 1.4.1 Document Preparation, Review, Approval, and Issuance (NQA-1-1989, Supplement 6S-1, Section 1, Section 2(a) and (c), Section 2.2(c))

- A. Documents shall be reviewed for adequacy, correctness, and completeness prior to approval and issuance.
- B. Program participants shall identify the individuals or organizations responsible for the preparation, review, approval, and issuance of controlled documents.
- C. Documents shall be controlled during the review and approval phase in accordance with approved procedures.
- D. The requesting organization shall identify the applicable criteria for the review. These criteria shall consider technical adequacy, accuracy, completeness, and compliance with established requirements.
- E. Pertinent background information or data shall be made available by the organization requesting the review if the information is not readily available to the reviewer.
- F. The review will be performed by individuals other than the originator.
- G. Reviewers will be technically competent in the subject area being reviewed.
- H. The organization or technical discipline affected by the document shall review the document according to the established review criteria.
- I. The appropriate quality assurance organization shall review documents that translate the CBFO QAPD or other CBFO requirements.

- J. Review comment documentation shall be resolved in accordance with approved procedures. Evidence of review comment resolution shall be maintained as records.
- K. Documents shall be approved for release by authorities designated in accordance with approved procedures, unless directed by procedure. These approvals shall include the use of authorized digital signatures.
- L. Documents shall be issued by designated individuals or organizations in accordance with approved procedures.

## 1.4.2 Document Distribution and Use (NQA-1-1989, Supplement 6S-1, Sections 1&2; DOE O 243.1C)

The distribution and use of controlled documents and forms that document or prescribe work, including changes and editorial corrections to documents, shall be controlled to meet the following requirements:

- A. Documents shall be distributed to affected personnel and used at the work location.
- B. Effective dates shall be established and identified on the approved documents.
- C. The disposition of obsolete or superseded documents and forms shall be controlled to avoid their inadvertent use.
- D. Controls shall be established and maintained to identify the current status or revision of controlled documents and forms.
- E. Controls shall provide for identification of documents to be controlled and their specified distribution.
- F. Electronic document controls shall meet the requirements of DOE O 243.1C, *Records Management Program*.

## 1.4.3 Document Changes (NQA-1-1989, Supplement 6S-1, Section 3.1 and Section 3.2)

- A. Changes to documents, other than those defined below as editorial changes, shall be reviewed and approved by the same organizations that performed the original review and approval, unless other organizations are specifically designated in accordance with approved procedures.
- B. Document changes shall be:
  - 1. Reviewed by the organizations or technical disciplines affected

- 2. Clearly indicated in the changed document
- C. Editorial or minor changes may be made without the same level of review and approval as the original or otherwise changed document.
- D. Changes to controlled documents, including comments and comment resolution of comments are to be maintained as records.
- E. The following items are considered editorial or minor changes:
  - 1. Correcting grammar or spelling (the meaning has not changed)
  - 2. Renumbering of sections or attachments that does not affect process sequential steps
  - 3. Updating organizational titles
  - 4. Changes to non-quality affecting schedules
  - 5. Revising or reformatting forms, providing the original intent of the form has not been altered
  - 6. Attachments marked "Example" or "Sample," or items that are clearly intended to be representative only
  - 7. Inconsequential editorial changes that do not affect the purpose of the document
- F. A change in an organizational title accompanied by a change in responsibilities is not considered an editorial change.
- G. The organization responsible for preparing the document shall identify and approve editorial changes.

## 1.5 RECORDS (NQA-1-1989, Basic Requirement 17; Supplement 17S-1, Section 2.1, and Section 2.3; 36 CFR 1236; DOE O 243.1C)

A records management system shall be established by the responsible organization at the earliest practical time, consistent with the schedule for accomplishing work activities. The records management system shall be established, defined, implemented, and enforced in accordance with written procedures, instructions, or other documentation Records shall also be managed in accordance with the requirements identified in 36 CFR 1236 and DOE O 243.1C.

Records shall be specified, prepared, reviewed, approved, distributed, handled, controlled, and maintained to accurately reflect completed work and facility conditions and to comply with statutory or contractual requirements. A "quality assurance record"

is a completed and authenticated record (regardless of medium) that provides evidence of the quality of items or activities.

All records shall be electronic (born digital) to the fullest extent possible to meet Federal requirements and CBFO Records Management and QA policies, plans, and procedures.

### 1.5.1 Electronically Managing Quality Assurance Records

- A. This section of the CBFO QAPD addresses the requirement that federal records are created, retained, and managed in electronic formats, as outlined in Office of Management and Budget Memorandum, M-19-21, which states that all records are to be submitted in electronic formats starting on 1 January 2023.
- B. Implementing electronic records requirements will not change the fundamental records requirements described in this program document.
- C. Records Management shall develop plans and procedures that address:
  - 1. Record Recovery
  - 2. Access Control and Retrieval
  - 3. Digital and Physical Security
  - 4. Electronic Data Integrity
  - 5. Disposal of Records
  - 6. Acquisition, Development, and Maintenance of Electronic Records Systems
- D. Records Management shall develop a plan for developing and obtaining approval of these procedures. This plan will also include a schedule for converting existing hard copy records to electronic records, prioritizing the most recent records. This plan shall be submitted to the CBFO QAD Director for concurrence.
- E. NQA-1-2019, Subpart 2.17, Quality Assurance Requirements for Electronic Quality Assurance Records Systems, NQA-1-2019, Subpart 3.1-17.1, Implementing Guidance for Part I, Requirement 17: Quality Assurance Records, and NQA-1-2019, Subpart 3.1-17.2, Implementing Guidance for Part I, Requirement 17: Quality Assurance Records, Electronic Records, are suggested references for developing these plans and procedures.

## 1.5.2 Generating Records (NQA-1-1989, Supplement 17S-1, Section 2.2, Section 2.3, Section 2.5, Section 3.1, Basic Requirement 17, 17.2)

QA records are a subset of all the records that may be produced for the WIPP Project. The records generated for the priorities listed in paragraph 1.1.2.2 are classified as QA records. The following outline the requirements that are applicable to these records.

A. Prior to conducting a work activity, the responsible organization shall:

- 1. Identify those documents that shall become QA records
- Identify the organization responsible for submitting the QA records to the records system
- 3. QA records shall be legible, accurate, and completed appropriate to the work accomplished
- QA records shall be maintained and stored in an electronic format per the requirements identified in the Electronically Managing Quality Assurance Records section
- B. Individuals handling documents intended to become QA records shall provide reasonable protection for the records from damage or loss until the records are stored in the records management system (this includes documents generated during field operations).
- C. Documents shall be considered valid QA records when stamped, initialed, or signed and dated by authorized personnel, or otherwise authenticated by digital signature. If the nature of the record (such as magnetic or optical media) precludes stamping or signing, then other means of authentication by authorized personnel are required. This authentication represents a certification as to the content of the record by those individuals with knowledge of the related facts, whether by direct personal knowledge or through the direct reports of others. The authentication should not be confused with any subsequent reviews of the content (i.e., a peer review).
- D. Once authenticated, QA records shall be submitted to the records management system as prescribed by approved procedures.
- E. Upon completion of a project or other discrete task or activity, responsible management shall verify that the contents of the applicable QA records package are stored in the records management system.
- F. QA records may be originals or reproducible copies unless otherwise required.
- G. Documents referenced in final reports, except readily available references such as encyclopedias, dictionaries, engineering handbooks, and national codes and standards, shall be retrievable from records management system.
- H. Preparers of such records shall ensure that the documents are entered into the records management system.

# 1.5.3 Indexing Records (NQA-1-1989, Supplement 17S-1, Section 2.1, Section 2.4, Section 2.6)

The records system shall provide for the indexing of QA records according to the following requirements:

- A. An individual or organization shall be assigned the responsibility of indexing and maintaining QA records.
- B. The indexing system shall identify, at a minimum, the location of the record and the established record schedule.
- C. The indexing system shall provide sufficient information to permit association/ identification between the records and the item(s) or activity(ies) to which they apply.
- 1.5.4 Classifying Records (NQA-3-1989, Basic Requirement 17.3; 40 CFR 191; NQA-1-1989, Supplement 17S-1, Section 2.7, Section 2.7.1 (a) & (c), Section 6)
- A. QA Records shall be classified as either "post-closure", "lifetime", or "nonpermanent".
- B. Post-closure QA records shall be defined as waste disposal repository records, that are created in order to preserve knowledge about location, design, and contents of the disposal system.

Records that are to be classified as "post-closure" QA records are:

- 1. Records assisting prevention of actions that could impair the long-term isolation of the waste
- 2. Records preserving information that would prevent inadvertent human intrusion, such as the nature and hazard of the waste and the locations of the geologic repository operations area, the underground facility, boreholes and shafts, and boundaries of the controlled area
- 3. Records providing information relevant to post-closure monitoring and assessment of performance of the repository system
- 4. Records preserving for future generations information regarding the geologic setting relevant to mitigation of releases of radioactive materials
- 5. Records of significant value in exercising the retrieval option for waste packages after decommissioning and closure of the repository

Post Closure records are scheduled in accordance with the NARA-compliant records disposition schedules.

- C. Records not falling into the categories listed above, but falling into one or more of the following categories, shall be classified as "lifetime" QA records:
  - 1. Records used for repository permitting or certification
  - 2. Records used to identify and assess the performance capabilities of those engineered and natural barriers important to waste isolation
  - Records of computer programs and mathematical models needed to perform ongoing correlations between performance assessment predictions and actual tests and data analyses
  - Records of significant value in demonstrating the capability for safe operation of the WIPP repository or in determining the cause of an accident or a malfunction of an item in the WIPP repository
  - 5. Records of significant value in maintaining, reworking, repairing, replacing, or modifying WIPP repository systems, components, or structures
  - 6. Records needed during decommissioning and closure of the repository
  - 7. Records relating to site characterization samples and data
  - 8. Records relating to data used in performance assessment of the WIPP facility
  - 9. Records documenting regulatory compliance
  - 10. Records providing required baseline data for in-service inspections

## NOTE: "Lifetime" in this document means "Life of the Facility." Records may be kept longer than the lifetime of the facility, if required.

- D. Lifetime QA records are required to be retained and preserved in an acceptable condition for the operating life of the repository (i.e., until termination of the HWFP).
- E. Prior to destruction of any lifetime record, it shall be evaluated for upgrade to a post-closure record.
- F. Records that provide objective evidence that the QA program has been properly implemented, but that do not meet the criteria for post-closure or lifetime records, shall be classified as "nonpermanent" QA records. The retention period for nonpermanent records shall be established in writing.

G. Records shall be classified in accordance with the requirements of the major regulatory requirements documents listed in Table I-1. In the case of conflicts between the records requirements contained in these documents, the most stringent requirements shall be used in determining the records classification.

## 1.5.5 Receiving Records (NQA-1-1989, Supplement 17S-1, Section 3.2, Section 3.3, Section 4.1 (c))

Each organization responsible for the receipt of QA records shall designate a person or organization responsible for receiving the records. The designee shall be responsible for organizing and implementing a system of controls for the receipt of QA records including legacy paper records for permanent and temporary storage. At a minimum, the receipt control system shall include:

- A. Provisions to permit a current and accurate assessment of the status of QA records
- B. A method for identifying the records required to be included in the records management system
- C. A method for identifying the records that have been received
- D. Procedures for the receipt and inspection of incoming records, including verification that the QA records received are in agreement with the transmittal document and that the records are legible
- E. Provisions to control and protect the records from damage or loss during the receiving processes
- F. A method for timely submittal of completed records to the storage facility
- 1.5.6 Storage, Preservation, Safekeeping, and Disposition of Records (NQA-1-1989, Supplement 17S-1, Sections 2.7.1, 2.9, 4.1, 4.2, 4.3, 4.4, 5, 6; NQA-3-1989, Basic Requirement 17.39(b)(7); HWFP Att. C WAP, Sections C-4a(6), C-7; 36 CFR Chapter 12, Subpart B, Section 1230.10 (a); DOE O 243.1b)
- A. QA records shall be stored and preserved in predetermined storage facilities in accordance with approved QA implementing procedures that provide:
  - 1. A description of the storage facility
  - 2. A description of the filing and indexing systems used
  - 3. For records submitted to the WIPP Records Archive for final disposition preparation, provisions for providing a receipt acknowledgement to the sender shall be included

- 4. A description of controls governing QA records access, retrieval, and removal
- 5. A method for filing supplemental information and documenting the authorization for corrections
- B. The records storage location shall provide adequate protection of records, including special processed records (such as radiographs, photographs, negatives, microfilm, magnetic media, or other electronic media) to preclude damage from:
  - 1. Natural disasters such as winds, floods, or fires
  - 2. Environmental conditions such as high and low temperatures, humidity, dust, pressure, and particulate matter
  - 3. Infestation of insects, mold, or rodents
- C. Records shall be firmly attached in binders or placed in folders or envelopes in steel file cabinets or on shelving in containers.
- D. Records that require special processing and control, such as software and related documentation or information on high-density media or optical disks, or hardware and software required to maintain and access records, shall be controlled to ensure that the records are useable.
- E. Lifetime QA records shall be retained and preserved in an acceptable condition for the operating life of the WIPP repository (i.e., until termination of the operating permits), or for the particular item while it is installed in the repository or is being stored for future use (NQA-1-1989). Lifetime records shall be evaluated for the need to be upgraded to post-closure records prior to their destruction.
- F. Waste characterization data and related QA/Quality Control (QC) records in the site project files for TRU waste to be shipped to the WIPP facility are designated as either lifetime records or nonpermanent records as specified in Attachment C of the WIPP Hazardous Waste Facility Permit. Records that are designated as lifetime records shall be maintained for the life of the participating generator/storage site waste characterization program plus six years, or transferred for permanent storage to the WIPP Records Archive. Waste characterization records designated as nonpermanent records shall be maintained for ten years from the date of generation at the participating generator/storage site, or at the WIPP Records Archive, and then dispositioned according to their approved file plan. If a generator/storage site ceases to operate, records shall be transferred before closeout for management at the WIPP Records Archive.

- G. Records relevant to an enforcement action under the WIPP HWFP, regardless of assigned dispositions, shall be maintained at the TRU waste site until the New Mexico Environment Department (NMED) determines that they are no longer needed for enforcement actions, and then dispositioned as required.
- H. Waste characterization data for each TRU mixed waste container transported to WIPP shall be maintained by the CBFO for the active life of the WIPP facility plus two years. The active life of the WIPP facility is defined as the period from the initial receipt of TRU mixed waste at the facility until NMED receives certification of final closure of the facility. After their active life, records shall be retired to the WIPP Records Archive and maintained for 30 years.
- Design and construction of a single records storage facility shall meet the applicable requirements of American Society of Mechanical Engineers (ASME) NQA-1-1989, ASME NQA-3-1989, 10 CFR 71, and current requirements of NARA.
- J. Records storage facility construction shall be reviewed by a person who is competent in the technical field of fire protection and fire extinguishing to determine adequacy. If the facility is located within an existing structure, the environment and construction of that structure can provide a portion or all of the required criteria.
- K. The following criteria are acceptable alternatives to the current NARA requirements and NQA-1-1989, Supplement 17S-1, section 4.4.1 criteria for a single storage facility:
  - Two-hour fire-rated vault meeting National Fire Protection Association (NFPA) 232-1986, Standards for the Protection of Records, NFPA 232AM-1986, Archives and Records Centers, or both
  - Two-hour fire-rated Class B file containers meeting the requirements of NFPA 232-1986, NFPA 232AM-1986, or both
  - 3. Two-hour fire-rated file room meeting the requirements of NFPA 232-1986, NFPA 232AM-1986, or both, with the following additional provisions:
    - a. Early warning fire detection and automatic fire suppression capability with electronic supervision at a constantly attended central station
    - b. Records storage in fully enclosed metal cabinets
    - c. Adequate access and aisle ways
    - d. Prohibition in the room of work not directly associated with record storage or retrieval
    - e. Prohibition of smoking, eating, or drinking

- f. Two-hour fire-rated dampers or doors in all boundary penetrations
- L. If storage at dual facilities for each record is provided, the facilities shall be at locations sufficiently remote from each other to eliminate the chance of exposure to a simultaneous hazard. Each facility is not required to satisfy the single records storage facility requirements of sections E, F, or G above, but shall meet all other records storage requirements prescribed in this QAPD.
- M. When temporary storage of records (such as for processing, review, or use) is required by an organization's procedures, the records shall be stored in a one-hour fire-rated container. The procedures shall specify the maximum allowable time limit for temporary storage. The container shall bear an Underwriters Laboratories (UL) label (or equivalent) certifying one-hour fire protection or be certified by a person competent in fire protection.
- N. Access to storage facilities shall be controlled. A list designating personnel who are permitted access to the QA records shall be maintained and posted. Measures to protect records against theft and vandalism shall be established to preclude the entry of unauthorized personnel into the storage area.
- O. Measures shall be taken to provide for replacement, restoration, or substitution of lost or damaged records.
- P. QA records shall not be destroyed until the following conditions are met:
  - 1. The appropriately assigned NARA-authorized disposition specifies destruction
  - 2. Regulatory requirements are satisfied
  - 3. Operational status permits the disposal of such records
  - 4. The related contractual requirements have been satisfied
  - 5. In cases of conflicting requirements concerning records retention requirements, the most stringent requirements shall be used in determining the final disposition

## 1.5.7 Correcting Information in Records (NQA-1-1989, Supplement 17S-1, Section 2.9)

- A. Corrections to QA records shall be authorized by the originating organization.
- B. Corrections to QA records should be made using a single line through and shall not obliterate the prior entry. The QA records shall not be corrected with correction fluids or tapes.
- C. Corrections to records will include the initials or signature of the authorized person making the correction and the date the correction was made.

D. If a record is born digital, changes must be tracked in the meta data and a new digital signature required.

#### **SECTION 2 – PERFORMANCE REQUIREMENTS**

### 2.1. WORK PROCESSES (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. Work shall be performed in accordance with established technical standards and administrative controls. Work shall be performed under controlled conditions using approved instructions, procedures, drawings, or other appropriate means. Items shall be identified and controlled to ensure their proper use. Items shall be maintained to prevent their damage, loss, or deterioration. Equipment used for process monitoring or data collection shall be calibrated and maintained.
- B. The intent of this section is to establish the policy that those who have been assigned responsibility for performing work are responsible for achieving and maintaining quality. Those performing work have the goal of doing work correctly the first time. To ensure that those doing the work achieve that goal, management is responsible for establishing processes and procedures to ensure that all work is planned and performed under controlled conditions by personnel who are knowledgeable of the work requirements, and that these individuals are capable of accomplishing the work in accordance with the requirements of this QAPD.
- C. This section further establishes management involvement in the work processes through interaction with personnel performing the work and through review and assessment of ongoing and completed work. This helps to ensure that the definition of "acceptable work performance" is clearly communicated and that personnel are provided the necessary training, resources, and administrative controls to properly accomplish their tasks.

#### 2.1.1 Work (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. Personnel performing work are responsible for the quality of their work. Because the individual worker is the first line in ensuring quality, personnel will be knowledgeable of requirements for work they perform and the capability of the tools and processes they use.
- B. Line managers will ensure that personnel working under their supervision are qualified and are provided the necessary training, resources, and administrative controls to accomplish assigned tasks. Criteria describing acceptable work performance shall be defined for the worker.
- C. Line managers will review work and related information to ensure that the desired quality is achieved and to identify areas needing improvement.
- D. Work shall be planned, authorized, and accomplished under controlled conditions using technical standards, QA requirements, drawings, and implementing procedures commensurate with applicable control levels.

#### 2.1.2 Implementing Procedures (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. Implementing procedures shall be developed, reviewed, and approved by technically competent personnel.
- B. Implementing procedures shall include the following information, as appropriate to the work to be performed:
  - 1. Responsibilities of the organizations affected by the document
  - 2. Technical, regulatory, quality assurance, or other program requirements
  - 3. Sequential description of the work to be performed, including any allowance for out-of-sequence processing
  - 4. Quantitative or qualitative acceptance criteria sufficient for determining that activities were satisfactorily accomplished
  - 5. Prerequisites, limits, precautions, process parameters, and environmental conditions
  - 6. Special qualification and training requirements
  - 7. Verification points and hold points
  - 8. Methods for demonstrating that the work was performed as required (such as provisions for recording inspection and test results, checklists, or sign-off blocks)
  - 9. Identification and classification of QA records to be generated by the implementing procedure
- C. Individuals performing work shall comply with implementing procedures; however, when work cannot be accomplished as described in the implementing procedure or accomplishment of such work would result in an undesirable situation, a condition adverse to quality, or an unacceptable safety risk, the work shall be suspended until the appropriate procedure change provisions are implemented.

### 2.1.3 Item Identification and Control (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

CBFO performs oversight of item identification and control activities performed by program participants. Program participants are responsible for implementation of these requirements.

A. Processes shall be established and maintained to identify, control, and maintain items to prevent their damage, loss, or deterioration. The identification of items shall be maintained to ensure appropriate traceability and its relationship to an applicable

design drawing or other pertinent specifying document. Processes shall be established and implemented to control consumables and items with limited operating or shelf life and to prevent the use of incorrect or defective items.

- B. The following controls shall be established to ensure that only correct and accepted items are used or installed:
  - 1. Items shall be identified and traced from the time of receipt, up to and including installation or end use. Records shall be maintained to ensure that the item can be traced at all times, from its source through installation or end use.
  - 2. Item identification methods shall include physical markings. If physical markings are either impractical or insufficient, other appropriate means shall be employed (such as physical separation, labels or tags attached to containers, or procedural controls). When used, physical markings shall:
    - a. Be applied using materials and methods that provide clear, permanent, and legible identification
    - b. Not be detrimental to the function or service life of the item.
    - c. Be transferred to each part of an identified item when the item is subdivided
    - d. Not be obliterated or hidden by surface treatments, coatings, or installation unless other means of identification are substituted
  - 3. If codes, standards, or specifications include specific identification or traceability requirements (such as identification or traceability of the item to applicable specification and/or grade of material; heat, batch, lot, part, or serial number; or specified inspection, test, or other record(s)), then identification and traceability methods shall be implemented to ensure the special requirements are met.
  - 4. Item identification control system records shall provide the inspection, test, and operating status of items. Items that have satisfactorily passed the required inspections and tests shall be identified. The identification methods shall preclude the inadvertent installation, use, or operation of items that have not passed required inspections and tests.
  - 5. The status of inspections and tests shall be identified either on the items or in documents traceable to the items. Status shall be maintained through the use of status indicators (such as tags, markings, labels, or stamps) or other means (such as inspection or test records), and the authority for applying and removing status indicators shall be specified.

#### 2.1.4 Special Processes (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. Processes shall be considered as special processes if they meet any one or a combination of the following criteria:
  - 1. The results are highly dependent on the control of the process
  - 2. The results are highly dependent on the skill of the operator
  - 3. The quality of the results cannot be readily determined by inspection or test of the product
- B. Where existing codes and standards do not exist, implementing procedures shall be developed and implemented to ensure that special process parameters are controlled and specified environmental conditions are maintained. In addition to the requirements provided in section 2.1.2, special process implementing procedures shall include or reference:
  - 1. The requirements for maintaining records of training/qualification for personnel and quality processes/equipment
  - 2. The conditions necessary for completion of the special process, including equipment, statistical process control, controlled parameters of the process, and calibration requirements

## 2.1.5 Handling, Storage, and Shipping (NQA-1-1989/DOE Order 414-1D/10CFR 830.122)

- A. Handling, storage, cleaning, shipping, and other means of preserving, transporting, and packaging of items shall be conducted in accordance with established work and inspection procedures, shipping instructions, or other specified documents.
- B. If required for critical, sensitive, perishable, or high-value articles, specific implementing procedures for handling, storage, cleaning, packaging, shipping, and other preservation shall be prepared and used.
- C. Measures shall be established and implemented for the marking and labeling of items for packaging, shipping, handling, and storage as necessary to adequately identify, maintain, and preserve the item. Markings and labels shall indicate the presence of special environments or the need for special controls, as necessary, and shall be applied and removed by authorized personnel.
- D. If required for protection or maintenance of particular items, special equipment (such as containers, shock absorbers, and accelerometers) and special protective environments (such as inert gas and specific moisture and temperature levels) shall be specified, planned for, and provided.

- 1. If special protective equipment and environments are used, provisions shall be made for verifying their adequacy.
- 2. Special handling tools and equipment shall be used and controlled, as necessary, to ensure safe and adequate handling.
- Special handling tools and equipment shall be inspected and tested at specified intervals and in accordance with implementing procedures to verify adequate maintenance.
- 4. Operators of special handling and lifting equipment shall be sufficiently experienced and trained.
- E. If storage of items is required, methods shall be established for the control of item identification records that are commensurate with the planned duration and conditions of storage. These methods shall provide for, as applicable:
  - 1. Maintenance or replacement of markings and identification tags damaged during handling or aging
  - 2. Protection of identification markings that are subject to excessive deterioration due to environmental exposure
  - 3. Update of related identification records and documentation
- F. Status indicators, such as tagging valves and switches to prevent inadvertent operation, shall be used to indicate the operating status of items. Status indicators, such as lockout tags, shall also be used where appropriate and shall be applied and removed by authorized personnel.

#### 2.2 DESIGN CONTROL (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

CBFO performs oversight of design activities performed by program participants.

- A. Items and processes shall be designed using sound engineering and scientific principles and appropriate standards. It is CBFO's expectation that program participants will implement DOE-STD-1073-2016, Configuration Management. Design work, including changes, shall incorporate appropriate requirements, such as general design criteria and design basis, including scientific data collection and modeling. Design interfaces shall be identified and controlled.
- B. The adequacy of design products shall be verified by individuals or groups other than those who performed the design work. Required verification and validation (V&V) shall be completed before approval and implementation of the design.

C. Designs (from conceptual through final) shall be defined, controlled, and verified. In establishing design controls, management is responsible for ensuring that design inputs are technically correct; that design interfaces are identified; that authorities, responsibilities, and lines of communication are clearly defined; and that the design processes clearly define the acceptance criteria for the product.

#### 2.2.1 Design Input (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

Applicable design inputs such as design bases, conceptual design reports, performance requirements, regulatory requirements, codes, and standards shall be controlled by those responsible for the design in accordance with the following requirements:

- A. Design inputs shall be identified and documented and their selection reviewed and approved by those responsible for the design.
- B. Design inputs shall be specified and approved on a timely basis to the level of detail necessary to permit the design work to be carried out correctly in a manner that provides a consistent basis for making design decisions, accomplishing design verification, and evaluating design changes.
- C. Changes from approved design inputs and reasons for the changes shall be identified, approved, documented, and controlled.
- D. Design inputs based on assumptions that require reverification shall be identified and controlled.

### 2.2.2 Design Process (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

The design process shall be controlled according to the following requirements:

- A. Appropriate standards shall be identified and documented and their selection reviewed and approved. Changes from specified standards, including the reasons for the change, shall be identified, approved, documented, and controlled.
- B. Design work shall be prescribed and documented on a timely basis and to the level of detail necessary to permit the design process to be carried out correctly.
- C. Design documents shall be adequate to support design, fabrication, construction, and operation. Applicable information derived from experience, as set forth in reports or other documentation, shall be made available to cognizant design personnel.
- D. Design analysis documents shall be sufficiently detailed as to purpose, method, assumptions, design input, references, and units such that a person technically qualified in the subject can review and understand the analysis documents and verify the adequacy of the results without recourse to the originator.

- E. Design documents shall identify assemblies and/or components that are part of the item being designed. If a commercial grade assembly or component is modified or selected by special inspection or testing to meet requirements that are more restrictive than the supplier's published product description, then the assembly or component shall be represented as different from the commercial grade item (CGI) in a manner traceable to a documented definition of the difference.
- F. Controls for selecting and reviewing design methods, materials, parts, equipment, and processes essential to the function of an item shall be established.
- G. Drawings, specifications, and other design output documents shall contain appropriate inspection and testing acceptance criteria.

### 2.2.3 Design Analyses (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. Design analysis documents shall be controlled.
- B. Documentation of design analyses shall include:
  - 1. Definition of the objective of the analyses
  - 2. Definition of design inputs and their sources
  - 3. Results of literature searches or other applicable background data
  - 4. Identification of assumptions and designation of those assumptions that shall be verified as the design proceeds
  - Identification of any computer calculations, including computer type, computer software name, revision identification, inputs, outputs, and the bases (or reference thereto) supporting application of the software to the specific physical problem
  - 6. Identification of the reviewer and the approver
- C. Calculations shall be identifiable by subject (including structure, system, or component to which the calculation applies), originator, reviewer, and date, or by other designator such that the calculations are traceable.
- D. Computer software shall have its data input and computations verified against the controlled design and conceptual models or the computer software shall be acquired, developed, controlled, verified prior to use, approved for use, and used according to the requirements of Section 6.

#### 2.2.4 Design Interface (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. Design interfaces shall be identified, documented, and controlled so that efforts are coordinated among participating organizations.
- B. Design interface controls shall include the assignment of responsibility and the establishment of implementing procedures among participating design organizations for the review, approval, release, distribution, and revision of documents involving design interfaces.
- C. Design information transmitted across interfaces shall be documented and controlled.
- D. The status of the design information or issued design documents shall be identified in transmittals. Where necessary, incomplete items that require further evaluation, review, or approval shall be identified.

### 2.2.5 Design Verification (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

The acceptability of design work and documents, including design inputs, processes, outputs, and changes, shall be verified. The following design control requirements shall be applied to verify the adequacy of design:

- A. Design verification shall be performed using one or a combination of the following methods:
  - 1. Design review
  - 2. Alternate calculations
  - 3. Qualification testing
- B. The particular design verification method shall be identified and its use justified.
- C. The results of design verification shall be clearly documented, including the identification of the verifier.
- D. Design verification shall be performed by competent individuals or groups other than those who performed the original design (but they may be from the same organization). If necessary, this design verification may be performed by the originator's supervisor, provided that:
  - The supervisor did not specify a singular design approach or rule out certain design considerations and did not establish the design inputs used in the design.
  - 2. The supervisor is the only individual in the organization competent to perform the verification.

- 3. The determination to use the supervisor is documented and approved in advance.
- E. Design verification shall be performed at appropriate times during the design process.
  - 1. Verification shall be performed before release for procurement, manufacture, construction, or release to another organization for use in other design work.
  - 2. Design verification shall be completed before relying on an item to perform its function.
- F. The extent of the design verification required shall be based on the complexity, risk, uniqueness of design, complexity of design, degree of standardization, state of the art, and similarity to previously proven designs. When the design has been subjected to a verification process in accordance with this QAPD, the verification process need not be duplicated for identical designs.
- G. Use of previously proven designs shall be controlled according to the following requirements:
  - 1. The applicability of standardized or previously proven designs shall be verified with respect to meeting pertinent design inputs for each application.
  - 2. Known problems affecting standard or previously proven designs and their effects on other features shall be considered.
  - 3. The original design and associated verification measures shall be adequately documented and referenced in the files of subsequent application of the design.
  - 4. Changes in previously verified designs shall require reverification. Such reverifications shall include the evaluation of the effects of those changes on the overall previously verified design and on any design analyses upon which the design is based.

### 2.2.6 Design Reviews (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. Design reviews shall be controlled, documented, and performed, and shall consider the following:
  - 1. Design inputs were correctly selected and incorporated.
  - 2. Assumptions necessary to perform the design work were adequately described, reasonable, and reverified as necessary.
  - 3. Appropriate design methods were used.

- 4. Design output is reasonable compared to design inputs.
- 5. The necessary design input and verification requirements for interfacing organizations were specified in the design documents or in supporting implementing procedures.
- B. Disposition of design review comments shall be documented.

#### 2.2.7 Alternative Calculations (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

Alternative calculations are calculations or analyses that are made using alternate methods to verify correctness of the original calculations or analyses. The appropriateness of any assumptions, the input data used, any computer programs, or other calculation methods used, shall be evaluated.

### 2.2.8 Qualification Testing (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

If design adequacy is to be verified by qualification tests, the tests shall be preidentified. When qualification testing is used, the following requirements shall apply:

- A. The test configuration shall be defined and documented.
- B. Testing shall demonstrate the adequacy of performance under conditions that simulate the most adverse design conditions. Operating modes and environmental conditions in which the item must perform satisfactorily shall be considered in determining the most adverse conditions.
- C. If the tests verify only specific design features, the other features of the design shall be verified by other means.
- D. Test results shall be documented and evaluated by the responsible design organization to ensure that test requirements have been met.
- E. If qualification testing indicates that a modification to an item is necessary to obtain acceptable performance, the modification shall be performed in accordance with an approved procedure. The modification shall be adequately documented and the modified item retested or otherwise verified to ensure satisfactory performance.
- F. Scaling laws shall be established and verified when tests are being performed on models or mockups.
- G. The results of model test work shall be subject to error analysis, where applicable, before the results are used in final design work.

#### 2.2.9 Design Change (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

Design changes shall be controlled in accordance with the following requirements:

- A. Changes to final designs, field changes, and nonconforming items dispositioned "use as is" or "repair" shall be justified and shall be subject to design control measures commensurate with those applied to the original design.
- B. Design control measures for changes shall include provisions to ensure that the design analyses for the item are still valid.
- C. Changes shall be approved by the same groups or organizations that reviewed and approved the original design documents, with the following considerations:
  - If an organization that originally was responsible for approving a particular design document is no longer responsible, the new responsible organization shall be designated.
  - 2. The cognizant design organization shall have demonstrated competence in the specific design area of interest and have an adequate understanding of the requirements and intent of the original design.
- D. When a design change is approved other than by revision to the affected design documents, measures shall be established to incorporate the change into these documents, where such incorporation is appropriate.
- E. If a significant design change becomes necessary because of an incorrect original design, the design process and design verification methods and implementing procedures shall be reviewed and modified as appropriate. These design deficiencies shall be documented according to the requirements provided in section 1.3.2.
- F. Field changes shall be incorporated into the applicable design documents.
- G. Design changes that affect related implementing procedures or training programs shall be communicated to the appropriate organizations.

# 2.3 ACQUISITION/PROCUREMENT (Control of Purchased Items and Services) (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

The CBFO and participant organizations shall ensure that procured items and services meet established technical and QA requirements, that applicable requirements are appropriately flowed down to sub-tier providers, and that procured items and services perform as specified. Prospective suppliers shall be evaluated and selected on the basis of documented criteria. The responsible organization shall verify that approved suppliers continue to provide acceptable items and services. All procurements by the

CBFO and program participants shall be in compliance with applicable requirements of the DEAR/FAR.

## 2.3.1 Acquisition/Procurement Planning Requirements (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

The requirements for procurement and design control described in this QAPD are sufficient to implement the requirements associated with Suspect/Counterfeit Items (S/CI) Prevention described in DOE O 414.1D, Attachment 3, and are consistent with the CBFO activity hazards and mission impact.

Procurement activities shall be planned as early as practicable. At a minimum, the activities shall be planned no later than the start of those procurement activities that are required to be controlled. Procurement planning shall be documented to ensure a systematic approach to the procurement process. Procurement planning shall:

- A. Identify procurement methods and organizational responsibilities, including the appropriate QA organization
- B. Identify and document the sequence of actions and milestones needed to effectively complete the procurement
- C. Provide for the integration of the following activities:
  - 1. Procurement document preparation, review, and change control
  - 2. Selection of procurement sources
  - 3. Proposal or bid evaluation and award
  - 4. Purchaser evaluation of supplier performance
  - 5. Purchaser verifications, including any hold-point and witness-point notifications
  - Control of nonconformances
  - 7. Corrective action
  - 8. Acceptance of the item or service
  - 9. Identification of QA records

#### 2.3.2 Supplier Selection (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

A. Supplier selection shall be based on evaluation of the supplier's capability to provide items or services in accordance with procurement document requirements.

- B. Organizations responsible for supplier source selection shall be identified and shall include the appropriate QA organization.
- C. Measures for selecting procurement sources shall include one or more of the following elements:
  - 1. An evaluation of the supplier's history for providing an identical or similar product that performs satisfactorily in actual use
  - 2. An evaluation of the supplier's current QA documentation, supported by any documented qualitative and quantitative information
  - 3. An evaluation of the supplier's technical and QA capability, based on an evaluation of the supplier's facilities, personnel, and quality program implementation
- D. The results of procurement source selection shall be documented.

#### 2.3.3 Proposal/Bid Evaluation (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. The proposal or bid evaluation process shall include a determination of the extent of conformance to the procurement document requirements. This evaluation shall be performed by designated, technically qualified personnel, including the QA organization, and shall include, at a minimum, the following:
  - 1. Technical considerations
  - 2. QA program requirements
  - 3. Supplier personnel skills
  - 4. Supplier production capabilities
  - 5. Supplier past performance
  - 6. Alternatives proposed by the supplier
  - 7. Exceptions taken by the supplier
- B. Before the contract is awarded, the purchaser shall resolve, or obtain commitments to resolve, deficiencies identified during the proposal or bid evaluation.
- C. Supplier QA provisions shall be accepted by the purchaser QA management before the supplier is authorized to start work.

## 2.3.4 Procurement Document Requirements (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

Procurement documents shall include the following, as applicable to the item or service being procured:

- A. The scope of work
- B. Technical requirements, including the following:
  - 1. Design bases shall be identified or referenced.
  - Specific documents (such as drawings, codes, standards, regulations, DOE orders, procedures, or instructions) that describe the technical requirements of the items or services to be furnished shall be identified. The revision level or change status of these documents shall also be identified.
  - 3. Tests, inspections, hold points, and acceptance criteria that the purchaser shall use to monitor and evaluate the performance of the supplier shall be specified.
- C. QA provisions specified by the purchaser QA organization shall include:
  - 1. The requisite QA and documentation requirements, depending on the control level of the item or service being procured
  - 2. The specific pass-down requirements that the supplier shall incorporate into any sub-tier procurement document
  - 3. When deemed appropriate, the purchaser may permit some or all supplier work to be performed under the purchaser QA program, provided that the requirements are adequately implemented. In these cases, procurement documents shall specify that the purchaser's QA implementing procedures are applicable to the supplier and that the purchaser shall provide these applicable documents to the supplier.
  - 4. Right of access to supplier facilities and records for inspection and audit by the purchaser, the CBFO, or other designee authorized by the purchaser
  - 5. The requirements of section 1.5 and provisions for disposition, if the supplier is required to maintain QA records
  - 6. Requirements for the supplier to report nonconformances and obtain purchaser approval of supplier-recommended dispositions
  - 7. Documentation required to be submitted for information, review, or approval shall be identified. The time of submittal shall also be established. If required, the retention, classification, and disposition of documentation that will become QA

- records shall be identified. The supplier's nonpermanent records shall not be disposed of until the related items are released for shipment.
- 8. Spare and replacement parts or assemblies and the appropriate technical and QA requirements for ordering

## 2.3.5 Procurement Document Review and Approval (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. A review of the procurement documents and any changes thereto shall be made to verify that documents include appropriate provisions to ensure that items or services meet the prescribed requirements. Procurement document changes shall be subject to the same degree of control as the original documents.
- B. Procurement document reviews shall be performed and documented prior to the document being issued to the supplier.
- C. Reviews shall be performed by personnel who have access to pertinent information and who have adequate understanding of the requirements and scope of the procurement.
- D. Procurement document reviews shall include representatives from the technical and QA organizations and shall be approved by responsible management.

## 2.3.6 Supplier Performance Evaluation (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

The purchaser of items and services shall establish measures to interface with the supplier and to verify supplier performance, as deemed necessary by the purchaser. The measures shall include:

- A. Establishing an understanding between the purchaser and supplier of the requirements and specifications identified in the procurement documents
- B. Requiring the supplier to identify planning techniques and processes to be used in fulfilling procurement document requirements
- C. Reviewing supplier documents that are prepared or processed during work performed to fulfill procurement requirements
- D. Identifying and processing necessary change information
- E. Establishing the method to be used to document information exchanges between purchaser and supplier
- F. Establishing the extent of assessment activities and inspection

#### 2.3.7 Control of Supplier Generated Documents

Supplier generated documents shall be controlled, handled, and approved in accordance with established methods. Means shall be implemented to assure that the submittal of these documents is accomplished in accordance with the procurement document requirements. These measures shall provide for the acquisition, processing, and recorded evaluation of technical, inspection, and test data against acceptance criteria.

#### 2.3.8 Control of Changes in Items or Services

The Purchaser and Supplier shall assure that measures to control changes in procurement documents are established, implemented, and documented and are in accordance with this document.

## 2.3.9 Acceptance of Items or Services (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. Methods shall be established for the acceptance of an item or service being furnished by a supplier.
- B. Prior to offering an item or service for acceptance, the supplier shall verify that the item or service complies with the procurement requirements.

### 2.3.9.1 Source Verification (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. The purchaser may accept an item or service by monitoring, auditing, surveilling, witnessing, or observing activities performed by the supplier. This method of acceptance is called source verification. Purchaser's verification activities, however, shall not relieve the supplier of responsibility for quality achievement.
- B. The extent of source verification shall be a function of the relative importance, complexity, and quantity of items or services being procured, as well as the supplier's quality of performance. Source verifications shall be accomplished as early as possible, but prior to the start of those activities that are required to be controlled, and shall include the active involvement of the purchaser's QA organization. In addition:
  - Source verification shall be accomplished consistent with the supplier's planned inspections, examinations, or tests and performed at intervals consistent with the importance and complexity of the item.
  - 2. Documented evidence of acceptance of source-verified items or services shall be furnished to the party receiving the item, to the purchaser, and to the supplier.
  - 3. Source verification shall be performed by qualified personnel.

- C. For procurement of services only (such as third-party inspection, engineering and consulting services), and installation, repair, overhaul, or maintenance work, the purchaser shall accept the service by any or all of the following methods:
  - 1. Technical verification of data produced
  - 2. Surveillance and/or audit of the activity
  - 3. Review of objective evidence for conformance to procurement document requirements such as certifications or test reports

### 2.3.9.2 Receiving Inspection (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

When a receiving inspection is used to accept an item:

- 1. The inspection shall include consideration of source assessments, verifications and audits, and the demonstrated quality performance of the supplier.
- 2. The inspection shall be performed in accordance with established inspection procedures or instructions.
- 3. The inspection shall verify the Certificate of Conformance as applicable; proper configuration; identification; dimensional, physical, and other characteristics; freedom from shipping damage; and cleanliness.
- 4. The inspection shall be planned and executed in accordance with the applicable requirements of section 2.4.
- 5. Receiving inspection shall include a review of the adequacy and completeness of any required supplier documentation.

#### 2.3.9.3 Post-Installation Testing (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

When post-installation testing is used as a method of acceptance, post-installation test requirements and acceptance documentation shall be mutually established and agreed upon by the purchaser and supplier.

## 2.3.9.4 Supplier Certificate of Conformance (NQA-1-1989/DOE O 414-1D/10 CFR 830.122

When a certificate of conformance is used, the following, at a minimum, shall be met:

A. The certificate shall identify the purchased material or equipment, including the purchase order and item number or other identification that is traceable to the requirements of the procurement document.

- B. The certificate shall identify the specific procurement requirements met by the purchased material or equipment, such as codes, standards, and other specifications. The procurement requirements identified shall include any approved changes, waivers, or deviations applicable to the subject material or equipment.
- C. The certificate shall identify any procurement requirements that have not been met, together with an explanation and the means for resolving the nonconformances.
- D. The certificate shall be signed or otherwise authenticated by an official of the supplier organization, whose function and position are described in the supplier's QA program.
- E. The certification system, including the procedures to be followed in filling out a certificate and the administrative procedures for review and approval of the certificate, shall be described in the purchaser or supplier QA program.
- F. Means shall be provided to verify the validity of supplier certificates and the effectiveness of the certification system, such as during the performance of audits of the supplier or independent inspection or test of the items. Such verification shall be conducted by the purchaser at intervals commensurate with the supplier's past quality performance.

## 2.3.10 Control of Supplier Nonconformances (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

The purchaser and supplier shall establish and document the process for dispositioning items and services that do not meet procurement document requirements in accordance with the following:

- A. The supplier shall submit a report of nonconformance to the purchaser that includes supplier-recommended disposition (for example, "use as is" or "repair") and provide technical justification for such disposition.
- B. Reports of nonconformances to procurement document requirements or documents approved by the purchaser shall be submitted to the purchaser for approval. Examples of conditions requiring a report of nonconformance include:
  - 1. Failure to meet technical or material requirements
  - 2. Failure to meet a requirement in supplier documents that have been approved by the purchaser
  - 3. The nonconformance cannot be corrected by continuation of the original manufacturing process or by rework

- 4. The item does not conform to the original requirement even though the item can be restored to a condition such that its capability to function is unimpaired (i.e., a waiver is requested)
- C. The purchaser shall evaluate and approve the supplier-recommended disposition.

### 2.3.11 Commercial Grade Items (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

Where the design specifies the use of CGIs, the following requirements are an acceptable alternative to other requirements of this section.

- A. The CGI shall be identified in an approved design output document, such as a drawing, specification, or other document translated from a design input document. An alternative CGI may be applied as long as the responsible design organization provides verification that the alternative CGI performs the intended function and meets design requirements that are applicable to both the replaced item and its application.
- B. Source evaluation and selection, where determined necessary by the purchaser based on complexity and importance to CRA, waste characterization and certification, repository performance assessment, waste isolation, waste transportation, nuclear and industrial safety, environmental protection, and management and operation of the WIPP facility, shall be in accordance with section 2.3.2.
- C. CGIs shall be identified in the procurement document by the manufacturer's published product description.
- D. After receipt of a CGI, the purchaser shall ensure that:
  - 1. Damage was not sustained during shipment
  - 2. The item received was the item ordered
  - 3. Inspection or testing is accomplished, to the extent determined by the purchaser, to ensure conformance with the manufacturer's published requirements
  - 4. Documentation, as applicable to the item, was received and is acceptable
- E. Formal commercial grade dedication (CGD) performed by program participants, shall be based on the requirements of ASME NQA-1-2008, Subpart 2.14, Quality Assurance Requirements for Commercial Grade Items and Services, and implementation guidance from DOE-HDBK-1230-2019, Commercial Grade Dedication Application Handbook.

## 2.3.12 Suspect Counterfeit Items Control (DOE O 414-1D Attachment 3)

Program participants are responsible for developing an S/CI Prevention program/process in accordance with DOE O 414.1D, Attachment 3, as directed by the appropriate site office.

The CBFO performs oversight of the CBFO participants' implementation of the following requirements:

- A. A point of contact with the Office of Health, Safety, and Security is assigned.
- B. Training and information is provided to managers, supervisors, and workers on S/CI processes and controls (including prevention, detection, and disposition of S/CIs).
- C. Prevent introduction of S/CIs into DOE work by:
  - 1. Engineering involvement:
    - a. In the development of procurement specifications;
    - b. During inspection and testing; and
    - c. When maintaining, replacing, or modifying equipment.
  - 2. Identifying and placing technical and QA requirements in procurement specifications;
  - 3. Accepting only those items that comply with procurement specifications, consensus standards, and commonly accepted industry practices; and
  - 4. Inspecting inventory and storage areas to identify, control, and disposition for S/CIs.
- D. Include processes for inspection, identification, evaluation, and disposition of S/CIs that have been installed in safety applications and other applications that create potential hazards. Also address the use of supporting engineering evaluations for acceptance of installed S/CIs as well as marking to prevent future reuse.
- E. Conduct engineering evaluations to be used in the disposition of identified S/CIs installed in safety applications/systems or in applications that create potential hazards. Evaluations must consider potential risks to the environment, the public and workers along with a cost/benefit impact, and a schedule for replacement (if required).
- F. Perform the evaluation to determine whether S/CIs installed in non-safety applications pose potential safety hazards or may remain in place. Disposition S/CIs identified during routine maintenance and/or inspections to prevent future use in these applications.

- G. Report to the DOE Inspector General in accordance with DOE O 221.1, Reporting Fraud, Waste and Abuse to the Office of Inspector General.
- H. S/CIs must be reported in accordance with DOE O 232.2A, current version.
- Collect, maintain, disseminate, and use the most accurate, up to date information on S/CIs and suppliers. Sources are identified on the DOE S/CI website (http://www.hss.energy.gov/sesa/corporatesafety/sci/).
- J. Conduct trend analyses for use in improving the S/CI prevention process.

## 2.4 INSPECTION AND TESTING (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

The CBFO performs oversight of the CBFO participants' implementation of the following requirements:

- A. Inspections and testing shall be performed in accordance with approved implementing procedures. An essential part of the work planning process is to identify the items and processes to be inspected or tested, the parameters or characteristics to be evaluated, the techniques to be used, the acceptance criteria, any hold points, and the organizations responsible for performing the tests and inspections. Inspection for acceptance shall be performed by personnel other than those who performed or directly supervised the work being inspected. Inspection and testing of specified items and processes shall be conducted using established acceptance and performance criteria. The acceptance of items and processes shall be made by and documented by qualified and authorized personnel. Equipment used for inspections and tests shall be calibrated and maintained.
- B. Inspection and testing activities shall be conducted in accordance with the following requirements, as applicable.

# 2.4.1 Qualification of Inspection and Test Personnel (NQA-1-1989/DOE O 414-1D/10 CFR 830.122

This section provides amplified requirements for the qualification of personnel who perform inspection and testing to verify conformance to specified requirements for the purpose of acceptability. The requirements of this section do not apply to the qualification of personnel for performance of nondestructive examination. Qualification of personnel for nondestructive examination is addressed in section 2.4.2.

A. The responsible organization shall designate those activities that require qualified inspection and test personnel and the minimum requirements for such personnel. Further, the responsible organization shall establish written procedures for the qualification of inspection and test personnel and for the assurance that only those personnel who meet the requirements of this section are permitted to perform applicable inspection and test activities.

- B. When a single inspection or test requires implementation by a team or a group, personnel not meeting the requirements of this section may be used in data-taking assignments or in plant or equipment operation, provided they are supervised or overseen by a qualified individual.
- C. Personnel selected for performing inspection and test activities shall have the experience or training commensurate with the scope, complexity, or special nature of the activities.
- D. Provisions shall be made for the indoctrination of personnel to the technical objectives and requirements of the applicable codes and standards and the QA program controls that are to be employed.
- E. The need for a formal training program shall be determined, and such training activities shall be conducted as required to qualify personnel that perform such inspections and tests. On-the-job training shall also be included in the program, as appropriate, with emphasis on first-hand experience gained through actual performance of inspections and tests; the results of which shall be verified for conformance by a qualified person until certification is achieved.
- F. The capabilities of a candidate for certification shall be initially determined by a suitable evaluation of the candidate's previous education, experience, training, and either test results or capability demonstration.
- G. The job performance of inspection and test personnel shall be reevaluated for capability at periodic intervals, not to exceed three years. Reevaluation shall be by evidence of continued satisfactory performance or redetermination of capability in accordance with the above requirements. If, during this evaluation or at any other time, it is determined by the responsible organization that the capabilities of an individual are not in accordance with the qualification requirements specified for the job, that person shall be removed from that activity until such time as the required capability has been demonstrated. Any person who has not performed inspection or testing activities in their qualified area for a period of one year shall be reevaluated for the required capability in accordance with the above requirements.
- H. The qualification of personnel shall be certified in writing in an appropriate form and shall include the following information:
  - 1. Employer's name
  - 2. Identification (name) of person being certified
  - 3. Activities certified to perform
  - 4. Basis used for certification, including such factors as: (1) education, experience, indoctrination, and training; (2) test results, where applicable; and (3) results of capability demonstration

- 5. Results of periodic evaluation
- 6. Results of physical examinations, when required
- 7. Signature of the employer's designated representative responsible for such certification
- 8. The date of certification and date of certification expiration
- The responsible organization shall identify any special physical characteristics needed in the performance of each activity, including the need for initial and subsequent physical examination.
- J. Records of personnel qualification shall be established and maintained by the employer. These records shall include the information required above for certification.

# 2.4.2 Qualification of Nondestructive Examination Personnel (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

This section identifies the requirements for the qualification of personnel who perform nondestructive examination (NDE) (radiographic, magnetic particle, ultrasonic, liquid penetrant, eddy current, neutron radiographic, leak testing, real-time radiography, and visual testing) to verify conformance to specified requirements for NDE.

- A. The American Society of Nondestructive Testing (ASNT) Recommended Practice No. SNT-TC-1A, *Personnel Qualification and Certification in Nondestructive Testing*, June 1980 Edition, and its applicable supplements, shall apply as requirements for personnel performing the above methods of NDE. Later editions of SNT-TC-1A may be used as the basis for the qualification of NDE personnel, as long as the minimum requirements of the June 1980 edition are met.
- B. The responsible organization shall establish written procedures for the control and administration of the training, examination, and certification of NDE personnel.
- C. Records of personnel qualification shall be established and maintained by the employer.

## 2.4.3 Inspection (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

## 2.4.3.1 Inspection Planning (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. Inspection planning shall be performed and documented and shall include:
  - 1. Identification of work operations where inspections are necessary
  - 2. Identification of the characteristics to be inspected and when, during the work process, inspections are to be performed
  - 3. Identification of inspection or process monitoring methods to be employed
  - 4. Identification of acceptance criteria
  - 5. Identification of sampling requirements
  - 6. Methods to record inspection results
  - 7. Selection and identification of the measuring and test equipment (M&TE) to be used to perform the inspection
  - 8. Process used to ensure that the equipment being utilized for inspection or testing is calibrated and is of the proper type, range, accuracy, and tolerance to accomplish the intended function
- B. When statistical sampling is to be used to verify the acceptability of a group of items, the sampling method shall be based on recognized standard practices.

## 2.4.3.2 Inspection Hold Points (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

Hold points are used to control work that is not to proceed without the specific consent of the organization placing the hold point. The specific hold points shall be indicated in appropriate documents. Only the organization responsible for the hold point may waive the hold point. Approval to waive specified hold points shall be documented before continuing work beyond the designated hold point.

# 2.4.3.3 In-Process Inspections and Monitoring (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

A. Items in process shall be inspected as necessary to verify quality. If inspection of processed items is impossible or disadvantageous, indirect control by monitoring of processing methods, equipment, and personnel shall be provided. Both inspection and process monitoring shall be conducted when control is deemed inadequate, using only one of these methods.

- B. When a combination of inspection and process monitoring methods is used, monitoring shall be performed systematically to ensure that the specified requirements for control of the process and the quality of the item are met throughout the duration of the process.
- C. Controls shall be established and documented for the coordination and sequencing of the work at established inspection points during successive stages of the process.

# 2.4.3.4 Final Inspections (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. Final inspections shall include a review of the results and the verification of the resolution of all nonconformances identified by earlier inspections.
- B. Finished items shall be inspected for completeness, markings, calibration, protection from damage, or other characteristics, as required to verify the quality and conformance of the item to the applicable requirements.
- C. Records review shall be performed to ensure adequacy and completeness.
- D. Item modifications, repairs, or replacements that are performed subsequent to final inspection shall require re-inspection or retest, as appropriate, to verify acceptability.

## 2.4.3.5 In-service Inspections (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

- A. Required in-service inspection or surveillance of structures, systems, or components shall be planned and executed by or for the organization responsible for their operation.
- B. Inspection methods shall be established and executed to verify that the characteristics of an item continue to remain within specified limits.
- C. Inspection methods shall include evaluations of performance capability of essential emergency and safety systems and equipment, verification of calibration and integrity of instruments and instrument systems, and verification of maintenance, as appropriate.

## 2.4.3.6 Inspection Documentation (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

Inspection documentation shall identify:

- A. The item inspected and the date of the inspection
- B. The name or unique identifier of the inspector who documented, evaluated, and determined acceptability

- C. The method of inspection
- D. The inspection criteria, sampling plan, or reference documents (including revision designation) used to determine acceptance
- E. The results
- F. The M&TE used during the inspection, including the identification number and the calibration due date
- G. Reference to any information on actions taken in connection with nonconformances, as applicable

# 2.4.4 Test Requirements (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

Test requirements and acceptance criteria shall be provided or approved by the organization responsible for the design of the item to be tested unless otherwise designated. Testing shall be used to determine the capability of an item to meet specified requirements by subjecting the item to a set of physical, chemical, environmental, or operating conditions. Examples of such tests include prototype qualification tests, production tests, proof tests prior to installation, construction tests, pre-operational tests, and operational tests. Test requirements and acceptance criteria shall be based on applicable design or other pertinent technical documents.

## 2.4.4.1 Test Procedures (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

Identify implementing procedures that are to be developed in order to control and perform the test. In lieu of specially prepared written test procedures, appropriate sections of appropriate test methods described in related documents such as American Society for Testing and Materials (ASTM) may be used. If used, the related documents or sections thereof shall be incorporated either directly, or by reference, into the approved test implementing procedure. Test procedures shall include:

- A. The identification of the item to be tested and the test requirements and acceptance limit, including the required levels of precision and accuracy
- B. The identification of the M&TE to be used to perform the test to ensure that the equipment being utilized is calibrated and is of the proper type, range, accuracy, and tolerance to accomplish the intended function
- C. Any test prerequisites, including test equipment, instrumentation and software needs, personnel training and qualification, and suitably controlled environmental conditions
- D. Any mandatory hold points
- E. The methods to be used to record data and results

F. The provisions for ensuring that prerequisites for the given test have been met

## 2.4.4.2 Test Documentation (NQA-1-1989/DOE O 414-1D/10 CFR 830.122)

Test documentation shall identify:

- A. The applicable test requirements, plans, and procedures, including revisions
- B. The item or work product tested
- C. The date of the test
- D. The name of the tester and data recorders
- E. The type of observation and method of testing
- F. The identification of test criteria or reference documents used to determine acceptance
- G. The results and acceptability of the test
- H. The actions taken in connection with any noted deviations
- I. The name of the person evaluating the test results
- J. The identification of the M&TE used during the test (including the identification number and calibration due date)

#### 2.4.4.3 Test Results

Test results shall be documented and their conformance with acceptance criteria shall be evaluated by a qualified individual within the responsible organization to ensure that all test requirements have been satisfied.

#### 2.4.5 Monitoring, Measuring, Testing, and Data Collection Equipment

The CBFO performs oversight of monitoring, measuring, testing, and data collection equipment activities performed by program participants. Program participants are responsible for implementation of these requirements.

The following sections establish requirements to ensure that equipment used for inspection and testing is properly controlled, calibrated, and maintained. Equipment discussed in the following sections includes inspection and test equipment, measuring and data collection equipment, equipment (either hand-held or installed) used for data indication, and other equipment used for data indication, collection, or evaluation. These are called M&TE.

Calibration and control measures may not be required for rulers, tape measures, levels, and other such devices, if normal commercial equipment provides sufficient accuracy.

#### 2.4.6 Use and Control of M&TE

Each organization using M&TE shall:

- A. Establish and document a system to control the use and calibration of M&TE
- B. Have a program to recall for calibration, or remove from service, M&TE that has exceeded its calibration interval; has broken calibration seals; has been modified, repaired, or had components replaced; or is suspected to be malfunctioning because of mishandling, misuse, or unusual results
- C. Establish and maintain documented procedures to evaluate the adequacy of the calibration system and to ensure compliance with the requirements of this QAPD
- D. Maintain records documenting that established M&TE schedules and procedures have been followed. These records shall include an individual record of calibration or other means of control, providing:
  - 1. A description or identification of the item
  - 2. Calibration interval
  - 3. Date calibrated
  - 4. Identification of the calibration source
  - 5. Calibration results (data and status)
  - 6. Calibration action taken (e.g., adjusted, repaired, new value assigned, derated)
  - 7. Evaluation and corrective action taken in response to out-of-calibration conditions
- E. Label all M&TE to indicate the calibration status, the date calibrated, the calibration due date or usage equivalent, and the identification of any limitations. (When it is impractical to apply a label directly to an item, the label may be affixed to the instrument container or some other suitable means may be used to reflect calibration status.)
- F. Evaluate the validity of previous inspection and test results and the acceptability of related items, data collected, and processes monitored, when M&TE is found to be out-of-calibration

- G. Handle, store, and transport M&TE in a manner that does not adversely affect the accuracy of the equipment
- H. Give due consideration to temperature, humidity, lighting, vibration, dust control, cleanliness, electromagnetic interference, and any other factors affecting the results of measurements. Where pertinent, these factors shall be monitored and recorded and, when appropriate, correcting compensations shall be applied to measurement results.

#### 2.4.7 Calibration

- A. M&TE requiring calibration shall be calibrated at periodic intervals established and maintained to ensure acceptable reliability, where reliability is described as the probability that M&TE will remain in tolerance throughout the interval.
- B. M&TE shall be calibrated to provide traceability of the calibration against certified equipment having known valid relationships to nationally recognized standards. If nationally recognized standards do not exist, the bases for calibration shall be documented.
- C. Intervals shall be established for all M&TE requiring calibration unless the equipment is regularly monitored through the use of check standards in a documented measurement assurance process. Check standards must closely represent the item parameters normally tested in the process, and the check standard must be verified periodically.
- D. Where intervals are used to ensure reliability, the interval setting system must be systematically applied and shall have stated reliability goals and a method of verifying that the goals are being attained.
- E. Intervals may be based on usage or time since last calibration.
- F. All exemptions from periodic calibration shall be approved and documented.
- G. The recall system may provide for the temporary extension of the calibration due date for limited periods of time under specified conditions that do not unreasonably impair the satisfaction of task objectives.
- H. If any M&TE is found to be significantly out-of-tolerance during the calibration process, the cognizant organization shall provide for the notification to the user and cognizant QA management of the out-of-tolerance condition, with the associated measurement data, so that appropriate action can be taken.

## **SECTION 3 – ASSESSMENT REQUIREMENTS**

# 3.1 MANAGEMENT ASSESSMENT (DOE O 414.1D, Criterion 9 and NQA-3-1989, Paragraph 2.4)

Managers shall periodically assess their management processes and identify problems that hinder their organization from achieving its directives.

All assessments shall be planned and documented in such a way that the assessment is a value-added process that will lead to improvement in organizational performance, safety, meeting customer expectations, and achieving mission goals in full compliance with regulatory and DOE requirements. The results of completed assessments shall be regularly (at a minimum annually) reported to management so that potential improvements are identified and corrective action (see section 1.3.3) is implemented, as required. The QA manager shall support management in reviewing reports to determine if there are trends or anomalies that need to be further addressed outside of the assessment functional area.

The guidance in DOE G 414.1-1C and DOE G 414.1-2B should be considered when developing an implementing procedure.

#### 3.2 INDEPENDENT ASSESSMENT

- A. Planned and periodic independent assessments shall be conducted to measure item and service quality and process effectiveness, and to promote improvement. The organization performing assessments shall have sufficient authority and freedom from the activities being assessed to carry out its responsibilities. Persons conducting independent assessments shall be technically qualified and knowledgeable of the items and activities being assessed. (DOE O 414.1D, Criterion 10)
- B. The types and frequencies of independent assessments shall be based upon the relevant control levels assigned to the items and activities under the cognizance of the organization. (NQA-1-1989, Supplement 18S-1, Section 2)
- C. The CBFO and participant organizations responsible for the performance of activities important to CRA, waste characterization and certification, repository performance assessment, waste isolation, waste transportation, nuclear and industrial safety, environmental protection, and management and operation of the WIPP site shall implement a program of surveillance and audits to verify compliance, adequacy, and effectiveness of all aspects of the program. (NQA-1-1989, Basic Requirement 18)

#### 3.2.1 Surveillances

A. A program of surveillance of the activities referenced above shall be planned, performed, documented, and reported to appropriate management personnel. The

surveillance process consists of monitoring or observing to verify whether an item, activity, system, or process conforms to specified requirements. (NQA-3-1989, Basic Requirement, Section 2.3); (NQA-1-2008, Subpart 3.1); (NQA-1-1989 18S-1, Section 4)

- B. Surveillances shall accomplish the following:
  - 1. Monitor work in progress
  - 2. Document compliance or noncompliance with established requirements and procedures
  - 3. Identify actual and potential conditions adverse to quality
  - 4. Obtain timely corrective action commitment from cognizant managers for identified conditions adverse to quality
  - 5. Provide notification to responsible managers of the status and performance of work under surveillance
  - 6. Verify timely implementation of corrective actions
- C. Audits or other independent assessments of the subject activities, conducted by the responsible organization, may be counted as satisfying the requirement to do surveillances of related activities in the corresponding surveillance schedule period.

#### 3.2.2 Audits

The following sections describe the audit process requirements.

## 3.2.2.1 Scheduling Audits

- A. Audits shall be scheduled to begin as early in the life of a project or activity as practicable and continue at intervals consistent with the schedule for accomplishing the work and commensurate with the assigned control level (NQA-1-1989, Supplement 18S-1, Section 2). The audit schedule shall be reviewed periodically and revised as necessary to assure that coverage is maintained current. (NQA-1-1989, Supplement 18S-1, Section 2)
- B. Periodically scheduled QA program audits shall be supplemented by, or integrated with, either audits or surveillances of a technical nature (e.g., performance-based audits) which assess the quality of selected work products and work processes. (NQA-1-1989, Supplement 18S-1, Section 2)

## 3.2.2.2 Planning and Preparation for Audits

The organization performing the audit shall develop and document a plan for each audit. (NQA-1-1989, Supplement 18S-1, Section 3.1)

- A. The plan shall include the scope, requirements, purpose, audit personnel, activities to be audited, organizations to be notified, applicable documents, schedule, and written procedures or checklists to be used. (NQA-1-1989, Supplement 18S-1, Section 3.1)
- B. Audit planning shall include a review of past assessment results to determine the nature of problems that have occurred. When recurring problems are found, the audit team shall review corrective actions that have been taken and attempt to determine whether the corrective actions were effective in preventing recurrence. (NQA-3-1989, Basic Requirements, Section 18.2)
- C. Audit preparation shall include review of pertinent background information, procedures, and technical documents so that audit team members are familiar with the work being audited. (NQA-1-1989, Supplement 18S-1, Section 3.1)
- D. Audits shall include technical evaluations of the applicable procedures, instructions, activities, and items, as appropriate. (NQA-1-1989, Supplement 18S-1, Section 4)
- E. The scope shall include related corrective actions taken since the previous assessment.

#### 3.2.2.3 Audit Team Selection

- A. Audit team members shall be identified prior to the start of the audit (NQA-1-1989, Supplement 18S-1, Section 3.3). Team members shall be selected on the basis of technical qualifications and knowledge of the item or process being audited, shall be independent from the items or processes being audited, and shall have sufficient authority and organizational freedom to carry out their assigned responsibilities. In the case of internal audits, personnel having direct responsibility for performing the activities being audited shall not be involved in the selection of the audit team. (NQA-1-1989, Supplement 18S-1, Section 3.2)
- B. An audit team leader shall be appointed to provide indoctrination and supervision of the team, organize and direct the audit, and coordinate the preparation and issuance of the audit report. (NQA-1-1989, Supplement 18S-1, Section 3.3)
- C. Before starting the audit, the audit team leader shall ensure that the assigned personnel collectively have experience and training commensurate with the scope, complexity, or special nature of the work to be audited. (NQA-1-1989, Supplement 18S-1, Section 3.3)

- D. Technical specialists, with appropriate technical expertise or experience in the work being audited, shall be used when auditing the adequacy of technical processes. (NQA-1-1989, Supplement 2S-3, Section 2.1)
- E. Upon selection of the Team Leader and Team Members, sufficient time shall be allowed for individuals to complete the audit process.

#### 3.2.2.4 Auditor Qualification

Auditors shall be technically qualified in their assigned roles. In addition, they shall have appropriate training or orientation to develop their competence for performing audits. Competence of personnel performing various audit functions shall be developed by one or more of the following methods: (NQA-1-1989, Supplement 2S-3, Section 2.1)

- A. Orientation to provide a working knowledge and understanding of the QA program requirements and the auditing organization's implementing procedures used to perform audits and report audit results. (NQA-1-1989, Supplement 2S-3, Section 2.1 (a))
- B. Training programs that provide general and specialized training in audit performance, including fundamentals, objectives, characteristics, organization, performance, and results of quality auditing. Training shall include methods of examining, questioning, evaluating, and documenting specific audit items and methods of evaluating the effectiveness of corrective actions for conditions adverse to quality. (NQA-1-1989, Supplement 2S-3, Section 2.1 (b))
- C. On-the-job training, guidance, and counseling under the direct supervision of a lead auditor. Such training shall include audit planning, performing, reporting, and follow-up actions. (NQA-1-1989, Supplement 2S-3, Section 2.1 (c))

#### 3.2.2.5 Technical Specialist Qualification

Technical specialists selected for audit assignments shall receive indoctrination commensurate with the scope, complexity, or special nature of the work being audited. In addition, they shall be trained to the requirements of the audit process associated with their duties. (NQA-1-1989, Supplement 2S-3, Section 2.1)

### 3.2.2.6 Lead Auditor Qualification

A lead auditor shall be capable of organizing and directing audits, reporting audit results, and evaluating planned and implemented corrective action. A lead auditor also shall be certified as meeting the requirements provided in this section for education and experience, communication skills, training, audit participation, and the successful completion of a lead auditor examination. (NQA-1-1989, Supplement 2S-3, Section 3.1)

### A. Lead Auditor Education and Experience:

The prospective lead auditor shall have verifiable evidence that a minimum of 10 credits have been accumulated under the following scoring system: (NQA-1-1989, Nonmandatory Guidance Appendix 2A-3, Section 2)

### 1. Education (four credits maximum)

- An associate's degree from an accredited institution scores one credit. If the degree is in engineering, physical sciences, mathematics, or QA, it scores two credits. (NQA-1-1989, Nonmandatory Guidance Appendix 2A-3, Section 2.1)
- b. A bachelor's degree from an accredited institution scores two credits. If the degree is in engineering, physical sciences, mathematics, or QA, it scores three credits. In addition, score one more credit for a master's degree in engineering, physical sciences, business management, or QA from an accredited institution. (NQA-1-1989, Nonmandatory Guidance Appendix 2A-3, Section 2.1)

## 2. Experience (nine credits maximum)

- a. The prospective Lead Auditor shall have participated in a minimum of five (5) QA audits within a period of time not to exceed three years prior to the date of qualification, one audit of which shall be a nuclear quality assurance audit within the year prior to the lead auditor's qualification. In addition, technical experience in engineering, manufacturing, construction, operation, or maintenance: score one (1) credit for each full year with a maximum of five (5) credits for the aspects of experience identified in 3.2.2.6 A.2.[b]-[f]. (NQA-1-1989, Nonmandatory Guidance Appendix 2A-3, Section 2.2)
- b. If two years of this experience have been in the nuclear field, score one (1) additional credit; or (NQA-1-1989, Nonmandatory Guidance Appendix 2A-3, Section 2.2)
- c. If two years of this experience have been in QA, score two (2) additional credits; or (NQA-1-1989, Nonmandatory Guidance Appendix 2A-3, Section 2.2)
- d. If two years of this experience have been in auditing or assessment, score three (3) additional credits; or (NQA-1-1989, Nonmandatory Guidance Appendix 2A-3, Section 2.2)
- e. If two years of this experience have been in nuclear QA, score three (3) additional credits; or (NQA-1-1989, Nonmandatory Guidance Appendix 2A-3, Section 2.2)

- f. If two years of this experience have been in nuclear QA auditing, score four (4) additional credits. (NQA-1-1989, Nonmandatory Guidance Appendix 2A-3, Section 2.2)
- 3. Professional Competence (two credits maximum)

For certification of competency in engineering, science, or QA specialties, issued and approved by a state agency or national professional or technical society, score two credits. (NQA-1-1989, Nonmandatory Guidance Appendix 2A-3, Section 2.3)

4. Rights of Management (two credits maximum)

The Lead Auditor's employer may grant up to two (2) credits for other performance factors applicable to auditing which may not be explicitly called out in this section. Examples of these factors are leadership, sound judgement, maturity, analytical ability, tenacity, and past performance and quality assurance training courses. (NQA-1-1989, Nonmandatory Guidance Appendix 2A-3, Section 2.4)

#### B. Lead Auditor Communication Skills

The prospective Lead Auditor shall have the capability to communicate effectively both in writing and orally. These skills shall be attested to in writing by the Lead Auditor's employer. (NQA-1-1989, Supplement 2S-3, Section 3.1)

#### C. Lead Auditor Training

Prospective Lead Auditors shall have training to the extent necessary to ensure their competence in auditing. Training in the following areas shall be given based upon management evaluation of the particular needs of each prospective Lead Auditor: (NQA-1-1989, Supplement 2S-3, Section 3.2)

- 1. Knowledge and understanding of the participant organization's QA program and other program-related procedures, codes, standards, regulations, DOE orders, and regulatory guides, as applicable (NQA-1-1989, Supplement 2S-3, Section 3.2.1)
- 2. General structure of QA plans and implementation procedures as a whole (NQA-1-1989, Supplement 2S-3, Section 3.2.2)
- 3. Auditing techniques of examining, questioning, evaluating, and reporting, and methods of identifying, following up, and closing corrective actions (NQA-1-1989, Supplement 2S-3, Section 3.2.3)

- 4. Audit planning in functional areas of nuclear QA (NQA-1-1989, Supplement 2S-3, Section 3.2.4)
- 5. On-the job training to include applicable elements of the audit program (NQA-1-1989, Supplement 2S-3, Section 3.2.5)

#### D. Lead Auditor Examination

The prospective lead auditor shall pass an examination that evaluates his or her comprehension of, and ability to apply, the audit knowledge described in this section. The examination may be oral, written, practical, or any combination thereof. (NQA-1-1989, Supplement 2S-3, Section 3.4)

- 1. The development and administration of the examination for a lead auditor is the responsibility of the organization responsible for the auditing program. This organization shall: (NQA-1-1989, Supplement 2S-3, Section 3.4), (NQA-1-1989, Supplement 2S-3, Section 5.1)
  - Maintain the integrity of the examination through confidentiality of files and, where applicable, proctor examinations (NQA-1-1989, Supplement 2S-3, Section 5.2)
  - b. Develop and maintain objective evidence regarding the type and content of the examination (NQA-1-1989, Supplement 2S-3, Section 5.2)

#### E. Lead Auditor Certification

- 1. Lead auditors shall be certified by the organization responsible for the auditing program as being qualified to lead audits. This certification will document the: (NQA-1-1989, Supplement 2S-3, Section 6.2)
  - a. Name of the organization performing the certification (NQA-1-1989, Supplement 2S-3, Section 6.2 (a))
  - b. Name of the lead auditor (NQA-1-1989, Supplement 2S-3, Section 6.2 (b))
  - c. Date of certification or recertification (NQA-1-1989, Supplement 2S-3, Section 6.2 (c))
  - d. Basis of certification (such as education, experience, communication skills, and training) (NQA-1-1989, Supplement 2S-3, Section 6.2 (d))
  - e. Signature of the designated representative of the organization responsible for the certification (NQA-1-1989 Supplement 2S-3, Section 6.2 (a))

## F. Lead Auditor Proficiency Maintenance

- 1. Lead auditors shall maintain their proficiency through one or a combination of the following:
  - a. Regular and active participation in the audit process (NQA-1-1989, Supplement 2S-3, Section 4.1)
  - b. Review and study of codes, standards, QA implementation procedures, instructions, and other documents related to QA program auditing (NQA-1-1989, Supplement 2S-3, Section 4.1)
  - c. Participation in training programs (NQA-1-1989, Supplement 2S-3, Section 4.1)
  - d. Management of the auditing organization shall evaluate the proficiency of lead auditors annually. Based on the evaluation, management shall choose to extend the qualification, require retraining, or require requalification. Management evaluations shall be documented. (NQA-1-1989, Supplement 2S-3, Section 4.1)
- 2. Lead auditors who fail to maintain their proficiency for a two-year period shall require requalification to the requirements of this section of the QAPD. However, participation in only one nuclear audit is required. (NQA-1-1989, Supplement 2S-3, Section 4.2)

## 3.2.2.7 Performing Audits

- A. Audits shall be performed using the written procedures or checklists related to the activity being audited. (NQA-1-1989, Supplement Requirement 18S-1, Section 4)
- B. Elements that have been selected for audit shall be evaluated against specified requirements. Objective evidence shall be examined to the depth necessary to determine if those elements are being implemented effectively. (NQA-1-1989, Supplement Requirement 18S-1, Section 4)
- C. Audit results shall be documented by audit personnel and reported to and reviewed by management having responsibility for the area audited. Conditions requiring prompt corrective action shall be reported immediately to management of the audited organization. (NQA-1-1989, Supplement Requirement 18S-1, Section 4)
- D. Conditions adverse to quality shall be documented and corrected according to the requirements of section 1.3.3. (NQA-1-1989, Supplement Requirement 18S-1, Section 4)

## 3.2.2.8 Reporting Audit Results

- A. The audit report shall be prepared and signed by the audit team leader and issued to the management of the audited organization and any affected organizations. The audit report shall include the following, as appropriate: (NQA-1-1989, Supplement Requirement 18S-1, Section 5)
  - 1. A description of the audit scope (NQA-1-1989, Supplement Requirement 18S-1, Section 5 (a))
  - 2. Identification of the auditors (NQA-1-1989, Supplement Requirement 18S-1, Section 5 (b))
  - 3. Identification of persons contacted during the audit (NQA-1-1989, Supplement Requirement 18S-1, Section 5 (c))
  - 4. A summary of the documents reviewed, persons interviewed, and the specific results of the reviews and interviews (i.e., a summary of the checklist contents) (DOE G 414.1-1c, Section 4.7.6.1)
  - A summary of audit results, including a statement of the QA program adequacy, implementation, and effectiveness, as appropriate to the scope (NQA-1-1989, Supplement Requirement 18S-1, Section 5 (d))
  - 6. A description of each reported condition adverse to quality in sufficient detail to enable corrective action to be taken by the audited organization (NQA-1-1989, Supplement Requirement 18S-1, Section 5 (e))
  - 7. A description of commendable quality practices (DOE G 414.1-1c, Section 4.7.6.1)
- B. Additionally, common audit findings shall be grouped in the report whenever possible so that related or systematic breakdowns in the QA program are identified. Findings or deficiencies shall be categorized based on their relative importance to indicate their degree of impact on CRA, waste characterization and certification, repository performance assessment, waste isolation, waste transportation, nuclear and industrial safety, environmental protection, or management and operation of the WIPP facility. (DOE G 414.1-1c, Section 4.7.5)

### 3.2.2.9 Audit Response and Follow Up

Management of the audited organization will investigate conditions adverse to quality; determine and schedule corrective actions, including measures to preclude recurrence; and notify the auditing organization in writing of the actions planned or taken. The adequacy of audit responses shall be evaluated by or for the auditing organization. Follow-up action shall be taken to verify that corrective action is accomplished as scheduled. (NQA-1-1989, Supplement Requirement 18S-1, Section 6 and 7)

# 3.2.2.10 Audit Records

The following documents, when developed in fulfillment of the audit requirements of this QAPD, shall be controlled as QA records in accordance with section 1.5 of this QAPD: audit plans, audit reports, audit responses, and documentation of corrective action completion and follow-up. (NQA-1-1989, Supplement Requirement 18S-1, Section 8)

### **SECTION 4 – SAMPLE CONTROL REQUIREMENTS**

This section identifies the requirements for controlling samples of waste and environmental media. The control measures shall include provisions for the identification, handling, storage, shipping, archiving, and disposition of the samples, including those identified as nonconforming (NQA-3-1989, Section II, Basic Requirements, para. 8.1, Sample Management).

#### 4.1 SAMPLE CONTROL

- A. Samples shall be controlled and identified in a manner consistent with their intended use.
- B. Implementing procedures shall define responsibilities, including organizational interfaces, related to documenting and tracking sample possession from sample collection and identification through handling, preservation, shipment, transfer, analysis, storage, and final disposition.
- C. Sample control measures shall include provisions for the identification of the in-situ orientation of samples, where appropriate.
- D. A chain-of-custody record form shall be maintained. The chain-of-custody record shall provide a document trail of all persons who have custody of a given sample, including the date and time of its transfer.
- E. Sample control measures, including identification and documentation, shall ensure that samples can be traced at all times, from collection through final disposition.
- F. Where samples have a maximum life expectancy or expiration date, methods shall be employed that preclude the use of the sample beyond its specified life.
- G. Representative archival samples from difficult-to-repeat sample collection activities, such as principal bore holes, shall be maintained.
- H. Implementing procedures shall specify the representative samples to be archived if the need to archive samples is identified.

#### 4.2 SAMPLE IDENTIFICATION

- A. Each sample shall be uniquely identified from its initial collection through the final disposition of the sample.
- B. Sample identification shall be verified and documented before each transfer or release for testing, analysis, or disposition.

- C. Identification shall be maintained by placing the identification directly on the samples wherever possible or in a manner that ensures identification is maintained. If direct physical markings are either impractical or insufficient, other appropriate means shall be employed (e.g., physical separation, labels or tags attached to containers, or procedural control). When used, physical markings shall:
  - 1. Be applied using materials and methods that provide clear and legible identification
  - 2. Not affect the sample content or form
  - 3. Be transferable to each identified sample part when the sample is subdivided
  - 4. Not be obliterated or hidden by surface treatments or sample preparation unless other means of identification are substituted
- D. If sample storage is required, methods shall be established for the control of sample identification that are commensurate with the planned duration and storage conditions. As applicable, these methods shall provide for:
  - 1. The maintenance or replacement of markings and identification tags that have been damaged because of age or during handling
  - 2. The protection of identification markings from excessive deterioration due to environmental exposure

## 4.3 HANDLING, STORING, AND SHIPPING SAMPLES

- A. Handling, storing, cleaning, packaging, shipping, and preserving samples shall be conducted in accordance with the manufacturers' applicable requirements and established work and inspection implementing procedures. Controls shall provide for the maintenance of sample characteristics, sample integrity, and sample identification during storage.
- B. The controls shall be consistent with planned duration and storage conditions and shall describe actions to be taken where maximum sample life expectancy limits are identified.
- C. Storage methodology shall be developed and implemented to ensure that samples are maintained in predetermined environmental conditions commensurate with their intended use and purpose.
- D. Samples shall be controlled to preclude the mixing of like samples.
- E. Samples on which analysis or tests have been performed shall be identified and maintained in a separate part of the storage area.

- F. If required for critical, sensitive, perishable, or high-value samples, specific measures for the handling, storage, cleaning, packaging, shipping, and sample preservation shall be identified and used.
- G. Measures shall be established for sample marking and labeling for packaging, shipping, handling, and storage as necessary to adequately identify, maintain, and preserve the sample. Markings and labels shall indicate the need for and the presence of special environments or the need for other special controls, if necessary.
- H. Samples requiring special protective equipment (such as containers) and special protective environments (such as inert gas or limits on moisture and temperature) shall be specified, employed, verified, and documented.

#### 4.4 DISPOSITION OF NONCONFORMING SAMPLES

- A. Samples that do not conform to requirements specified in work controlling documents (such as job packages, travelers, or work requests) shall be identified, documented, evaluated, and segregated in accordance with section 1.3.
- B. The disposition for nonconforming samples shall be identified and documented and shall be limited to "use-as-is", "limited use", or "discard."
- C. Samples that have lost their identity labeling shall be documented as nonconforming and shall not be used.

## **SECTION 5 – SCIENTIFIC INVESTIGATION REQUIREMENTS**

Scientific investigations shall be defined, controlled, verified, and documented. Process variables affecting scientific investigations shall be measured and controlled. Test processes conducted in support of such investigations shall be controlled in accordance with the requirements of sections 1.1.2.4, Planning Work; 2.4, Inspection and Testing; 2.4.4, Test Requirements; and 2.4.5, Monitoring, Measuring, Testing, and Data Collection Equipment, as applicable, and as supplemented by the requirements of this section.

Scientific investigations are typically CBFO contracted or delegated activities. As such, the CBFO does not maintain implementing procedures beyond that of the peer review process (see MP 10.5, *Peer Review*). The contracted or external organization is required to prepare and implement procedures covering these requirements, as applicable.

## 5.1 PLANNING SCIENTIFIC INVESTIGATIONS (NQA-3-1989, Paragraph 2.1)

- A. Variables that affect interrelated scientific investigations shall be identified and controlled appropriately in each related investigation.
- B. The intended use of the data shall be documented before collection as part of the planning for data processing. Any alternate use of the data shall be evaluated for appropriateness and the justification for use shall be documented.
- C. Planning shall consider the compatibility of data processing with any conceptual or mathematical models used at each applicable stage.
- D. The technical adequacy of procedures or methods for conducting scientific investigations and their implementation shall be reviewed and approved by qualified persons other than those who prepared the procedures or methods. Changes to procedures or methods for conducting scientific investigations shall be reviewed and approved in a manner commensurate with the original procedure or method.
- E. Development activities used to establish new methods or procedures for conducting scientific investigations shall be documented. The results of developmental testing shall be reviewed for adequacy and approved by qualified persons prior to implementation of the procedures for data collection.
- F. Planning shall be coordinated with organizations providing input to or using the results of the investigation.
- G. Planning shall include the establishment of acceptance criteria for data quality evaluation to ensure that the data generated are valid and satisfy documented requirements for the following characteristics, as appropriate: data precision, data accuracy, data representativeness, data comparability, and data completeness.

H. Planning shall include the identification of known sources of error and uncertainty, as well as any input data that are suspect or whose quality is beyond the control of the performing organizations.

# 5.2 PERFORMING SCIENTIFIC INVESTIGATIONS (NQA-3-1989, Paragraphs 3.1, 4, and 11SW-1)

- A. Scientific investigations shall be performed in accordance with requirements documented in test plans, procedures, and scientific notebooks.
- B. If deviation from test standards or the establishment of specially prepared test procedures is deemed appropriate (e.g., no nationally recognized test standards exist), the modified or new test procedures shall be documented in sufficient detail to be repeatable and shall be justified, evaluated, and approved by the cognizant technical organization.
- C. Scientific notebooks shall contain, at a minimum:
  - 1. A statement of the objectives and description of work to be performed or reference to an approved plan that describes the work
  - The methods used
  - 3. Identification of the samples
  - Identification of the M&TE used
  - A description of the work performed and the results obtained, the names of individuals performing the work, and dated initials or signature, as appropriate, of individuals making the entries
  - 6. A description of changes made to methods used, as appropriate
  - 7. The potential sources of uncertainty and error in test plans, procedures, and parameters that must be controlled and measured to ensure that tests are valid
- D. Scientific results shall be periodically reviewed by an independent qualified individual to verify that there is sufficient detail to retrace the investigation and confirm the results, if feasible, or repeat the investigation and achieve comparable results without recourse to the original investigator.
- E. Practices, techniques, equipment, and manual or computerized methods used to obtain and analyze data shall be verified to ensure that they are technically sound and have been properly selected. Controls shall be established for these processes to ensure that they are properly implemented, including controls to prevent tampering.

- F. Data collection and analysis shall be controlled by procedures of sufficient detail to allow the processes to be repeated. Where appropriate, quality control checks shall be performed using recognized methods such as replicate, spike, and split samples; control charts; blanks; reagent checks; replication of the methods used to obtain the results; or alternate analysis methods.
- G. Test media (such as fluids), when used, shall be characterized and controlled in accordance with test procedures and storage and handling requirements per section 4.0, Sample Control.
- H. Scientific notebooks and technical implementation documents shall be maintained as QA records.

## 5.3 DATA DOCUMENTATION, CONTROL, AND VALIDATION

# 5.3.1 Data Identification and Usage (NQA-3-1989, Paragraph II-3.1, 3.2, 3.4, and 3SW-1 Paragraphs 4.1 thru 7)

- A. All data shall be recorded so that they are clearly identifiable and traceable to the test, experiment, study, or other source from which they were generated. Identification and traceability of the data shall be maintained for the lifetime of the WIPP.
- B. The method of data recording (e.g., scientific notebooks, log books, data sheets, or computerized instrumentation systems) shall be controlled to avoid data loss and permit data retrievability. Controls shall be established to ensure that data integrity and security are maintained wherever data are stored. Controls shall prescribe how specific types of data will be stored with respect to media, conditions, location, retention time, security, and access. Data shall be suitably protected from damage and destruction during their prescribed lifetime and shall be readily retrievable.
- C. Data transfer and reduction controls shall be established to ensure that data transfer is error free (or within a prescribed permissible error rate), that no information is lost in transfer, and that the input is completely recoverable. Data transfer and reduction will be controlled to permit independent reproducibility by another qualified individual. Examples of data transfer include copying raw data from a notebook into computerized data form, or copying from computer tape to disk.
- D. Data that are determined to be erroneous, rejected, superseded, or otherwise unsuited for their intended use shall be controlled to prevent their inadvertent use. Controls shall include the identification, segregation, and disposition of inadequate data. The basis for the disposition of erroneous data shall be justified and documented.
- E. All processes which change either the form of expression or quantity of data, values, or number of data items (data reduction) shall be controlled by prescribed methods that allow for the validation of the conversion process.

F. Data collection and analysis shall be critically reviewed and questions resolved before the results are either used or reported. Uncertainty limits shall be assigned to the data prior to their use.

### 5.3.2 Data Validation (NQA-3-1989, Paragraph II-4.1, 5, and 6)

Data validation is a systematic process used to review data to ensure that the required data quality characteristics have been obtained. Results of the review may require that qualifiers be placed on the use of the data.

- A. Validation methods shall be planned and documented. The documentation shall include the acceptance criteria used to determine if the data are valid.
- B. All applicable data collected shall be validated. Validation shall include the following:
  - 1. The relevant documentation is reviewed to evaluate the technical adequacy, the suitability for the intended use, and the adequacy of the QA record
  - 2. The results of the data review shall be documented
  - 3. The reviewer shall be independent of the collection activities
- C. Data validation shall be controlled to permit independent reproducibility by another qualified individual.
- D. Data considered as established fact by the scientific and engineering community, such as engineering handbook data or critical tables, do not require validation.

# 5.4 QUALIFICATION OF EXISTING DATA (NQA-3-1989, Supplement 3SW-1, Section 9)

- A. This section contains requirements unique to the post-qualification of data and information that are relied upon to support the WIPP CRA and were collected prior to the implementation of this QAPD. While the qualification process shall be conducted in accordance with the program control requirements of the CBFO QAPD, it is not intended that the QAPD identify the data that are subject to this process or the technical requirements of the qualification process. The qualification process shall be conducted in accordance with approved procedures that provide for documentation of the decision process, the factors used in arriving at the choice of the qualification method, and the decision that the data are qualified for their intended use.
- B. Existing data shall be qualified using one or a combination of the following methods:
  - 1. Determination that the data were collected under a QA program that is equivalent in effect to ASME NQA-1-1989 edition; ASME NQA-2a-1990 addenda, Part 2.7, Quality Assurance Requirements of Computer Software for Nuclear Facility

*Applications*, to ASME NQA-2-1989 edition; and NQA-3-1989. Factors to be considered include:

- a. Qualifications of personnel or organizations generating the data
- b. Technical adequacy of the equipment and procedures used to collect and analyze the data
- c. Environmental conditions under which the data were obtained (if germane)
- d. Quality and reliability of the measurement control program under which the data were generated
- e. Extent to which data demonstrate properties of interest (e.g., physical, chemical, geologic, geophysical, or mechanical)
- f. Extent to which conditions generating the data may partially meet requirements of this QAPD
- g. Prior uses of the data and the associated verification processes
- h. Prior peer or other professional reviews of data and their results
- i. Extent and reliability of the documentation associated with the data
- Extent and quality of corroborating data or confirmatory testing results
- k. Degree to which data generating processes were independently audited
- I. The importance of the data in showing that the repository design meets the performance objectives
- 2. The use of corroborating data, with the data relationships and inferences clearly identified and justified
- 3. Confirmatory testing that is performed and documented
- 4. Peer review conducted in a manner that is compatible with NUREG-1297, *Peer Review for High-Level Nuclear Waste Repositories* 
  - a. Peer reviews shall be performed when the adequacy of information or the suitability of procedures and methods essential to showing that a repository system meets or exceeds its performance requirements with respect to safety and waste isolation cannot otherwise be established through testing, alternate calculations, or reference to previously established standards and practices.

- b. Peer reviews performed in support of WIPP compliance activities shall be documented, as shall all peer review processes.
- 5. Peer reviews are used for the following activities:
  - a. Conceptual models and model calibration selected and developed by DOE.
  - b. Waste characterization analysis as required in 40 CFR 194.24(b), *Waste Characterization*.
  - c. Engineered barrier evaluation as required in 40 CFR 194.44, *Engineering Barriers*.

## **SECTION 6 – SOFTWARE REQUIREMENTS**

This section establishes software quality assurance (SQA) requirements for the CBFO participants who acquire, develop, control, verify, approve, maintain, or use computer software that is important to CRA and waste characterization. The CBFO does not typically develop or procure software but assigns that task to contractor or other implementing organizations. These organizations shall develop processes that follow the requirements outlined below.

CBFO's expectation is that WIPP QA participants utilize guidance from NQA-1-2008/2009, Part IV, Subpart 4.1, *Guide on Quality Assurance Requirements for Computer Software*, regarding firmware and programmable M&TE and the requirements of Attachment 4 of DOE O 414.1D.

The CBFO may develop or procure non-safety related administrative software. In these cases, it will utilize MP 5.16, *CBFO Software Quality Assurance of Non-Safety Software*, or as applicable develop a software specific software quality assurance plan that addresses the requirements listed below.

# 6.1 APPLICABILITY (DOE O 414.1D, Attachment 4; NQA-2-1989, Part 2.7, Paragraph 2.1)

- A. The requirements in this section apply to computer software and/or M&TE firmware used in the manipulation or production of data that are, in turn, used in the processing, gathering, or generation of information whose output is relied upon to make design, analytical, operational, or compliance-related decisions with respect to the performance of the waste confinement, waste characterization and certification, waste transportation, or waste acceptance processes in accordance with ASME NQA-2-1989 Part 2.7 as graded using the requirements in Section 1.1.2.3 of this document. The requirements also apply to safety software as defined in DOE O 414.1D and used by the CBFO and its program participants. The application of these requirements shall be prescribed in written plans, policies, procedures, or instructions.
- B. Software that is used solely for office administration functions such as word processing, financial accounting, human resources management and software that is determined to be outside of a Quality Assurance program is exempt from the requirements of this section of the QAPD. Software that is determined to be outside of a Quality Assurance program is software that is not applicable to 6.1A or 6.1C.
- C. General support software (e.g., software tools, administrative and management systems, system utilities, compilers, assemblers, translators, interpreters, query languages, word processing programs, database managers, and graphing programs) or other software that does not generate data shall meet the following requirements:

- 1. A listing of the support software (i.e., name, supplier, version, installed location, or macro reference) shall be developed and maintained.
- 2. Documentation shall be prepared to address the functions and/or settings of the support software that are implemented.

Specific applications supporting section 6.1A., written for use within general support software (e.g., detailed formulas, macros, operating parameter library files or program/equipment settings, equipment operating software/languages, system software) that can be verified by hand calculations or other means, shall meet the following requirements:

- 1. A listing of the software code (i.e., details of formulas, file/table/cell references, macros, operating parameters, and/or program/equipment settings) shall be developed and maintained.
- Documentation shall be prepared to demonstrate by hand or other independent calculations that the specific application provides the correct results for the specified range of input parameters.
- 6.2 BASIC REQUIREMENTS FOR INVENTORY, GRADING, AND CLASSIFICATION OF SOFTWARE (DOE O 414.1D, Attachment 4, Paragraph 2A.(2))
- A. An inventory of all applicable software shall be maintained that identifies the software description, software name, version, classification, exemption status, operating environment, the person and organization responsible for the software, and the grade level designation. The grade level designation shall be used to classify the significance of the software.
- B. Software governed by this section of the QAPD shall be classified. The criteria for classification shall address the purpose of the software relative to its use in engineering, scientific testing, data collection, design, analysis, and operations activities, as well as its importance to safety or its significance in managing information or augmenting mission-essential decisions. The classification shall consider the impact of the software output on intended usage (i.e., impact on design, impact on equipment operations, and impact on other intended usage of the software application). The graded approach analysis for categorization/classification of software items shall be documented.
- C. The assigned grading levels are defined as follows.

Level A: This grading level includes safety software applications that meet one or more of the following criteria.

1. Software failure that could compromise a limiting condition for operation.

- Software failure that could cause a reduction in the safety margin for a safety structure, system, or component (SSC) that is cited in DOE approved documented safety analysis.
- 3. Software failure that could cause a reduction in the safety margin for other systems such as toxic or chemical protection systems that are cited in either (a) a DOE approved documented safety analysis or (b) an approved hazard analysis per DOE P 450.1, *Environment, Safety, and Health Policy for the Department of Energy Complex*, and the DEAR ISMS clause.
- 4. Software failure that could result in nonconservative safety analysis, design, or misclassification of facilities or SSCs.

Level B: This grading level includes safety software applications that do not meet Level A criteria but meet one or more of the following criteria.

- 1. Safety management databases used to aid in decision making, whose failure could impact safety SSC operation.
- 2. Software failure that could result in incorrect analysis, design, monitoring, alarming, or recording of hazardous exposures to workers or the public.
- 3. Software failure that could compromise the defense in depth capability for the nuclear facility.

Level C: This grading level includes software applications that do not meet Level B criteria but meet one or more of the following criteria.

- 1. Software failure that could cause a potential violation of regulatory permitting requirements.
- Software failure that could affect environment, safety, health monitoring, or alarming systems.
- 3. Software failure that could affect the safe operation of an SSC.

Guidance is also provided in DOE G 414.1-4 Safety Software Guide for use with 10 CFR 830 Subpart A, Quality Assurance Requirements, and DOE O 414.1D, Quality Assurance, to assist in the development of appropriate implementing procedures.

#### 6.3 SOFTWARE QUALITY ASSURANCE

# 6.3.1 Basic Requirements for Software Quality Assurance (DOE O 414.1D, Attachment 4, Paragraph 2A.(4))

Controls governing applicable software development projects shall be identified in controlled and documented plans. The plans shall be formally reviewed and approved. Controls governing the configuration and use of the software shall be identified in plans or procedures appropriate to the organizations using the software. The following activities shall be addressed in plans or procedures:

- A. Software development
- B. Software verification and validation
- C. Software configuration control
- D. Software operation and maintenance

Plans may be issued separately or as a single, composite plan, depending on the nature and complexity of the project. The software control plans may be a section of the overall project plan, provided that each software item is addressed and the software control portion of the plan prescribes the documentation, reviews, and controls required by this section.

As appropriate, the software development and acquisition plan shall establish the need for standards, conventions, other required work practices, and the use of software tools to facilitate the software life cycle activities. Standards and conventions, and other required work practices shall be documented.

## 6.3.2 NQA-2 Part 2.7 Supplemental Requirements for Software Quality Assurance

SQA plans shall be prepared for each new software project at the start of the software life cycle. For acquired software, the SQA plan shall be prepared before the software enters the purchaser organization. Plans may be prepared individually for each software project, may exist as a generic document to be applied to software prepared within or procured by an organization, or may be incorporated into the overall QA program. The plan shall identify:

- A. The software products governed by the plan
- B. The types of documentation to be prepared, reviewed, and maintained during the software design, development, implementation, test, and use
- C. The organizations responsible for performing the work and achieving software quality, and their tasks and responsibilities

- D. The process for reporting and documenting software discrepancies, evaluating the impact of discrepancies on previous calculations, and determining the appropriate corrective action(s)
- E. The standards, conventions, techniques, or methodologies that guide the software development, as well as the methods used to ensure implementation of requirements
- F. The procedure(s) used for establishing and maintaining the integrity of data, embodied mathematical models, and output files

### 6.4 SOFTWARE PROCUREMENT (DOE O 414.1D, Attachment 4, Paragraph 2a)

#### 6.4.1 Basic Requirements for Software Procurement

This section of the QAPD identifies responsibilities of the sponsoring organization for acquired software upon receipt of the software.

The sponsoring organization shall determine and document the functional requirements, the scope of development activities, and the life cycle documentation required for the software. The executable software package defined in the procurement and required documentation shall be received by the sponsoring organization and evaluated prior to performance of acceptance testing. The requirements for procured commercial off-the-shelf software shall be completed using section 6.6.

All procured software governed by this section shall be tested in accordance with documented and approved test procedures using approved test-case specifications to ensure that the acquired software will perform satisfactorily in its operating environment. The installation tests (including the test procedures), the test case specifications, and the results of the installation tests shall be identified, documented, and maintained as records according to established procedures.

# 6.4.2 NQA-2 Part 2.7 Supplemental Requirements for Software Procurement (NQA-2-1989, Part 2.7, Section 10)

- A. The procurement of software and related services shall be performed in accordance with sections 2.3 and 6.6 of this QAPD as applicable.
- B. The organization providing software services shall have an SQA plan/program governing the scope of services to be provided. The purchaser shall review and approve the SQA plan/program of the organization providing software services prior to the start of software development or any other services.
- C. Once the software has been installed, but before its use, the sponsoring organization shall perform user acceptance to verify the functional capability of the software and the acceptability of the supplier's supporting documentation (e.g., the user manual, technical specifications, and the results of supplier testing).

- D. For software developed and supplied under contract, the supplier shall be required, pursuant to the terms of the contract, to report software errors and failures to the sponsoring organization. The sponsoring organization shall also report software errors to the supplier, pursuant to the terms of the contract, requiring the supplier to evaluate and make return responses to sponsor-reported errors. The length of the term for error reporting and response activities to be provided by the supplier shall be stated in the contract.
- E. The applicable requirements stated in a software procurement shall become the responsibility of the purchaser upon receipt of software.

# 6.5 SOFTWARE USED IN DESIGN ANALYSIS (DOE O 414.1D, Attachment 4, Paragraph 2.a(4)(f))

### 6.5.1 Basic Requirements for Software Used in Design Analysis

- A. The computer software used in design analysis shall show that it produces the correct solutions for the encoded mathematical model within the defined limits for each parameter employed in the design analysis.
- B. The encoded mathematical model shall be shown to produce a valid solution to the physical problem associated with the design analysis.

#### 6.6 SOFTWARE DEVELOPED UNDER OTHER QA PROGRAMS

## 6.6.1 Basic Requirements for Software Developed Under Other QA Programs

Software that has not been developed or approved in accordance with this QAPD (e.g., freeware, shareware, procured commercial off-the-shelf, or otherwise acquired or procured software) shall be evaluated to determine its adequacy to perform intended functions. The evaluation shall be documented. The intended use of the software shall be described in detail and documented. The software shall be uniquely identified and controlled prior to the evaluation, clearly traceable to the software requirements, accepted by the sponsoring organization, and placed under configuration control prior to use.

CGD of software shall be performed in accordance with section 2.3.11 of this QAPD. Identification of a software item for CGD and determination of bounding conditions and critical characteristics shall include an evaluation performed by engineering, software, facility design, safety, and operations departments and other departments as necessary based on the scope of the commercial grade evaluation.

# 6.6.2 Supplemental Requirements for Software Developed Under Other QA Programs (NQA-2-1989, Part 2.7, Section 10.2)

The evaluation of existing software developed in accordance with other QA programs shall address the following:

- A. The evaluation shall include a determination of the adequacy of existing V&V activities and software documentation to support operations and maintenance.
- B. The evaluation shall identify the activities to be performed and the documentation necessary to accept the software for its intended use and placement under configuration control. The evaluation shall be documented and shall contain, at a minimum:
  - 1. A determination of the capabilities and limitation for the intended use of the software
  - 2. User application requirements (instruction for use of the software within the limits of the capabilities as addressed in the evaluation)
  - Test plans and test cases required to demonstrate the capabilities within evaluated limitations and to validate the acceptability of the software for the intended use
  - 4. User documentation as described in section 6.10.2.6
- C. As an alternative, the sponsoring organization shall obtain the documentation noted above from the supplier or shall perform a documented review of the documentation at the supplier facility to determine acceptability. The review shall be performed in accordance with requirements stated directly above.
- D. All revisions of software developed under other QA programs shall be reviewed in accordance with section 6.6.2, unless the software meets the criteria of 6.1 B.

# 6.7 SOFTWARE DEVELOPMENT AND LIFE CYCLE (DOE O 414.1D, Attachment 4, Paragraphs 2.a(4)(c, e, and f))

#### 6.7.1 Basic Requirements for Software Development and Life Cycle

The developmental activities of software projects subject to this QAPD shall be identified in documented and approved plans to ensure that the project proceeds in an orderly and traceable manner. SQA plans for developed software applications shall be generated in accordance with section 6.3.2 of this QAPD. Sufficient information shall be provided to clearly indicate the necessary tasks, the deliverables and baselines for each phase, the required reviews, appropriate milestones, and the responsibilities associated with each task.

Software project development plans shall identify the items that need to be baselined and the methods to be used for controlling the configuration of those baselines throughout the development process. Configuration control planning for software is addressed in section 6.9 of this QAPD.

### 6.7.2 NQA-2 Part 2.7 Supplemental Requirements for Software Development and Life Cycle (NQA-2-1989, Part 2.7, Section 3)

- A. The activities associated with the evolution of the software shall be accomplished using an iterative or sequential approach. The approach shall include the analysis of the problem under study, the transformation of the analysis into the design, the implementation of the design into validated computer software, and the development of sufficient documentation to demonstrate that the specified requirements have been successfully included in the computer software.
- B. The iterative or sequential approach to software development consists of phases, with each phase leading to the development of a specific work product representing components of the software baseline. The software phases are:
  - 1. Definition of requirements
  - 2. Design
  - 3. Implementation
  - 4. Testing
  - Installation and checkout
  - 6. Operations and maintenance
  - 7. Retirement
- C. Following the development of the SQA plan, no strict sequence of performing activities is required (i.e., activities may be performed serially or concurrently) provided that all the specified requirements for each software development phase have been met.

#### **6.7.2.1** Requirements Phase (NQA-2-1989, Part 2.7, Section 3.1)

Software requirements shall be specified, documented, reviewed, and approved. These requirements shall pertain to functionality, performance, design constraints, data attributes, security vulnerabilities, cyber security requirements, response of the software to anticipated classes of input data, and external interfaces (e.g., hardware limitations) as outlined in section 6.10.2.2. Each requirement shall be specified in sufficient detail to permit the accomplishment of design and validation activities. Software requirements shall be traceable throughout the software development cycle, and a V&V plan shall be prepared after the software requirements have been documented and approved.

A review of software requirements shall be performed upon completion of the software requirement documentation. This review shall assure that the requirements are complete, verifiable, consistent, and technically feasible. The review shall also assure that the requirements will result in feasible and usable implementation of code.

#### 6.7.2.2 Design Phase (NQA-2-1989, Part 2.7, Section 3.2)

The software design shall be based on the software requirements and shall be documented and reviewed. An integral part of the software design is the consideration of the computer program's operating environment. The design shall specify the overall structure (control and data flow) and the reduction of the overall structure into physical solutions (algorithms, equations, control logic, and data structures). The design may necessitate the modification of the requirements documentation and the V&V plans.

A software design review shall be held at the completion of the software design documentation. This review shall assure that the software design is traceable to software design requirements and that the software design is complete, verifiable, consistent, and technically feasible. The review shall also assure that the requirements will result in feasible and usable code.

#### 6.7.2.3 Implementation Phase (NQA-2-1989, Part 2.7, Section 3.3)

The software design shall be translated into a form (programming language) suitable for processing by a computer. The executable software shall be analyzed to identify and correct errors. The implementation process shall result in software products such as computer program listings and instructions for computer use (e.g., user's manual).

#### 6.7.2.4 Testing Phase (NQA-2-1989, Part 2.7, Section 3.4)

- A. Test requirements, test acceptance criteria, and test methods shall be specified and documented by the organization responsible for the design, or provided to the design organization for approval. The test requirements and acceptance criteria shall be reviewed and based upon applicable design or other pertinent technical bases. If the test requirements and acceptance criteria are not prepared by the organization responsible for the design, the design organization shall review and approve the test requirements and acceptance criteria. Appropriate tests, such as verification tests, requirements-driven tests, hardware integration tests, and in-use tests, shall be controlled. Software testing, using documented test plans, test cases, and test results are the primary methods of software validation.
- B. Test procedures or plans shall specify the following, as applicable:
  - 1. Required tests and test sequence
  - Required ranges of input parameters
  - Identification of the stages at which testing is required
  - 4. Criteria for establishing test cases
  - 5. Requirement for testing logic branches
  - 6. Requirements for hardware integration

- 7. Anticipated output values
- Acceptance criteria
- 9. Reports, records, standard formatting, and conventions
- C. Testing of software shall be performed to the extent that unintended functions are identified and reviewed and their impact determined and corrected. If appropriate, determine if modifications are needed to the requirements, design, implementation, or test plans and test cases.
- D. Design-driven tests shall be used to demonstrate the capability of the software to produce valid results for test problems encompassing the range of intended use as defined by the software documentation. Testing of software used for operational control shall demonstrate the required performance over the entire range of the controlled function or process. Acceptable test methods consist of:
  - 1. Hand calculations
  - 2. Calculations using comparable proven problems
  - 3. Empirical data and information from confirmed published data and correlations or technical literature
  - 4. Comparison with other validated software of similar purpose
  - 5. Manual inspections or qualitative checks not involving numerical manipulation (examples include visual inspection of database reformatting or data plotting)
- E. Requirements-driven tests to verify conformance of an item or computer program to specified requirements and to demonstrate satisfactory performance for service shall be planned and executed. These shall be used to validate software by comparing test results of software execution with objective evidence obtained by the above methods. The results of this evaluation shall be of sufficient scope and depth to prove the capabilities and limitations delineated in the software documentation.
- F. Test records shall identify each of the following:
  - 1. Computer program tested
  - Computer hardware used
  - 3. Test equipment and calibrations, where applicable
  - 4. Date of test
  - 5. Tester or data recorder
  - 6. Simulation models used, where applicable

- 7. Test problems
- 8. Results and acceptability
- 9. Action taken in connection with any deviations noted
- 10. Persons evaluating test results
- G. Acceptance test cases and procedures shall be generated to provide details for the acceptance of a completed software application and placement of the application under configuration management. Test cases and procedures shall be revised to address changes in requirements, design, and implementation aspects of the applicable software application.
- H. A review and evaluation of verification of test results shall be performed by the responsible acceptance authority to assure that the test requirements have been satisfied.

#### 6.7.2.5 Installation and Checkout Phase (NQA-2-1989, Part 2.7, Section 3.5)

- A. During installation and checkout, the software becomes part of a system consisting of applicable software components, hardware, and data. The process of integrating the software with other applicable components may consist of installing both the hardware and software, converting or creating databases, and verifying that all components of the system have been included in the installation. Test problems shall be developed and documented to permit confirmation of the acceptable performance of the software in its operating environment. Installation and checkout of software shall consist of:
  - 1. Execution of tests for installation and integration
  - 2. Documented acceptance of the software for operational use
  - 3. Placement of the software under configuration control prior to use
- B. Completion of the installation and checkout activities establishes the software baseline.

#### 6.7.2.6 Operations and Maintenance Phase (NQA-2-1989, Part 2.7, Section 3.6)

A. Operation of the software is conducted by the user in accordance with the operation and usage instructions described in the software user documentation. Once the software has been made available for use, the software requirements and the design integrity shall be maintained. Maintenance activities shall be performed and documented in a traceable, planned, and orderly manner.

B. In all cases, V&V of software shall be completed and approved and corrective actions performed, as necessary, prior to relying upon the software to perform its intended function.

#### 1. Post Installation Maintenance

Software shall be maintained to remove latent errors (corrective maintenance), to respond to new or revised requirements (perfective maintenance), or to adapt the software to changes in the operating environment (adaptive maintenance). Software modifications shall be approved by authorized personnel, documented, verified, validated, and controlled.

Test problems shall be run whenever the software is installed on a different computer or when significant hardware or system software configuration changes are made. These tests shall be documented, performed by an individual technically competent in the subject area(s), and serve as the basis for determining if the software still meets specified requirements.

#### 2. In-Use Tests

In-use test procedures shall be developed and documented to permit confirmation of acceptable performance of the computer program in the operating system, after computer hardware changes, or when there are significant changes in the operating system. In-use test procedures shall be performed after computer hardware changes, or when there are significant changes in the operating system.

Periodic in-use manuals or automatic self-check routines shall be prescribed and performed for software applications and equipment where computer program errors, data errors, computer failure, or electronic or instrument drift can affect required performance.

#### 6.7.2.7 Retirement Phase (NQA-2-1989, Part 2.7, Section 3.7)

Criteria shall be developed to determine when software can be retired from use. Methods shall be developed to prevent the use of software that is no longer controlled. Upon retirement, user support for a software product is terminated.

# 6.8 SOFTWARE VERIFICATION AND VALIDATION (DOE O 414.1D, Attachment 4, Paragraph 2.a(4)(h))

#### 6.8.1 Basic Requirements for Verification and Validation

- A. Verification and validation of software shall include the review of software activities, documentation, and tests to ensure that the software:
  - 1. Adequately and correctly performs all intended functions

- 2. Does not perform any unintended function that either by itself, or in combination with other functions, can degrade the intended outcomes of the software
- B. Verification and validation shall be performed by any competent individual(s) or group(s) other than those who performed the software design. The individuals may be from the same organization and may include the designer's supervisor, provided the supervisor:
  - 1. Did not specify a singular design approach
  - 2. Did not rule out certain design considerations
  - 3. Did not establish the design inputs used
  - 4. Is the only individual in the organization competent to perform the verification or validation

#### 6.8.2 NQA-2 Part 2.7 Supplemental Requirements for Verification and Validation

#### 6.8.2.1 Verification (NQA-2-1989, Part 2.7, Section 7)

Verification is a formal checking activity performed throughout the evolution of the software life cycle. Verification methods shall include any one or a combination of design reviews, alternate calculations, and tests performed during the software life cycle phases. Verification activities, including development and updating of test plans and test cases shall be integrated into each phase of the software life cycle. Verification activities shall be clearly documented, including the identification of those performing and approving the verification. Software verification shall be performed during the software development to ensure that the products of a given life-cycle phase fulfill the requirements of the previous phase or phases following the SQA plan developed in accordance with 6.3.2 of this QAPD. Software verification reviews do not follow a strict sequence of verification activities (i.e., activities many be performed serially or concurrently) provided that the specified requirements for each software development phase have been met. Verification reviews shall be performed and documented and shall identify the participants and their specific responsibilities during the review and in the preparation and distribution of the review documentation. The reviewed documents shall be updated and placed under configuration control. Documentation of review comments and their disposition shall be retained. Unincorporated comments and their disposition shall also be retained in accordance with established procedures.

#### 6.8.2.2 Requirements

Verification review(s) of software requirements shall ensure that the requirements are complete, verifiable through testing, consistent, and technically feasible as described in section 6.7.2.1.

#### 6.8.2.3 Design

Verification review of software design shall evaluate the technical adequacy of the design approach and ensure that all the requirements have been addressed and that the design is complete, verifiable (through testing, using approved test plans and test cases), consistent, technically feasible, and traceable to the software requirements as described in section 6.7.2.2.

#### 6.8.2.4 Implementation

Verification of the implementation of software design shall consist of the examination of software logic and source code to ensure adherence to standards and conventions and to ensure that the design has been implemented as described in section 6.7.2.3.

#### 6.8.2.5 **Testing**

Verification of software testing shall consist of reviews to ensure that the specified test criteria, the expected results, and the software development documentation have been met as described in section 6.7.2.4. Individuals familiar with the software design detail and the intended use of the computer program shall be included in the review.

#### 6.8.2.6 Installation and Checkout

Verification of installation and checkout activities consists of reviews to ensure that the software baseline has been established, including the completion of software validation testing.

#### 6.8.3 Validation (NQA-2-1989, Part 2.7, Section 4)

- A. Prior to software validation, a review shall consider the appropriate requirements in sections 6.6 and 6.6.2 for ensuring the computer program is ready for software validation testing.
- B. Software validation is primarily a formal testing activity that shall be performed prior to installation and checkout. It shall be used to demonstrate that the computational model embodied in the software is an acceptable representation of the process or system for which it is intended and that the software produces correct solutions within defined limits for each parameter employed.
- C. Software validation activities, including development and updating of test plans and test cases, shall be integrated into each phase of the software life cycle.
- D. Required tests shall be controlled under appropriate environmental conditions using tools and equipment necessary to conduct the test in a manner to fulfill test requirements and acceptance criteria. The tests performed shall obtain the necessary data with sufficient accuracy for evaluation and acceptance. If temporary

- changes to the approved configuration of a facility are required for testing purposes, approval from the design authority is required prior to performing the test.
- E. Validation methods, test data, software-generated results, and conclusions shall be documented in a form that can be understood by an independent individual technically competent to use the software for the particular problem under study. Observations of unexpected or unintended results shall be documented and dispositioned prior to test results approval. The documentation shall be reviewed and approved to assure the test requirements have been satisfied.
- F. When the adequacy of the conceptual, mathematical, or computational models or the suitability of procedures and methods cannot be established through testing, alternate calculations, or reference to previously established standards and practices, a documented peer review shall be performed to meet the software validation requirements.
- G. The validation of software modifications shall be subject to selective regression testing to:
  - Detect errors introduced during the modification of the systems or system components
  - 2. Verify that the modifications have not caused unintended adverse effects
  - 3. Verify that the modified systems or system components still meet specified requirements

# 6.9 SOFTWARE CONFIGURATION MANAGEMENT (DOE O 414.1D, Attachment 4, Paragraph 2.a(4)(c))

#### 6.9.1 Basic Requirements for Software Configuration Management

- A. Implementation of baseline and change control processes is fundamental to configuration management. A baseline is a collection of all approved components of the software development cycle. As each component is approved, it is added to the overall software baseline. A software baseline serves as the basis for further development and maintenance that can be changed only through the use of formal change control procedures. Change control is the process by which a change to a baseline is proposed, evaluated, and approved or rejected.
- B. Software configuration controls shall be planned, including the identification of organizational positions that are authorized to make changes and specification of the methods, procedures, and instructions to be used to control the identification of, access to, changes to, and the status of computer software. Configuration control documents shall indicate how changes will be validated, including regression testing, and how the tests will be documented. These control documents shall be formally reviewed, approved, and in place before the software is released for use.

- C. A configuration baseline shall be defined at the completion of each major phase of the software development.
- D. Configuration items shall be maintained under configuration management until the software is retired.

### 6.9.2 NQA-2 Part 2.7 Supplemental Requirements for Software Configuration Management (NQA-2-1989, Part 2.7, Section 5)

#### 6.9.2.1 Configuration Identification

Software shall be placed under configuration control as each configuration item is approved. Software shall be evaluated to identify individual configuration items. Configuration items to be controlled shall include, as appropriate, documentation (e.g., software design requirements, instructions for computer program use, test plans and results); computer program(s) (e.g., source, object, backup files); and support software. A software baseline shall define the most recent approved software configuration. The configuration items and their associated documentation shall be traceable to one another and to the baseline. A labeling system for configuration items shall be implemented that:

- A. Uniquely identifies each configuration item
- B. Identifies changes to configuration items by revision or version identifier
- C. Provides the ability to uniquely identify each approved configuration of the revised software that is available for use

#### 6.9.2.2 Configuration Change Control

- A. Changes to configuration items shall be systematically proposed, evaluated, documented, and approved to ensure that the impact and rationale for making the change is carefully assessed prior to updating the software baseline. Changes to configuration items shall be controlled until they are incorporated into the approved baseline. Changes to previously accepted software shall be subject to the same level of control as the original software. Where changes to previously verified computer programs are made, verification shall be required for the change.
- B. Information concerning approved changes shall be transmitted to all affected organizations. All changes shall be formally evaluated and approved by the organization responsible for the original design, unless an alternate organization has been given the authority to approve the changes. Only authorized changes shall be made to software baselines. Software verification activities shall be performed for the change as necessary to ensure that the change is appropriately reflected in the software documentation and to ensure that traceability is maintained. The degree of software validation shall be commensurate with the nature and scope of the change.

#### 6.9.2.3 Configuration Status Accounting

Information shall be maintained that reflects the current status of the software baseline. This includes the identity and version of the approved configuration and the status of any proposed and approved changes to the baseline components. Configuration status accounting shall include a process for maintaining the status of changes which are proposed and approved, but not implemented. This information shall be available to all designated users of the software upon request.

#### 6.10 DOCUMENTATION (DOE O 414.1D, Attachment 4, Paragraph 2a.(2))

#### 6.10.1 Basic Requirements for Documentation

Software shall be described in one or more documents that detail user instructions, technical bases, functional requirements, and maintenance-related information sufficient to allow independent verification and maintenance and to provide traceability of the documentation to the software. The documentation shall be reviewed by an individual competent in the technical subject area for which the use of the software is intended. The review shall verify that the documentation adequately and accurately reflects the software that constitutes the system, and is sufficient to objectively demonstrate that the software requirements have been successfully implemented. Appropriate documentation shall be made available to all designated users of the software. Changes to procurement, requirement, design, implementation, V&V, and user documents shall be subject to configuration management and shall be performed in accordance with document change requirements of this QAPD. Record copies of software documentation shall be retained with other project records as required by file plan, codes, standards, specifications, plans, or procedures.

### 6.10.2 NQA-2 Part 2.7 Supplemental Requirements for Documentation (NQA-2-1989, Part 2.7, Section 6)

#### 6.10.2.1 Procurement Documentation (NQA-2-1989, Part 2.7, Section 10)

The applicable quality assurance requirements shall be specified and the required vendor-supplied software documentation, plans, and procedures shall be identified in the software procurement documentation.

#### 6.10.2.2 Requirements Documentation

- A. Software requirements documentation shall outline the requirements that the proposed software must satisfy. The software requirements shall, as applicable, address the following:
  - 1. Functionality the functions the software performs
  - 2. Performance the time-related issues of software operation such as speed, recovery time, and response time

- 3. Constraints limits imposed on implementation activities; any elements that will restrict design options
- 4. Attributes non-time-related issues of software operation such as portability, acceptance criteria, access control, and maintainability
- 5. External interfaces interactions with people, hardware, and other software
- B. Software requirements shall be traceable throughout the software development cycle.

#### 6.10.2.3 Design and Implementation Documentation

Software design and implementation documentation shall consist of a document or series of documents that:

- Describe the major components of the software design as they relate to the software requirements
- 2. Describe the theoretical basis, embodied mathematical model, control flow, control logic, and data structure(s) of the software
- 3. Describe the allowable or prescribed ranges for inputs and outputs
- 4. Describe the design in a manner that can be translated into executable code

#### 6.10.2.4 Verification and Validation Documentation

- A. Software V&V documentation shall consist of associated plans and shall describe the activities (including the results of reviews and tests) and the criteria for accomplishing the verification of the software throughout the software evolution process. The documentation shall also specify the hardware and software configurations pertinent to the software V&V.
- B. Software V&V documentation shall be organized in a manner that allows traceability from the software requirements to both the software design and to the validated capabilities of the software.

#### 6.10.2.5 Change Documentation

Changes to software shall be formally documented. This documentation shall contain a description of the change, the rationale for the change, and the identification of affected configuration items of the software baseline.

#### 6.10.2.6 User Documentation

User documentation shall be sufficient to allow any qualified user (i.e., one having adequate technical background) to install and run the software and properly respond to errors. User documentation, at a minimum, shall include:

- A. The software name and version identifier
- B. Statements of functional requirements and system limitations, including hardware
- C. An explanation of the mathematical models and derivation of the numerical methods used in the software design (physical and mathematical assumptions on which the software is based shall be included, along with an explanation of the capabilities and limitations inherent in the software)
- D. Instructions that describe user interaction with the software, user messages initiated as a result of improper input and how the user can respond, the identification and description of input and output specifications and formats, and input parameters
- E. A description of any required training necessary to use the software

#### 6.10.2.7 Error Documentation

Documentation of errors detected during the use of the software following installation and checkout shall be maintained. This documentation can be used for process improvement and to prevent recurrence of errors during the development and maintenance of other software. This documentation shall contain the identity of the software, the classification of the error in terms of its significance to the integrity of the software output, and the corrective action(s).

# 6.11 PROBLEM REPORTING AND CORRECTIVE ACTION (DOE O 414.1D, Attachment 4, Paragraph 2.a(4)(i))

#### 6.11.1 Basic Requirements for Problem Reporting and Corrective Action

Problems (e.g., errors, faults, failures) detected in released software shall be promptly reported and documented in accordance with documented procedures. When problems are detected in a software item, work previously performed using versions of the software that contain that problem shall be evaluated to determine the impact on the completed work. The evaluations shall be documented and retained in accordance with records requirements.

# 6.11.2 NQA-2 Part 2.7 Supplemental Requirements for Problem Reporting and Corrective Action (NQA 2-1989, Part 2.7, Section 8)

A. A system shall be established and maintained to record, classify, analyze, track, and report software problems (in released versions) and the associated corrective

- actions. Problems shall be promptly reported to any affected organizations and the resolution shall be formally processed.
- B. When problems are discovered in software or software results, the sponsoring organization shall determine the effect on previous uses and the need for corrective action based on sufficient information obtained from the affected users. Corrective action shall ensure that:
  - 1. Problems are identified, evaluated, documented and, if required, corrected
  - 2. Problems are assessed for their impact on past and present uses of the software
  - 3. Changes to software are in accordance with the software configuration management requirements of this section of the QAPD
  - Results are provided to the affected users, along with any revised software documentation
- C. Problems that could significantly affect decisions based upon prior use or that require significant modification to the software shall be identifiable to all users. Errors that have been determined to represent a condition adverse to quality shall be controlled in accordance with section 1.3 of this QAPD.

#### 6.12 ACCESS CONTROL (NQA-2-1989, Part 2.7, Section 9)

To the extent appropriate, controls shall be established to permit authorized and prevent unauthorized access to software that has been accepted in accordance with this section.

#### 6.13 SUPPORT SOFTWARE (DOE O 414.1D, Attachment 4, Paragraph 1.b)

Support software includes software tools and system software.

#### 6.13.1 Software Tools

- A. Software tools shall be evaluated, reviewed, tested, and accepted for use, and placed under configuration management as part of the software development cycle of a new or revised software product. Software tools that do not affect the performance of the software need not be placed under configuration management.
- B. In cases involving modifications of software products using the software tools, the configuration of the support software associated with that modification shall be managed. Changes to the software tool shall be evaluated for impact on the software product to determine the level of reviews and retesting that will be required.

#### 6.13.2 System Software

- A. System software consists of the on-line computer programs used to provide basic or general functionality and facilitate the operation and maintenance of the application computer program. Examples of such software include operating systems, administrative and management systems, system utilities, compilers, assemblers, translators, interpreters, automated protocols, utilities and tools, teleprocessing managers, and query languages.
- B. System software shall be evaluated, reviewed, tested, and accepted for use as part of the software development cycle of a new or revised software product. The testing shall consist of verification and documentation that the new or revised software product will function as intended on the system software. System software shall be placed under configuration change control as part of the software development of a new or revised software product. Changes to the system software shall be evaluated for impact on the software product to determine the level of reviews and retesting that will be required. Changes to system software that impact the baseline configuration shall be tested and documented on the new configuration.

#### APPENDIX A – GLOSSARY

**Acceptance:** The documented determination by the receiving organization that a work project, item, service, or software is suitable for the intended purpose.

**Acquired Software:** Computer software obtained that was not developed by the user organization.

**Alternative Calculations:** Calculations that are made with alternative methods to verify correctness of the original calculation.

**Approval:** The documented determination by a responsible individual that a work product, item, service, document and software is suitable for the intended purpose and shall be used as required.

**Assessment:** The act of reviewing, inspecting, testing, checking, conducting surveillances, auditing, or otherwise determining and documenting whether items, processes, or services meet specified requirements. Assessments are performed by or for management.

**Audit:** A planned and documented independent assessment to determine by investigation, examination, or evaluation of objective evidence the adequacy of and compliance with established procedures, instructions, drawings, and other applicable documents, and the effectiveness of implementation. An audit shall not be confused with surveillance or inspection activities performed for the sole purpose of process control or product acceptance.

Auditor: An individual who is qualified to perform assigned portions of an audit.

**Audit Team Leader:** A lead auditor who is assigned to direct the efforts of an audit (or assessment) team.

**Authenticate:** To establish as genuine or valid by stamping, initialing, or signing and dating by authorized personnel, or certification by individuals with knowledge of the related facts, whether by direct personal knowledge or through the direct reports of others.

**Calibration:** The set of operations which establish, under specified conditions, the relationship between values indicated by a measuring instrument or measuring system, and the corresponding standard or known values derived from the standard.

**Causal Analysis:** Identification of the direct and/or contributing cause(s), which led to a CAQ based on the results of investigative action(s)

**Certificate of Compliance:** Certificate issued by the Nuclear Regulatory Commission which approves the design of a package for the transportation of radioactive material.

**Certificate of Conformance:** A document signed or otherwise authenticated by an authorized individual certifying the degree to which items or services meet specified requirements.

**Certification:** The act of determining, verifying, and attesting to, in writing the qualifications of personnel, processes, procedures, or items in accordance with specified requirements.

**Characteristic:** A property or attribute of an item, process, or service that is distinct, describable, and measurable.

**Commercial Grade Item:** An item that is (1) not subject to design or specification criteria unique to a CBFO program or facility, (2) used in applications other than the nuclear industry, and (3) ordered from the manufacturer or supplier on the basis of specifications set forth in the manufacturer's published product description.

**Compliance Certification Application:** The compliance certification application submitted to the U.S. Environmental Protection Agency (EPA) pursuant to section 8 (d) (1) of the WIPP Land Withdrawal Act of 1992 (Pub. L. 102-579, 106 Stat. 4777) or any CRAs submitted to the EPA pursuant to section 8(f) of the WIPP Land Withdrawal Act.

**Condition Adverse to Quality (CAQ):** An all-inclusive term used in reference to any of the following: findings, failures, malfunctions, deficiencies, defective items, nonconformances, and technical inadequacies. A condition adverse to quality is considered significant when

- if uncorrected, the condition adverse to quality could have a serious effect on safety, operability, waste isolation, TRU waste site certification, regulatory compliance demonstration, or effective implementation of the QA program
- the condition adverse to quality requires immediate notification of regulatory entities (e.g., 10 CFR Part 21, HWFP Parts 1.7.10 through 1.7.13)
- the condition adverse to quality indicates a significant failure or breakdown in the implementation of QA Program requirements
- evidence indicating that previous corrective actions for the same/similar condition adverse to quality have been ineffective in precluding recurrence
- the condition adverse to quality is identified in items or activities important to safety or waste isolation and compromises the ability to prevent or mitigate the consequences of an accident, thereby presenting a significant hazard to safety and health of workers and/or the public
- Any CAQ that meets the definition of DOE O 460.1D, Paragraph 5.c.(10) shall be processed as an SCAQ with a 30-day reporting to the DOE CO.

**Configuration Control:** The process of identifying and defining the configuration items in a system, controlling the release and change of these items throughout the system

life cycle, and the recording and reporting of the status of configuration items and change requests.

**Configuration Item:** A collection of hardware or software elements treated as a unit for the purpose of configuration control.

**Controlled Document:** A document that is prepared, reviewed, approved, and distributed in accordance with established implementation procedures. Controlled documents are subject to controlled distribution and to a defined and controlled change process.

**Corrective Action:** A measure that is taken to rectify a condition adverse to quality and, where necessary, to preclude recurrence.

Corrective Action Report (CAR): A document used to identify and rectify conditions adverse to quality (CAQ), and track the associated corrective actions. CARs address CAQs that are primarily programmatic in nature, as opposed to nonconformance reports (NCRs) which address CAQs relating to a specific item(s) such as a piece of hardware or data. The category of CARs includes: corrective action reports or corrective action requests, nonconformance corrective action reports (NCARs), management corrective action reports (MCARs), deficiency reports (DRs), process deficiency reports (PDRs), audit findings, condition adverse to quality reports (CAQR), etc.

**Corrected During the Audit (CDA):** Isolated deficiencies that do not require a causal analysis or actions to preclude recurrence. Correction of the deficiency can be verified prior to the end of the audit. Examples include one or two minor changes required to correct a procedure (isolated), one or two forms not signed or not dated (isolated), and one or two individuals that have not completed a reading assignment.

**Data Accuracy:** The degree to which data agree with an accepted reference or true value. Accuracy is a measure of the bias in a system.

**Data Comparability:** A measure of the confidence with which one data set can be compared to another.

**Data Completeness:** A measure of the amount of valid data obtained compared to the amount that was planned.

**Data Precision:** A measure of the mutual agreement between comparable data gathered or developed under similar conditions, usually expressed in terms of a standard deviation.

**Data Representativeness:** The degree to which data accurately and precisely represent a characteristic of a population, a parameter, variations at a sampling point, or environmental conditions.

**Data Quality Objectives (DQOs):** Qualitative and quantitative statements derived from outputs of the first six steps of the DQO process (see below). DQOs 1) clarify the study objective, 2) define the most appropriate type of data to collect, 3) determine the most appropriate conditions from which to collect the data, and 4) specify tolerable limits on decision errors which will be used as the basis for establishing the quantity and quality of data needed to support compliance decisions. DQOs are used to develop a scientific and resource-effective data collection design.

**DQO Process:** A strategic planning approach based on the Scientific Method that is used to prepare for a data collection activity. The DQO process provides a systematic procedure for defining the criteria that a data collection design should satisfy, including when to collect samples, where to collect samples, the tolerable level of decision errors for the study, and how many samples to collect. By using the DQO process, DOE will assure that the type, quantity, and quality of environmental data used in decision making will be appropriate for the intended application. In addition, DOE will guard against committing resources to data collection efforts that do not support a defensible decision. The DQO process consists of seven steps and is more fully described in the U. S. Environmental Protection Agency, 1996, *Test Methods for Evaluating Solid Waste, SW-846*, or equivalent.

**Design Basis:** Information that identifies the specific functions to be performed by items and the specific values or ranges of values chosen for controlling parameters as reference bounds for design.

**Design Input:** Those criteria, parameters, bases, or other design requirements upon which the detailed final design is based.

**Design Output:** Drawings, specifications, and other documents resulting from the translation of design input requirements.

**Design Process:** The technical process that begins with the identification of design input and ends with the issuance of design output documents.

**Design Review:** A documented evaluation of design output during the design process to determine the design adequacy and the conformance to specified acceptance criteria.

**Disposal System:** Any combination of engineered and natural barriers that isolate transuranic waste after disposal. For the purposes of the WIPP, this will include the combination of the repository/shaft system and the controlled area.

**Document:** Written or pictorial information that describes, specifies, reports, or certifies activities, requirements, procedures, or results.

**Document Control:** The process that provides for document adequacy review, approval for release by authorized personnel, and distribution for use at the prescribed work locations.

**Error:** A discrepancy between a computed, observed, or measured value or condition and the true, specified, or theoretically correct value or condition.

**Graded Approach:** The process by which the level of analysis, documentation, verification, and other controls necessary to comply with QA program requirements are developed commensurate with specified factors.

**Independent Assessment:** An assessment of activities conducted by a group or organization having authority and freedom from the line organization to evaluate the scope, status, adequacy, programmatic implementation, or effectiveness of a program or process which they do not currently perform, supervise, or have direct responsibility for performing. Independence is determined based on an individual having no bias, rather than on organizational affiliation.

**Item:** An all-inclusive term used in place of appurtenance, assembly, component, equipment, material, module, part, structure, product, software, subassembly, subsystem, system, unit, or support systems.

**Lead Auditor:** An individual trained, qualified, and certified to organize and direct an audit, report audit findings, and evaluate corrective actions.

**Lifetime Records:** Records required to be maintained for the useful life of the items to which they pertain while the items are installed in the plant or facility (life of the item), or for the lifetime of the equipment, facilities, or programs to which the records apply.

**Line Management:** Those management positions that are directly responsible for task products and services. Includes CBFO supervisors and team leaders and contractor management within the context of the definition.

**Line Organization:** The organization directly responsible for task products and services. Includes CBFO offices and teams and contractor organizations within the context of the definition.

**Macro:** Single computer instructions invoked by a symbol, name, or key that represents commands, actions, or keystrokes.

**Management Assessment:** A periodic introspective self-analysis, conducted by management, to evaluate management systems, processes, and programs ensuring the organization's work is properly focused on achieving desired results.

**Measuring and Test Equipment:** All devices used to calibrate, measure, gage, test, inspect, or otherwise determine compliance with prescribed technical requirements.

**Nonconformance:** A deficiency in a characteristic or record that renders the quality of an item or sample unacceptable or indeterminate.

**Nonpermanent Records:** Records having value for a specific, limited time and authorized by the National Archives and Records Administration to be destroyed after that time.

**Nonreactor Nuclear Facility:** Facilities, activities or operations that involve, or will involve, radioactive and/or fissionable materials in such form and quantity that a nuclear or a nuclear explosive hazard potentially exists to workers, the public, or the environment, but does not include accelerators and their operations and does not include activities involving only incidental use and generation of radioactive materials or radiation such as check and calibration sources, use of radioactive sources in research and experimental and analytical laboratory activities, electron microscopes, and X-ray machines.

**Participant:** A DOE contractor or funded organization that furnishes items or services in support of CBFO-sponsored programs, including those TRU waste generator and storage sites characterizing waste for shipment to WIPP.

**Peer:** A person having technical expertise in the subject matter to be reviewed to a degree at least equivalent to that needed for the original work.

**Peer Review**: A documented, critical review performed by peers who are independent of the work being reviewed. A peer review is an in-depth critique of assumptions, calculations, extrapolations, alternate interpretations, methodology, and acceptance criteria employed, and of conclusions drawn in the original work. Peer reviews confirm the adequacy of work.

**Periodic:** Occurring or recurring at regular intervals. For the purposes of this QAPD, these intervals are determined by the responsible management unless otherwise specified.

**Post-Closure QA Records:** QA records required to be maintained beyond the operating life of the WIPP repository, for periods of several hundreds of years, and in a manner that would permit future generations to maintain them longer, if desired, using present reasonably available technology.

**Procedure:** A document that specifies or describes how an activity is to be performed. The term "procedure" may also include instructions and drawings.

**Process:** A series of actions that achieve an end or result.

**Procurement Documents:** Purchase orders, contracts, specifications, or other documents used to define technical and quality assurance requirements for the procurement of items or services.

**Qualification (Personnel):** The characteristics or abilities gained through education, training, or experience, as measured against established requirements such as standards or tests that qualify an individual to perform a required function.

**Qualification Testing:** A test that is intended to provide a desired level of confidence that an item meets specified criteria.

**Quality:** The condition achieved when an item, service, or process meets or exceeds the user's requirements and expectations.

**Quality Assurance:** All those planned and systematic actions necessary to provide adequate confidence that an item will perform satisfactorily in service.

**Quality Assurance Objectives:** Objectives that represent the required quality of data necessary to draw valid conclusions regarding program objectives.

**Quality Assurance Program:** The program established to assign responsibilities and authorities, define policies and requirements, and provide for the performance and assessment of work.

**Quality Assurance Record:** A completed record or any authenticated portion of a record that provides objective evidence of the quality of items or activities.

**Records:** Books, papers, maps, photographs, machine readable materials or other documentary materials, regardless of physical form or characteristics, made or received by an agency of the United States Government under Federal law or in connection with the transaction of public business and preserved or appropriate for preservation by that agency or its legitimate successor as evidence of the organization, functions, policies, decisions, procedures, operations or other activities of the government or because of the informational value of the data they contain.

**Records Archive:** A CBFO records storage facility meeting regulatory requirements for the storage of inactive records pending their final disposition.

**Repair:** The process of restoring an item to a condition such that the capability of an item to function reliably and safely is unimpaired even though that item still does not conform to the original requirement.

**Rework:** The process by which an item is restored to original specifications by completion or correction.

**Safety:** An all-inclusive term used synonymously with environment, safety, and health to encompass protection of the public, the workers, and the environment.

#### Safety Software: Includes the following:

- (1) Safety System Software. Software for a nuclear facility that performs a safety function as part of a structure, system, or component and is cited in either (a) a DOE approved documented safety analysis or (b) an approved hazard analysis.
- (2) Safety and Hazard Analysis Software and Design Software. Software that is used to classify, design, or analyze nuclear facilities. This software is not part of a structure, system, or component (SSC) but helps to ensure the proper accident or hazards analysis of nuclear facilities or an SSC that performs a safety function.
- (3) Safety Management and Administrative Controls Software. Software that performs a hazard control function in support of nuclear facility or radiological safety management programs or technical safety requirements or other software that performs a control function necessary to provide adequate protection from nuclear facility or radiological hazards. This software supports eliminating, limiting, or mitigating nuclear hazards to workers, the public, or the environment.

**Sample:** A subset of a population (e.g., wastes, environmental media, materials, cores) whose properties are used to gain information about the population.

**Scientific Investigation:** Any research, experiment, test, study, or activity that is performed for the purpose of investigating a natural system or the man-made aspects of a geologic repository, including the investigations that support design of the facilities and the waste package.

**Scientific Notebook:** A record of the methods and results of scientific investigations that is used when the work involves a high degree of professional judgment or trial and error methods, or both.

**Service:** The performance of work, such as design, construction, fabrication, inspection, nondestructive examination, testing, environmental qualification, equipment qualification, repair, installation, waste characterization/certification, waste disposal/isolation, management and operation of the WIPP or similar activities.

Significant Condition Adverse to Quality: See Condition Adverse to Quality.

**Site Characterization:** The program of exploration and research both in the laboratory and the field that is undertaken to establish the natural conditions and the ranges of parameters of a particular site.

**Software:** Computer programs, procedures, rules, and associated documentation and data pertaining to the operation of a computer system.

**Software Baseline:** An item or product that has been formally reviewed and agreed upon, that serves as the basis for further development, and that can be changed only through formal change control procedures.

**Software Quality Assurance Plan:** A plan for the development of software products necessary to provide adequate confidence that the software conforms to established requirements.

**Software Tool:** A program that is employed in the development, repair, maintenance, test, analyze, or enhancement of other programs or of hardware. Software tools may include modules within a software application that allow the user to specify or set user preferences, set-points, and operating parameters. Including but not limited to a set of software tools that address only the essential needs during program development (e.g. text editors, compilers, link loaders, and debug tools) and concentrate solely on the program production phase normally provided by a program development system.

Software tools can also assist in all activities of all phases of the software life cycle, including planning, development, management, life-cycle documentation, and application of quality assurance including specification of requirements, design, validation, configuration control, and project management (time-line management and deliverable scheduling).

**Software Validation:** The process of test and evaluation of the completed software to ensure compliance with software requirements.

**Software Verification:** The process of determining whether or not the product of a given phase of the software development cycle fulfills the requirements imposed by the previous phase.

**Software Verification and Validation:** The process of determining whether the requirements for a system or component are complete and correct, the products of each development phase fulfill the requirements or conditions imposed by the previous phase, and the final system or component complies with specified requirements.

**Source Verification:** A purchaser method of accepting an item or related service from a supplier by monitoring, auditing, surveillance, witnessing, or observing activities performed by the supplier.

**Special Process:** A process, the results of which are highly dependent on the control of the process or the skill of the operators, or both, and in which the specified quality cannot be readily determined by inspection or test of the product.

**Supplier:** Any individual or organization who furnishes items or services in accordance with a contract. An all-inclusive term used in place of any of the following: vendor, seller, source, participant, contractor, or subcontractor.

**Surveillance:** The act of monitoring or observing to verify whether an item, activity, system, or process conforms to specified requirements. Surveillance of a technical work activity is normally done in real time (i.e., the surveillance is accomplished as the work is being performed).

**Suspect/Counterfeit Item (S/CI):** An item is suspect when inspection or testing indicates that it may not conform to established Government or industry-accepted specifications or national consensus standards or whose documentation, appearance, performance, material, or other characteristics may have been misrepresented by the supplier or manufacturer. A counterfeit item is one that has been copied or substituted without legal right or authority or whose material, performance, or characteristics have been misrepresented by the supplier or manufacturer. Items that do not conform to established requirements are not normally considered S/CIs if nonconformity results from one or more of the following conditions (which must be controlled by site procedures as nonconforming items):

- (1) defects resulting from inadequate design or production quality control;
- (2) damage during shipping, handling, or storage;
- (3) improper installation;
- (4) deterioration during service;
- (5) degradation during removal;
- (6) failure resulting from aging or misapplication; or
- (7) other controllable causes.

**System Software:** Software which is used exclusively in the preparation, installation, or operation of executable software applications. Examples of such software include operating systems, administrative and management systems, system utilities, compilers, assemblers, translators, interpreters, automated protocols, utilities and tools, teleprocessing managers, and query languages.

**Technical Review:** A documented critical review of work that has been performed within the state of the art. The review is accomplished by one or more qualified reviewers who are independent of the work but collectively have equivalent technical expertise to those who performed the original work. The review is an in-depth analysis and evaluation of documents, activities, material, data, or items that require technical verification or validation for applicability, correctness, adequacy, completeness, and assurance that established requirements are satisfied.

**Technical Specialist:** An individual assigned to an assessment team when the scope, complexity, or special nature of the work to be examined warrants assessment of the technical adequacy of the work or the effectiveness of the technical process.

**Testing:** An element of verification to determine the capability of an item to meet specified requirements or processes that facilitate the collection of data in conducting scientific investigations by subjecting the item or environment to a set of physical, chemical, environmental, or operating conditions.

**Traceability:** The ability to trace the history, application, and location of an item, data, or sample using recorded documentation. As related to metrology, traceability means the ability to relate individual measurement results through an unbroken chain of calibrations to one or more of the following:

- U.S. national standards maintained by National Institute of Standards and Technology or the U.S. Naval Observatory
- Fundamental or natural physical constants with values assigned or accepted by the National Institute of Standards and Technology
- National standards of other countries which are correlated with the National Institute of Standards and Technology

**Transuranic (TRU) Waste:** Waste containing more than 100 nCi of alpha-emitting TRU isotopes per gram of waste, with half-lives greater than 20 years, except for (1) high-level radioactive waste, (2) waste that the Secretary has determined, with the concurrence of the Administrator, does not need the degree of isolation required by the disposal regulations, or (3) waste that the NRC has approved for disposal on a case-by-case basis in accordance with 10 CFR § 61, *Licensing Requirements for Land Disposal of Radioactive Waste*.

**TRU Mixed Waste:** TRU waste that is also a hazardous waste as defined by the Hazardous Waste Act and 20 NMAC 4.1.200 (incorporating 40 CFR § 261.3).

**Use As Is:** A disposition permitted for a nonconforming item when it can be established that the item is satisfactory for its intended use.

**Validation:** An activity that demonstrates or confirms that a process, item, data set, or service satisfies the requirements defined by the user.

**Verification:** The act of reviewing, inspecting, testing, checking, auditing, or otherwise determining and documenting whether items, processes, services, or documents conform to specified requirements.

**Waiver:** Documented authorization to depart from specified requirements.

**WIPP:** The Waste Isolation Pilot Plant, as authorized pursuant to Section 213 of the Department of Energy National Security and Military Applications of Nuclear Energy Authorization Act of 1980 (Pub. L. 96-164; 93 Stat. 1259, 1265) to provide a research

and development facility for demonstrating the safe disposal of radioactive wastes produced by national defense activities.

**Work:** The process of performing a defined task or activity, for example, research and development, operations, maintenance and repair, administration, software development and use, inspection, safeguards and security, data collection, and analysis.

**Work Suspension:** A formal directive issued by management that work must be stopped until the related significant condition adverse to quality or nonconformance has been resolved.

#### **APPENDIX B - REFERENCES**

ASME NQA-1-2008 with NQA-1a-2009 addenda, *Quality Assurance Requirements for Nuclear Facility Applications*.

10 CFR Part 21, Reporting of Defects and Noncompliance

10 CFR Part 71, Packaging and Transportation of Radioactive Material, Subpart H, Quality Assurance

10 CFR Part 830, Nuclear Safety Management

40 CFR Part 191, Environmental Radiation Protection Standards for Management and Disposal of Spent Nuclear Fuel, High-Level and Transuranic Radioactive Wastes

40 CFR Part 194, Criteria for the Certification and Re-Certification of the Waste Isolation Pilot Plant's Compliance with 40 CFR Part 191 Disposal Regulations

DOE/CBFO-14-3540, Quality Assurance Implementation Plan and Requirements Flow Down

DOE O 226.1B, Implementation of Department of Energy Oversight Policy

DOE O 232.2A, Occurrence Reporting and Processing of Operations Information

DOE O 243.1C, Records Management Program

DOE O 414.1D, Quality Assurance

DOE O 460.1D, Hazardous Materials Packaging and Transportation Safety

DOE G 414.1-2B, Admin Change 2, Quality Assurance Program Guide

DOE G 414.1-4, Safety Software Guide for Use with 10 CFR 830 Subpart A, Quality Assurance Requirements, and DOE O 414.1C, Quality Assurance

EM-QA-001, DOE Office of Environmental Management (EM) Quality Assurance Program

DOE-HDBK-1230-2019, Commercial Grade Dedication Application Handbook

DOE-STD-1150-2013, Quality Assurance Functional Area Qualification Standard

DOE-STD-1172-2011, Safety Software Quality Assurance Functional Area Qualification Standard

U.S. Department of Energy Office of Environmental Safety and Quality Guidance for Commercial Grade Dedication

Waste Isolation Pilot Plant Hazardous Waste Facility Final Permit, EPA No. NM4890139088

DOE/WIPP-02-3122, Transuranic Waste Acceptance Criteria for the Waste Isolation Pilot Plant

ASME NQA-1-1989, Quality Assurance Program Requirements for Nuclear Facilities

ASME NQA-2a-1990 addenda, Part 2.7, Quality Assurance Requirements of Computer Software for Nuclear Facility Applications

ASME NQA-3-1989, Quality Assurance Program Requirements for the Collection of Scientific and Technical Information for Site Characterization of High-Level Nuclear Waste Repositories

National Fire Protection Association (NFPA) Standard 232-1986, Standard for the Protection of Records

ASME NQA-1–2008, Subpart 2.14, Quality Assurance Requirements for Commercial Grade Items and Services

ASME NQA-1-2019, Quality Assurance Program Requirements for Nuclear Facility Applications

M-19-21, Transition to Electronic Records, Memorandum for Heads of Executive Departments and Agencies, Office of Management and Budget, dated 6-28-2019

NUREG-1297 (1988), Peer Review for High-Level Nuclear Waste Repositories

NUREG/BR-0167 (1993), Software Quality Assurance Program and Guidelines

SNT-TC-1A, Current Revision, The American Society of Nondestructive Testing (ASNT) Recommended Practice, *Personnel Qualification and Certification in Nondestructive Testing* 

TRUPACT-II Certificate of Compliance, NRC Certificate Number 9218

TRUPACT-III Certificate of Compliance, NRC Certificate Number 9305

HalfPACT Certificate of Compliance, NRC Certificate Number 9279

RH 72-B Certificate of Compliance, NRC Certificate Number 9212

10-160B Certificate of Compliance, NRC Certificate Number 9204

# APPENDIX C – CBFO ORGANIZATION, RESPONSIBILITIES, AND INTERFACES

Effective implementation of the CBFO QA program is dependent on efforts at all CBFO levels. The CBFO organization is structured such that those assigned responsibility for performing the work are responsible for achieving and maintaining quality. Management is responsible for defining quality, developing appropriate plans to attain quality, and providing support of the workers in pursuit of quality. Persons or organizations not directly responsible for performing the work verify quality achievement. Management empowers employees by delegating authority and decision making to the lowest appropriate level in the organization.

The CBFO Manager is responsible for overall implementation of DOE programs, policies, orders, and guidance pertaining to TRU waste disposal at WIPP. As such, the CBFO Manager provides policy direction and oversight of activities that affect TRU waste characterization and grants DOE waste certification authority to the TRU waste sites. This responsibility includes policy direction and oversight for waste characterization, certification, packaging, and transportation activities at participating sites. Overall responsibility for the development and implementation of the CBFO QA program belongs to the CBFO Manager. Authority for execution of the QA function, which ensures effective implementation, is delegated to the Director of the CBFO Quality Assurance Division in accordance with the allowable delegations as defined by EM.

The Assistant Manager of the CBFO Office of the National TRU Program Waste Certification and Disposal is responsible for TRU waste characterization, certification, and loading and for ensuring that program requirements are met with regard to TRU waste testing, sampling, analysis, sample handling and custody, associated data management, and waste transportation.

The CBFO Deputy Manager, Office Directors, and Assistant Managers are responsible for planning, organizing, directing, controlling, and evaluating those activities in their area of responsibility that support the CBFO mission and implement the QAPD. Their responsibilities include, but are not limited to:

- Ensuring that adequate technical and QA training is provided for personnel performing activities important to the satisfaction of CBFO organizational and quality objectives
- Ensuring compliance with all applicable regulations, DOE orders, applicable state and local laws, and other requirements applicable to the CBFO programs
- Ensuring that personnel adhere to procedures for the generation, identification, control, and protection of QA records

- Exercising the authority and responsibility to stop unsatisfactory work such that cost and schedule do not override environmental, safety, health, or quality considerations
- Developing, implementing, and maintaining plans, policies, and procedures that implement the QAPD
- Identifying, investigating, reporting, and correcting conditions adverse to quality

Each CBFO employee, including contractor personnel working to CBFO procedures, is responsible for the quality of his or her work and for promptly reporting all existing, developing, or potential conditions adverse to quality to the responsible management for evaluation and action.

Organizations at all management levels shall establish communication channels that provide timely, routine, and wide dissemination of information pertinent to quality performance.

Where more than one CBFO organization is involved in the execution of activities covered by the QAPD, the responsibility and authority of each organization shall be clearly established and documented. The internal interfaces between organizational units are depicted in CBFO organizational charts. The CBFO external interfaces include other DOE elements, CBFO program participants, suppliers, the Environmental Protection Agency, Nuclear Regulatory Commission, and the New Mexico Environment Department.

# APPENDIX D – RESPONSIBILITIES OF THE DIRECTOR OF THE CBFO QUALITY ASSURANCE DIVISION

The CBFO Manager has overall responsibility for the CBFO QA program. Authority for execution of the CBFO QA function, including the independent verification of effective implementation, is delegated to the Director of the CBFO Quality Assurance Division in accordance with the allowable delegations as defined by EM-1. It is the policy of the CBFO to grant the CBFO QA organization sufficient authority, freedom, and access to all work areas to:

- Identify quality problems
- Recommend solutions
- Verify implementation of solutions
- Ensure that unsatisfactory conditions are controlled until proper disposition has occurred

The Quality Assurance Division shall:

- Have direct access to responsible management at a level where appropriate action can be affected
- Be sufficiently independent from cost and schedule considerations
- Have the organizational freedom to communicate with management
- Have the authority and responsibility to stop unsatisfactory work such that cost and schedule do not override environmental, safety, or health considerations
- Have no other assigned responsibilities that would prevent adequate attention to quality assurance matters

The Director of the CBFO Quality Assurance Division has the authority and overall responsibility to independently assess the effective implementation of the CBFO QAPD, both within the CBFO organization and in those participant organizations supporting the CBFO.

The Director of the CBFO Quality Assurance Division has the following additional authorities and responsibilities:

- The organizational freedom to communicate with management
- Scheduling and conducting independent QA assessments, including WIPP core participant organizations

- Scheduling and conducting audits of activities related to waste generating site certification when notified by the Director of the CBFO Office of National TRU Program Waste Certification and Disposal that the waste generating site is ready
- Scheduling and conducting recertification audits and surveillances of waste generating sites
- Preparing, as appropriate, and reviewing internal procedures that implement the provision of the QAPD
- Tracking, performing trend analysis, and reporting quality problem areas
- Developing, establishing, and interpreting the CBFO QA policy and ensuring effective implementation
- Preparing, issuing, and maintaining the CBFO QAPD
- Interfacing with the CBFO staff, participants, and other stakeholders on quality assurance matters
- Reviewing QA plans, including participant Quality Assurance Project Plans
- Performing adequacy reviews of QA program documents
- Certifying all CBFO lead auditors and qualifying auditors and technical specialists
- Assuring the independence of lead auditors, auditors, and technical specialists

# APPENDIX E – TRU WASTE CHARACTERIZATION AND CERTIFICATION ORGANIZATIONAL AND INDIVIDUAL RESPONSIBILITIES

### 1. <u>Assistant Manager, Office of the National TRU Program Waste Certification and Disposal</u>

Manages the National TRU Program and executes program functions related to characterization of waste for disposal at the WIPP. Manages activities that prepare waste sites for certification and notifies the Director of the CBFO Quality Assurance Division when new sites are ready for independent audit. Also manages WIPP CBFO functions associated with International and Scientific TRU Programs, the Security Program, the WIPP Program, the day-to-day site operations, infrastructure development, and physical and cyber security of the WIPP facilities. There are three Divisions reporting to this Assistant Manager: National TRU Program Certification Division, National TRU Program Operations Division, and Site Operations and Infrastructure Division.

#### 2. Assistant Manager, Office of Environment, Safety, Health, and Quality Assurance

Responsible for the oversight of industrial, radiological, mining, and nuclear safety, facility engineering waste operations, fire protection, emergency management, regulatory compliance, quality assurance activities at the WIPP, management, program support, including independent oversight of select programs in the area of environmental monitoring, land management, and environmental regulatory compliance. There are five divisions reporting to this Assistant Manager: Safety Programs Division, Safety Systems Oversight Division, Environmental Regulatory Compliance Division, Facility Oversight Division, and the Quality Assurance Division.

#### 3. Director of the CBFO Quality Assurance Division

Responsible for the overall implementation and effectiveness of the QA program as delegated and outlined in Appendix D.

#### 4. <u>Director of the CBFO Office of Business Operations</u>

Oversees financial and contractual aspects of waste characterization and certification activities. Responsible for oversight and implementation of information management/technology, software management, records management, document control, procurement, budget planning and analysis, human resources, and contract management for the CBFO. There are two divisions reporting to this Office Director: Business Operations and Budget and Contracts Divisions.

#### 5. DOE Site Offices

Responsible for ensuring that the requirements of the Quality Assurance Project Plans (QAPjPs) are in compliance with all DOE orders and that the resources and funding are available to accomplish program activities. Provide liaison between the site contractors and the CBFO.

#### 6. TRU Waste Sites

Each participating site shall develop and implement a QAPjP that demonstrates compliance with and implementation of WIPP TRU waste characterization requirements and the applicable requirements of the WIPP HWFP and its associated Waste Analysis Plan. These QAPjPs shall include or reference the appropriate management and technical criteria of the program, as well as qualitative or quantitative criteria for determining that program activities are being satisfactorily performed. The QAPjPs shall identify the organizations and positions responsible for their implementation. The QAPjPs shall also reference site-specific documentation that details how each of the required elements of the program will be performed. The QAPjPs and subsequent revisions must be reviewed for concurrence by the site project manager, site project QA manager, the cognizant DOE site office, the Director of the CBFO Office of National TRU Program Waste Certification and Disposal, and the Director of the CBFO Quality Assurance Division.

Prior to the implementation of program activities at participating sites, standard operating procedures (SOPs) will be developed for all activities affecting program quality that require written instructions or procedures. For the purposes of the program, the term SOP refers to any site-specific implementing document. Compliance with SOPs will ensure that tasks are performed in a consistent manner that results in achieving the quality required for the program. The organization, format, content, and designation of SOPs must be described in the QAPiPs.

#### 7. <u>Site Project Manager</u>

Each participating site's contractor designates a site project manager to oversee characterization program activities at the site. A description of the site project manager's role in relation to the other organizational functions at the site must be included in the site's QAPjP. The site project manager (or designee) reviews and recommends approval of the site QAPjP and subsequent revisions before it is submitted to the CBFO for review. Specific program responsibilities assigned to the site project manager include the following:

- Waste selection and tracking
- Data validation/verification
- Data reconciliation with DQOs

- Assignment of EPA Hazardous Waste Numbers
- QA/QC reports to DOE site office
- Data transmission to the CBFO

#### 8. <u>Site Project Quality Assurance Management</u>

Each participating site's contractor designates a site project QA manager. The site project QA manager shall have the responsibilities and authorities described in section 1.1.1.3 of this QAPD. This individual will have the authority to stop program activities at a participating site if quality is not assured or controlled.

The site project QA manager shall summarize all relevant information on the QA/QC activities during the period in a semiannual report. This semiannual report shall be distributed to the DOE site office and the site project manager at the same time. The site project manager shall review the report, comment if appropriate, and then forward a copy of the report with comments to the DOE site office.

#### 9. Site Waste Certification Official

Each participating site's contractor designates a waste certification official who must document and certify that all TRU waste payload containers prepared for shipment to WIPP meet all the requirements specified in the *Transuranic Waste Acceptance Criteria for the Waste Isolation Pilot Plant*, and transmit the waste certification data to the WIPP M&O contractor.

#### 10. Site Transportation Certification Official

Each participating site's contractor designates a transportation certification official who documents and certifies that payload assemblies for shipment to WIPP meet all the requirements of the Contact-Handled Transuranic Waste Authorized Methods for Payload Control, the TRUPACT-III TRU Waste Authorized Methods for Payload Control, and the Remote-Handled Transuranic Waste Authorized Methods for Payload Control, as applicable.